


TI-80 Graphic Calculator

USER MANUAL







TI-80

OWNER'S MANUAL

Copyright © 1985 by Texas Instruments Incorporated.

IBM is a registered trademark of International Business Machines Corporation.
Macintosh is a registered trademark of Apple Computer, Inc.

Important

Texas Instruments makes no warranty, either expressed or implied, including but not limited to any implied warranties of merchantability and fitness for a particular purpose, regarding any programs or book materials and makes such materials available solely on an "as-is" basis.


In no event shall Texas Instruments be liable to anyone for special, collateral, incidental, or consequential damages in connection with or arising from the purchase or use of these materials, and the sole and exclusive liability of Texas Instruments, regardless of the form of action, shall not exceed the purchase price of this equipment. Moreover, Texas Instruments shall not be liable for any claim of any kind whatsoever against the use of these materials by any other party.

Caution: Any changes or modifications to this equipment not expressly approved by Texas Instruments may void your authority to operate the equipment.

TEXAS INSTRUMENTS

WARRANTY CARD

TWO (2) YEAR WARRANTY

Name : Profession : Address :	Model : TI-80 Date of purchase :
Telephone : <ul style="list-style-type: none">- Warranty is accepted if this card is correctly filled in by the retailer; stamp & date of purchase are required. If these are missing, you must send in the invoice or your receipt proving the purchase.).- To simplify your return and expedite its processing, please complete the other side of this card. <p style="text-align: right;">Thank you</p>	 RETAILER'S STAMP

ANY DAMAGE TO THE DISPLAY IS NOT
COVERED BY WARRANTY.

IN CASE OF DIFFICULTY

In case of difficulty, please carefully read the information in your manual, calculator and duplicate examples. Please also refer to the section "In Case of Difficulty":

1. In case of difficulty with the display (blank display or digits and graphs do not appear), check the display contrast: Press **[2/3]** to switch the calculator on. Press then release the 2nd. Press and hold the **[<]** or **[>]** cursor keys to adjust the contrast.
2. In case of erratic functioning or erratic display, reset your calculator. Press **[2/3]** [OFF] then **[2/3]** to switch the calculator on. Press then release **[2/3]**, then **[M+]**. Press **[3]** (RESET), then press **[3]** (RESET). Then adjust the contrast (see 1).
3. Checking the batteries: try again with new batteries.

Warning: battery replacement is not covered by warranty.

REASON FOR RETURN

DISPLAY ☐ Dark ☐ No display ☐ Other

Describe the problem :

KEYBOARD

Indicate which keys are not working :

RANDOM FUNCTIONING : Wrong calculations, wrong display...

Please give some examples :

OTHERS :

Please specify :

This manual describes how to use the TI-80 Graphics Calculator. *Getting Started* gives a quick overview of its features. The first chapter gives general instructions on operating the TI-80. Other chapters describe its interactive features. The applications in Chapter 11 show how to use these features in combination.

	Using this Guidebook Effectively	viii
	Glossary	x
Getting Started: Do This First!	TI-80 Keyboard	2
	First Steps	3
	TI-80 Menus	4
	Entering a Calculation: Compound Interest	5
	Continuing a Calculation	6
	Defining a Function: Box, with Lid	7
	Defining a Table of Values	8
	Zooming In on the Table	9
	Changing the Viewing Window	11
	Displaying and Tracing the Graph	12
	Zooming In on the Graph	13
	Other TI-80 Features	14
Chapter 1: Operating the TI-80	Turning the TI-80 On and Off	1-2
	Setting the Display Contrast	1-3
	The Display	1-4
	Entering Expressions and Instructions	1-6
	The Edit Keys	1-8
	Setting Modes	1-9
	TI-80 Modes	1-10
	Variable Names	1-12
	Storing and Recalling Variable Values	1-13
	Last Entry	1-14
	Last Answer	1-16
	TI-80 Menus	1-17
	The VARS and Y-VARS Menus	1-19
	EOS (Equation Operating System)	1-20
	Error Conditions	1-22

Chapter 2: Math, Angle, and Test Operations	Getting Started: Lottery Chances	2-2
	Using the TI-80 Functions	2-3
	Keyboard Math Operations	2-4
	MATH MATH Operations	2-7
	MATH NUM (Number) Operations	2-10
	MATH PRB (Probability) Operations	2-12
	ANGLE Operations	2-14
Chapter 3: Fractions	TEST (Relational) Operations	2-16
	Getting Started: Working with Fractions	3-2
	Setting Modes for Fraction Results	3-4
	Entering and Using Fractions in Calculations	3-5
Chapter 4: Function Graphing	The FRACTION Menu	3-6
	Getting Started: Graphing a Circle	4-2
	Defining a Graph	4-3
	Setting Graph Modes	4-4
	Defining Functions in the Y= List	4-5
	Evaluating Y= Functions in Expressions	4-7
	Selecting Functions	4-8
	Defining the Viewing Window	4-9
	Displaying a Graph	4-11
	Exploring a Graph with the Free-Moving Cursor	4-12
	Exploring a Graph with TRACE	4-13
	Exploring a Graph with ZOOM	4-15
Chapter 5: Parametric Graphing	Setting the Zoom Factors	4-18
	Getting Started: Path of a Ball	5-2
	Defining and Displaying a Parametric Graph	5-3
	Exploring a Parametric Graph	5-6

Chapter 6: Tables	Getting Started: Rows of a Function	6-2
	Defining the Independent Variable	6-3
	Defining the Dependent Variable	6-4
	Displaying the Table	6-5
Chapter 7: Draw Operations	Getting Started: Shading a Graph	7-2
	DRW: DRAW Menu	7-3
	Drawing Lines	7-4
	Drawing Horizontal and Vertical Lines	7-5
	Drawing a Function	7-6
	Shading Areas on a Graph	7-7
	Drawing Points	7-10
	Clearing a Drawing	7-11
Chapter 8: Lists	Getting Started: Generating a Sequence	8-2
	About Lists	8-3
	LIST OPS Operations	8-5
	LIST MATH Operations	8-9
Chapter 9: Statistics	Getting Started: Building Height and City Size	9-2
	Setting Up a Statistical Analysis	9-6
	The STAT List Editor	9-9
	Viewing, Fixing, and Editing Lists	9-10
	Sorting and Clearing Lists	9-15
	Statistical Analysis	9-16
	Types of Statistical Analysis	9-15
	Statistical Variables	9-17
	Statistical Plotting	9-18
	Statistical Analysis in a Program	9-22
	Statistical Plotting in a Program	9-23

Table of Contents (Continued)

Chapter 10: Programming	Getting Started: Rolling a Die	10-2
	About TI-80 Programs	10-4
	Creating and Executing Programs	10-5
	Editing Programs	10-6
	PRGM CTL (Control) Instructions	10-7
	PRGM IO (Input/Output) Instructions	10-11
	Calling Other Programs	10-14
 Chapter 11: Applications	 Probability Experiments: Coins, Dice, and Spinners	 11-2
	The Unit Circle and Trigonometric Curves	11-3
	Program: Newton's Numerical Solve Routine	11-4
	Program: Numerical Integration	11-6
	Program: Window Variables Store and Recall	11-8
	Graphing the Inverse of a Function	11-10
	Graphing a Piece-by-Piece Function	11-12
	Graphing Inequalities	11-14
	Graphing a Polar Equation	11-15
	Program: Guess the Coefficients	11-16
 Chapter 12: Memory Management	 Checking Available Memory	 12-2
	Deleting Items from Memory	12-3
	Resetting the TI-80	12-4

Appendix A:	Table of TI-80 Functions and Instructions	A-2
Tables and	Menu Map	A-20
Reference	TI-80 Variables	A-26
Information		
Appendix B:	Battery Information	B-2
Service and	Accuracy Information	B-8
Warranty	In Case of Difficulty	B-10
Information	Free Conditions	B-11
	Two-Year Limited Warranty	B-14

Index

Using this Guidebook Effectively

The structure of the TI-80 guidebook and the design of its pages can help you find the information you need, quickly. Consistent presentation techniques are used throughout to make the guidebook easy to use.

Structure of the Guidebook

The guidebook is designed to teach you how to use the calculator.

- Getting Started is a fast-paced, key-stroke-by-key-stroke introduction.
- Chapter 1 describes general operations and lays the foundations for Chapters 2 to 10, which describe specific functional areas of the TI-80. Most chapters begin with a brief Getting Started introduction.
- Chapter 11 contains application examples that incorporate features from different functional areas of the calculator. These examples can help you see how different functional areas work together to accomplish meaningful tasks.
- Chapter 12 describes memory management.


Page-Design Conventions

When possible, units of information are presented on a single page or on two facing pages. Several page-design elements help you find information quickly.

- **Page headings**—The descriptive heading at the top of the page or two-page unit identifies the subject of the unit.
- **General text**—Just below the page heading, a short section of bold text provides general information about the subject covered in the unit.
- **Left-column subheadings**—Each subheading identifies a specific topic or task related to the page or unit subject.
- **Specific text**—The text to the right of a subheading presents detailed information about that specific topic or task. The information may be presented as paragraphs, numbered procedures, bulleted lists, or illustrations.
- **Page “footers”**—The bottom of each page shows the chapter name, chapter number, and page number.

Information-Mapping Conventions

Several conventions are used to present information concisely and in an easily referenced format:

- **Numbered procedures**—A procedure is a sequence of steps that performs a task. In this guidebook, each step is numbered in the order in which it is performed. No other text in the guidebook is numbered; therefore, when you see numbered text, you know you should perform the steps sequentially.
- **Lists with bullets**—If several items have equal importance, or if you may choose from one of several alternative actions, this guidebook provides each item with a “bullet” (•) to highlight it—like this list.
- **Tables and charts**—Sets of related information are presented in tables or charts for quick reference.
- **Keystroke examples**—The Getting Started examples provide keystroke-by-keystroke instructions, as do the numerous short examples and several detailed examples, identified with a .

Reference Aids

Several techniques have been used to help you look up specific information when you need it. These include:

- A chapter table of contents on the first page of each chapter, as well as the full table of contents at the front of the guidebook.
- A glossary at the end of this section, defining important terms used throughout the guidebook.
- An alphabetical table of functions and instructions in Appendix A, showing their correct formats, how to access them, and page references for more information.
- Information about system variables in Appendix A.
- A table of error messages in Appendix B, showing the messages and their meanings and giving problem-handling information.
- An alphabetical index at the back of the guidebook, listing tasks and topics you may need to look up.

Glossary

This glossary provides definitions for important terms that are used throughout this guidebook.

Argument	An argument is an input item upon which the value of a function depends.
Command	A command is any entry submitted to the calculator using □ . There are two types of TI-80 command: instructions and expressions.
Expression	An expression is a complete sequence of numbers, variables, functions, and their arguments that can be evaluated to a single answer. An expression returns the evaluated result to Ans .
Function	<p>A function, which may have arguments, returns a value and can be used in an expression.</p> <p>A function is also the expression entered in the Y= editor used in graphing.</p>
Home Screen	The Home screen is the primary screen of the TI-80, where expressions can be entered and evaluated and instructions can be entered and executed.
Instruction	An instruction, which may have arguments, initiates an action. Instructions are not valid in expressions. An instruction does not return a value to Ans .
List	A list is a set of values that the TI-80 can use for activities such as evaluating a function at multiple values and entering statistical data.
Menu Item	Menu items are shown on full-screen menus.
Pixel	A pixel (picture element) is a square dot on the TI-80 display. The TI-80 display is 64 pixels wide and 48 pixels high.
Real Number	On the TI-80, real numbers are individual decimal or fraction values.
Value	A value is a single decimal or fraction number or a list of decimals or fractions.
Variable	A variable is the name given to a location in memory in which a value, an expression, a list, or another named item is stored.

Getting Started contains two keystroke-by-keystroke examples—an interest rate problem and a volume problem—which introduce you to some of the principal operating and graphing features on the TI-80. You will learn to use the TI-80 more quickly by completing both of these examples first.

Contents	TI-80 Keyboard	2
	First Steps	3
	TI-80 Menus	4
	Entering a Calculation: Compound Interest	5
	Continuing a Calculation	6
	Defining a Function: Box with Lid	7
	Defining a Table of Values	8
	Zooming In on the Table	9
	Changing the Viewing Window	11
	Displaying and Tracing the Graph	12
	Zooming In on the Graph	13
	Other TI-80 Features	14

First Steps

Before beginning the two sample problems, follow the steps on this page to reset the TI-80 to its factory settings. (Resetting the TI-80 erases all previously entered data.) This ensures that following the keystrokes in this section will produce the same actions.

1. Press **ON** to turn the calculator on.

If the screen is very dark or blank, adjust the display contrast. Press and release **CONTRAST**, and then press and hold **▲** to make the display lighter or press and hold **▼** to make the display darker. You can press **CLR** to clear the display.



Entering a Calculation: Compound Interest

The TI-80 displays up to 8 18-character lines so that you see an expression and its solution together. You can store values to variables, enter multiple instructions on one line, and recall previous entries.

By trial and error, determine when \$1000 invested at 6% annual compound interest will double in value.

- 1 For the first guess, calculate the amount available at the end of 10 years. Enter the expression just as you would write it:

Press $1000 \square \square 1.06 \square \square 10$



1000*1.06^10

- 2 Press $\square \square \square$ to evaluate the expression

The answer is shown on the right hand side of the display. The cursor is positioned on the next line, ready for you to enter the next expression



1000*1.06^10
1790.847697

- 3 The next guess should be greater than 10 years. Make the next guess 12 years. To calculate the amount after 12 years, press $1000 \square \square 1.06 \square \square 12$ followed by $\square \square \square$



1000*1.06^12
1790.847697
2012.196472

Continuing a Calculation

To save keystrokes, you can use the Last Entry feature to recall the last expression entered and then edit it for a new calculation. In addition, the next expression can be continued from the previous result.

- 1 The next guess should be less than, but close to 12 years. Calculate the amount available at the end of 11.9 years, using the Last Entry feature. Press $\boxed{\text{F2}}$, followed by $\boxed{\text{EDIT}}$ (the second function of $\boxed{\text{F7}}$).

The last calculated expression is shown on the next line of the display. The cursor is positioned at the end of the expression.

```
2000=1.04^12
1795.847697
2000=1.04^12
2862.196472
2000=1.04^11.9
2000.305716
```

- 2 You can edit the expression. Press $\boxed{\text{F2}}$ to move the cursor over the 2. Then type 1.9 to change 12 to 11.9. Press $\boxed{\text{F2}}$ to evaluate the expression.

Note: This process can be continued to obtain a solution with the desired accuracy.

```
2000=1.04^12
1795.847697
2000=1.04^12
2862.196472
2000=1.04^11.9
2000.305716
0
```

- 3 You can continue a calculation using the result of the last calculation. For example, if the final amount determined above is to be divided among seven people, how much would each person get?

To divide the last calculation by seven, press $\boxed{\text{F2}}$ 7, followed by $\boxed{\text{F7}}$.

As soon as you press $\boxed{\text{F2}}$, **ANS** is displayed at the beginning of the new expression. **ANS** is a variable that contains the last calculated result. In this case, **ANS** contains the variable 2000.305716 .

```
1795.847697
2000=1.04^12
2862.196472
2000=1.04^11.9
2000.305716
ANS/7
285.786799
0
```

Defining a Function: Box with Lid

Take an 21.0 cm \times 29.7 cm sheet of paper and cut X by X squares from two corners and X by $(X+B)$ rectangles from the other two corners. Now fold the paper into a box with lid. What X would give the maximum volume V of a box made in this way? Use tables and graphs to determine the solution.

Begin by defining a function that describes the volume of the box.

From the diagram $3X + A = W$
 $2X + 2B = L$
 $V = A \cdot B \cdot X$

Substituting $V = (W - 2X)(L/2) \cdot X$



If necessary, press **MODE** **[F1]** **[F2]** to change the **MODE** to **FLOAT**. Then press **2nd** **[Quit]** **[2nd]** **[F1]** to return to the Home screen and clear it.

- 1 Press **21** **[STO]** **[ALPHA]** **W** **[ENTER]** to store the width of the paper.

Press **29.7** **[STO]** **[ALPHA]** **L** **[ENTER]** to store the length of the paper.

W →	21
L →	29.7
X	

- 2 You can define functions for tables and graphs on the **Y=** edit screen.

Press **[Y=]** to access this screen.

Y1=	
Y2=	
Y3=	
Y4=	

- 3 Enter the function for volume as **Y1**. Press **[2nd]** **[F1]** **W** **[2nd]** **[F1]** **[2nd]** **[F1]** **L** **[2nd]** **[F1]** **[2nd]** **[F1]** **[ENTER]** to define function **Y1** in terms of **X**. **[2nd]** **[F1]** lets you quickly enter **X** without pressing **[ALPHA]**.

The **=** sign is highlighted to show that **Y1** is selected.

Y1=	(W-2X)(L/2)X
Y2=	
Y3=	
Y4=	

Defining a Table of Values

The table feature of the TI-80 provides numeric information about a function. Use a table of values from the previously defined function to estimate an answer to the problem.

1. Press **[2nd]** **[Table]** (above **[WINDOW]**) to display the **TABLE SETUP** screen.
2. Press **[ENTER]** to accept **TBLMIN=0**.
3. Press **1** **[ENTER]** to define the table increment Δ **TBL=1**.



TABLE SETUP
TBLMIN=0
ΔTBL=1

4. Press **[2nd]** **[TABLE]** (above **[GRAPH]**) to display the table.
Note that the maximum value is around 4 between 3 and 5.



X	Y1
0	0.00
1	1.00
2	2.00
3	3.00
4	4.00
5	3.00
6	1.00
7	-1.00
8	-3.00
9	-5.00
10	-6.00

5. Press and hold **[↑]** to scroll through the table until the sign change appears. Note that the maximum length of X for this problem occurs where the sign of **Y1** (column) becomes negative.



X	Y1
0	0.00
1	1.00
2	2.00
3	3.00
4	4.00
5	3.00
6	1.00
7	-1.00
8	-3.00
9	-5.00
10	-6.00

6. Press **[2nd]** **[Table]**. Note that **TBLMIN** has changed to reflect the first line of the table you last displayed.



TABLE SETUP
TBLMIN=7
ΔTBL=1

Zooming in on the Table

You can adjust the way a table is displayed to get more detailed information about any defined function. By varying the value of ΔTBL , you can “zoom in” on the table.

1. Adjust the table setup to get a more accurate estimate of the maximum size of the output. Press 2ND [TABLE] to set **TBLMIN**. Press .1 to set ΔTBL .

TABLE SETUP	
TBLMIN=0	
$\Delta TBL=.1$	

2. Press $\text{[2ND]} \text{[TABLE]}$.

X	Y1
2	1.11-28
3	2.18-09
4	3.44-29
5	4.98-84
6	6.77-81
7	8.78-12

3. Use [LEFT] and [RIGHT] to scroll through the table. Note that the maximum value displayed is **884.2**, which occurs at **X=4**. The maximum occurs at **3.8-03-e4.1**.

X	Y1
2	1.11-28
3	2.18-09
4	3.44-29
5	4.98-84
6	6.77-81
7	8.78-12

Zooming In on the Table (Continued)

4. Press $\boxed{\text{F2}}$ [Table], Press 3.9 $\boxed{\text{ENTER}}$ to set TBLMIN. Press .01 $\boxed{\text{ENTER}}$ to set ΔTBL .

TABLE SETUP	
TBLRC(1)=9	
$\Delta\text{TBL}=0.1$	

5. Press $\boxed{\text{F2}}$ [TABLE] and use $\boxed{\leftarrow}$ and $\boxed{\rightarrow}$ to scroll through the table. Two "equal" maximum values are shown, 564.25 at $X=4.04$ and $X=4.05$.

X	Y1
4.02	564.22
4.03	564.24
4.04	564.25
4.05	564.25
4.06	564.24
4.07	564.22
Y1=564.25	

6. Press $\boxed{\rightarrow}$ or $\boxed{\leftarrow}$ to move the cursor to 4.05. Press $\boxed{\downarrow}$ to move the cursor into the Y1 column. The bottom line of the display shows the value of Y1 at 4.05 in full precision, 564.247408.

X	Y1
4.02	564.22
4.03	564.24
4.04	564.25
4.05	564.25
4.06	564.24
4.07	564.22
Y1=564.247408	

7. Press $\boxed{\rightarrow}$ to display the "other" maximum. The value of Y1 at 4.04 in full precision is 564.247408. This would be the maximum volume of the box if you could cut your piece of paper at 0.1-cm increments.

X	Y1
4.02	564.22
4.03	564.24
4.04	564.25
4.05	564.25
4.06	564.24
4.07	564.22
Y1=564.247408	

Changing the Viewing Window

The viewing window defines the portion of the coordinate plane that appears in the display. The values of the Window variables determine the size of the viewing window. You can view and change these values.

- 1 Press **WINDOW** to display the Window variables edit screen. You can view and edit the values of the Window variables here.

```
WINDOW
Xmin=-10
Xmax=10
Ymin=-10
Ymax=10
Xscl=1
Yscl=1
```

The standard Window variables define the viewing window as shown. **Xmin**, **Xmax**, **Ymin**, and **Ymax** define the boundaries of the display. **Xscl** and **Yscl** define the distance between tick marks on the **X** and **Y** axes.



- 2 Press **0** **ENTER** to define **Xmin**.
- 3 You can enter expressions to define values in the window editor. Press **21** **=** **2**.
- 4 Press **ENTER**. The expression is evaluated, and 10.8 is stored in **Xmax**. Press **ENTER** to accept **Xscl** as 1.
- 5 Press **0** **ENTER** **600** **ENTER** **100** **ENTER** to define the Y Window variables.

```
WINDOW
Xmin=0
Xmax=21+2
Xscl=1
Ymin=-10
Ymax=600
Yscl=1
```

```
WINDOW
Xmin=0
Xmax=10.8
Xscl=1
Ymin=0
Ymax=600
Yscl=100
```

Displaying and Tracing the Graph

Now that you have defined the function to be graphed and the window in which to graph it, you can display and explore the graph. You can trace along a function with **TRACE**.

- 1 Press **Y=** to graph the selected function in the viewing window.

The graph of $Y1=(W-2X)X/2-X(X)$ is shown in the display.



- 2 Press **→** once to display the free-moving cursor just to the right of the center of the screen. The bottom line of the display shows the X- and Y-coordinate values for the position of the graph cursor.



- 3 Use **↑**, **↓**, **←**, and **→** to position the free-moving cursor at the apparent maximum of the function.

As you move the cursor, the X- and Y-coordinate values are updated continuously to reflect the cursor position.



- 4 Press **TRACE**. The Trace cursor appears on the Y1 function. 1 in the upper right corner of the display shows that the cursor is on Y1. As you press **→** and **←**, you trace along Y1, one X dot at a time, evaluating Y1 at each X.



- 5 Press **↑** and **↓** until you are at the maximum Y value. This is the maximum of Y1(X) for the X pixels. (There may be a maximum value "in between" pixels.)

Zooming In on the Graph

You can magnify the viewing window around a specific location using the Zoom instructions to help identify maximums, minimums, roots, and intersections of functions.

1. Press **ZOOM** to display the **ZOOM** menu.

This menu is typical of TI-80 menus. To select an item, you may either press the number to the left of the item, or you may press **→** until the item number is highlighted, and then press **ENTER**.



2. To **ZOOM IN**, press **2**. The graph is displayed again. The cursor changes to indicate that you are using a Zoom instruction.



3. Use **←**, **→**, **↑**, and **↓** to position the cursor near the maximum value on the function, and press **ENTER**.

The new viewing window is displayed. It has been adjusted in both the **X** and **Y** directions by factors of 4 which are the values for Zoom factors.



4. Press **WINDOW** to display the new window variable values.



Other TI-80 Features

Getting Started has introduced you to the basic calculator operations and the table and function graphing features of the TI-80. The remainder of this Guidebook describes these features in more detail and also covers other functions of the TI-80.

Fractions	You can enter fractions directly from the keyboard and perform calculations with fractions. You can convert between fractions and their decimal equivalents. In MATHMODE mode, you can simplify fractions, step-by-step. The TI-80 tells you when a fraction can be simplified and shows the common factor after simplification (Chapter 9).
Graphing	You can store, graph, and analyze up to four functions (Chapter 4) and up to three parametric functions (Chapter 5). You can use Draw operations to annotate graphs (Chapter 7).
Tables	You can create function evaluation tables to simultaneously analyze multiple functions (Chapter 6).
Lists	You can enter and save up to six lists for use in statistical analysis. You also can use lists to simultaneously evaluate expressions at multiple values (Chapter 8).
Statistics	You can perform one-variable and two-variable list-based statistical analysis, including regression analysis, and plot the data as histograms, points, X-Y lines, or box-and-whisker plots. You can define and save three statistical plot definitions (Chapter 9).
Programming	You can enter and save programs that include extensive control and input/output instructions (Chapter 10).

Chapter 1: Operating the TI-80

This chapter describes the TI-80 and provides general information about its operation.

Chapter	Turning the TI-80 On and Off	1-2
Contents	Setting the Display Contrast	1-3
	The Display	1-4
	Entering Expressions and Instructions	1-6
	The Edit Keys	1-8
	Setting Modes	1-9
	TI-80 Modes	1-10
	Variable Names	1-12
	Storing and Recalling Variable Values	1-13
	Last Entry	1-14
	Last Answer	1-16
	TI-80 Menus	1-17
	The VARS and Y-VARS Menus	1-19
	EOS (Equation Operating System)	1-20
	Error Conditions	1-22

Turning the TI-80 On and Off

To turn the TI-80 on, press the **ON** key. To turn it off, press and release **ON**, and then press **OFF**. After about five minutes without any activity, the APD™ (Automatic Power Down) feature turns the TI-80 off automatically.

Turning the Calculator On

Press **ON** to turn the TI-80 on.

- If you pressed **ON** **OFF** to turn the calculator off, the display shows the Home screen as it was when you last used it, and errors are cleared.
- If APD turned the calculator off, the display returns to the same screen or editor in which you left it. See "APD (Automatic Power Down)" below.

Turning the Calculator Off

Press and release **ON**, and then press **OFF** to turn the TI-80 off.

- Any error condition is cleared.
- All settings and memory contents are retained by the Constant Memory™ feature.

APD (Automatic Power Down)

To prolong the life of the batteries, APD turns the TI-80 off automatically after several minutes without any activity. When you press **ON**, the calculator shows the same screen or editor in which you left it.

- If an error message was displayed when APD turned the TI-80 off, the error is cleared and the display returns to a blank line on the Home screen.
- If a menu was displayed, the display returns to the screen or editor from which you called the menu.

All settings and memory contents are retained by the Constant Memory feature.

Note: APD does not occur if a calculation or program is in progress, unless the program is paused.

Batteries

The TI-80 uses two lithium batteries. To replace the batteries without losing any information stored in memory, follow the directions in Appendix B.




Setting the Display Contrast

The brightness and contrast of the display depend on room lighting, battery freshness, viewing angle, and the adjustment of the display contrast. The contrast setting is retained in memory when the TI-80 is turned off.

Adjusting the Display Contrast

You can adjust the display contrast to suit your viewing angle and lighting conditions. As you adjust the contrast setting, the display becomes lighter or darker. A highlighted number in the top right corner changes to indicate the current contrast setting, 0 is the lightest, and 9 is the darkest.



To adjust the display contrast,

1. Press and release the  key.
2. Use one of two keys.
 - To increase the contrast (darken the screen), press and hold .
 - To decrease the contrast (lighten the screen), press and hold .

Note: If you adjust the contrast setting too low, the display may become completely blank. If this happens, press and release , and then press and hold  until the display reappears.

When to Replace Batteries

As you use the TI-80, the battery voltage will gradually drop, and the display will dim. You can adjust the contrast to darken the display when this happens. If the display is dim and adjusting the contrast does not make it dark enough, you should replace the batteries soon. Refer to Appendix B for instructions on how to change the batteries.

Notes: The display contrast may appear very dark after you change batteries. Press and release  and then press and hold  to lighten the display.

The Display

The TI-80 displays both text and graphs. Graphs are described in Chapters 4 and 5.

Home Screen

The primary screen of the TI-80 is the Home screen. You enter instructions to be executed, expressions to be evaluated, and see the results on the Home screen.

Displaying Entries and Answers

When text is displayed, the TI-80 screen can show a maximum of eight lines with 16 characters each.

- If all lines of the display are filled, text “scrolls” off the top of the display.
- If an expression on the Home screen, the Y= editor (Chapter 4), or the program editor (Chapter 10) is longer than one line, it wraps to the beginning of the next line.
- On numeric editors such as the **WINDOW** screen (Chapter 4), expressions scroll to the left and right.

When an entry is executed on the Home screen, the answer is displayed on the right side of the next line.

3+4	7
	Ans

The mode settings (pages 1-9 to 1-11) control the way the calculator interprets expressions and displays answers.

If an answer is too long to display in its entirety, you can press **→** and **←** to scroll the answer so that you can view all of it. In the second example below, the open brace without a corresponding close brace indicates that the list is too long to be displayed in its entirety.






1.1	41.233
	Ans
2.3 5.6824 9.9	Ans
3.5 9.4824 9.4540	Ans (scrolled)

Returning to the Home Screen

To return to the Home screen from any other screen, press **2ND** **QUIT**.

Display Cursors

In most cases, the appearance of the cursor indicates what will happen when you press the next key.

Cursor	Appearance	Meaning
Entry	Flashing 	The next keystroke is entered at the cursor; it types over any character.
INS (insert)	Flashing 	The next keystroke is inserted at the cursor.
2nd	Flashing 	The next keystroke is a 2nd operation.
ALPHA	Flashing 	The next keystroke is an alphabetic character.
memory "full"	Checked rectangle 	You have entered the maximum number of characters in a name, or memory is full.

Graphs and the screens for viewing and editing tables and lists have different cursors, which are described in the appropriate chapters.

Busy Indicator

When the TI-89 is calculating or graphing, a vertical line shows in the top right of the display, as a busy indicator. During a pause in a program, the busy indicator is a dotted line.

Entering Expressions and Instructions

In most places where a value is required, you can use an expression to enter the value. You can enter instructions, which initiate an action, on the Home screen or in the program editor (Chapter 10).

Expressions

An expression is a complete sequence of numbers, variables, functions, and their arguments that evaluate to a single answer. For example, x^2 is an expression. On the TI-80, you enter an expression in the same order as you would write it.

You can create expressions on the Home screen to calculate an answer. In most places where a value is required, you can use an expression to enter the value.

Entering an Expression

To create an expression, you enter numbers, variables, and functions from the keyboard and menus. An expression is completed when you press **ENTER**, regardless of the cursor location. The entire expression is evaluated according to Equation Operating System (EOS™) rules, and then the answer is displayed.

Note: EOS rules determine the order in which operations are completed (page 1-20).

Most TI-80 functions and operations are symbols with several characters in them. You must enter the symbol from the keyboard or menu. You cannot spell it out. For example, to calculate the log of 45, you must press **LOG** 4 5. You cannot type in the letters L O G. (If you type LOG, the TI-80 interprets the entry as implied multiplication of the variables L, O, and G.)



Calculate $3.75 + (-2.9 + \sqrt{5}) + 2 \log 45$

3.75 **+** (**-** 2.9 **+** **√** 5) **+** 2 **LOG** 45
ENTER

3.75 **+** (**-** 2.9 **+** **√** 5) **+** 2 **LOG** 45
2.64375232

Multiple Entries on a Line

To enter more than one expression or instruction on a line, separate them with a colon (:). They are all stored together in Last Entry (page 1-15).

5 **→** **STO2** **→** **STO3** **→** 8 **→** 8
2.5

Entering a Number in Scientific Notation

To enter a number in scientific notation:

1. Type the part of the number that precedes the exponent. This value can be an expression.
2. Press $\boxed{\text{EE}}$ ($\boxed{\text{E}6}$). It is displayed.
3. If the exponent is negative, press $\boxed{-}$, and then type the exponent, which can be one or two digits.

$$\boxed{3.5\text{E}-2} \quad .015$$

Entering a number in scientific notation does not cause the answers to be displayed in scientific notation. The display format is determined by the mode settings (pages 1-9 to 1-11) and the size of the number.

Functions

A function returns a value. For example, π , $\sqrt{}$, $\sin()$ and LOG are functions. Some functions take more than one argument, which is indicated by a { at the end of the name. MIN requires two arguments in this example: $\text{MIN}(5,6)$.



Instructions

























An instruction initiates an action. For example, CLRDRAW is an instruction that clears any drawn elements from a graph. Instructions cannot be used in expressions. Some instructions require more than one argument, as indicated by a { at the end of the name. LINE requires four arguments in this example: $\text{LINE}(1,1,3,3)$.

Interrupting a Calculation

While the busy indicator is displayed, indicating that a calculation or a graph is in progress, you can press $\boxed{\text{ON}}$ to stop the calculation. (There may be a delay.)

The Edit Keys

The arrow keys near the top right of the keyboard control the movement of the cursor. In normal entry, a keystroke types over the character or characters at the position of the cursor. The  and  [ins] keys delete or insert characters.

Key(s)	Action(s)
 or 	Moves the cursor within an expression. These keys repeat when you hold them down.
 or 	Moves the cursor between lines within an expression. These keys repeat when you hold them down. <ul style="list-style-type: none">• On the top line of an expression on the Home screen,  moves the cursor to the beginning of the expression.• On the bottom line of an expression on the Home screen,  moves the cursor to the end of the expression.
 [H]	Moves the cursor to the beginning of an expression.
 [E]	Moves the cursor to the end of an expression.
 [EXE]	Evaluates an expression or executes an instruction.
 [CLR]	<ul style="list-style-type: none">• On a line with text on the Home screen, clears (blanks) the current line.• On a blank line on the Home screen, clears everything on the Home screen.• In an editor, clears (blanks) the expression or value where the cursor is located; it does not store a zero.
 [DEL]	Deletes the character at the cursor. This key repeats.
 [INS] [ins]	Lets you insert characters at the underline cursor. To end insertion, press  [DEL] or a cursor key.
 [2nd]	Next key press is a 2nd operation (the gold-colored label printed to the left above a key). The cursor changes to an  . To cancel 2nd, press  again.
 [ALPHA]	Next key press is an ALPHA character (the light grey character to the right above a key). The cursor changes to an  . To cancel ALPHA, press  or a cursor key.
 [ALPHA-LOCK]	Sets ALPHA-LOCK; each subsequent key press results in an ALPHA character. The cursor changes to an  . To cancel ALPHA-LOCK, press  .
 [X] [T]	Allows you to enter an X in FUNC mode or a T in PARAM mode without first pressing  .

Setting Modes

Modes control how numbers and graphs are displayed and interpreted by the calculator. Mode settings are retained by the Constant Memory feature when the TI-80 is turned off.

Checking MODE Settings

Press **[MODE]** to display the **MODE** screen. The current settings are highlighted. The settings are described on the following pages.

NORMAL	SCI	Numeric display format
FIXED	0123456789	Number of decimal places
RADIAN	DEGREE	Unit of angle measure
a/b/c	b/c	Type of fraction display
AUTOSIMPLIFY	FRAC	Whether to simplify fractions
FUNC	PARAM	Type of graphing
CONNECTED	DOT	Whether to connect graph points
SEQUENTIAL	SIMPL	Whether to plot simultaneously

Changing MODE Settings

To change the mode setting:

1. Press **[\leftarrow]** or **[\rightarrow]** to move the cursor to the line of the setting that you want to change. The setting that the cursor is on flashes.
2. Press **[\leftarrow]** or **[\rightarrow]** to move the cursor to the setting that you want.
3. Press **[ENTER]**.

Leaving the MODE Screen

To leave the **MODE** screen:

- Press the appropriate keys to go to another screen.
- Press **[2ND] [QUIT]** or **[EXIT]** to return to the Home screen.

Setting a Mode from a Program

You can set a mode from a program by entering the name of the mode as an instruction, for example, **FUNC** or **FIXED**. From a blank line in the program editor (line 10), press **[MODE]** to display a menu of the mode names, and then select the name. The name is copied to the cursor location.

The TI-80 has eight mode settings. They control how numeric entries are interpreted, how answers are calculated or displayed, and how graphs appear in the display. Modes are set on the MODE screen (page 1-9).

NORMAL **SCI**

Notation formats affect only how an answer is displayed on the Home screen. Numeric answers can be displayed with up to 10 digits and a two-digit exponent. You can enter a number in any format.

NORMAL display format is the way in which we usually express decimal numbers, with digits to the left and right of the decimal point, as in 12345.67.

SCI (scientific) notation expresses numbers in two parts. The significant digits can be displayed with one digit to the left of the decimal point. The appropriate power of 10 displays to the right of E , as in 1.234567E4.

Note: If you select normal display format, but the answer cannot be displayed in 10 digits or the absolute value is less than .001, the TI-80 displays the answer in scientific notation.

FLOAT **Fixed Decimal**

Decimal settings affect only how an answer is displayed on the Home screen. You can enter a number in any format. The decimal settings apply to both notation formats.

FLOAT (floating) decimal setting displays up to 10 digits, plus the sign and decimal.

The **fixed decimal** setting lets you select the number of digits (0 to 9) to be displayed to the right of the decimal point. The displayed value is rounded based on the number of digits you selected. The actual value is stored and used in calculations. Place the cursor on the number of decimal digits you want, and press **ENTER**.

Note: In the program editor, the format for fixed decimal settings is **FR n**. Enter n as an integer from 0 to 9. The mode is changed to fixed decimal when the program is executed.

**RADIAN
DEGREE**

The angle mode controls.

- How the calculator interprets angle arguments in **SIN**, **COS**, **TAN**, and polar-to-rectangular conversions.
- How the calculator returns angle answers to **SIN⁻¹**, **COS⁻¹**, **TAN⁻¹**, and rectangular-to-polar conversions.

RADIAN mode interprets angle arguments as radians and returns angle answers in radians.

DEGREE mode interprets angle arguments as degrees and returns angle answers in degrees.

**a./b/c
b/c**

a./b/c displays fraction results as mixed numbers, for example, the result of $1/3 + 4/3$ is displayed as $1.3\overline{3}$.

b/c displays fraction results as simple fractions; for example, the result of $1/3 + 4/3$ is displayed as $5/3$.

**AUTOSMP
MANOSMP**

AUTOSMP automatically simplifies fraction results to their lowest terms before displaying them, for example, the result of $2/8 + 2/8$ is displayed as $2/3$.

MANOSMP displays fraction results without automatic simplification. For example, the result of $2/8 + 2/8$ is displayed as $4/8$.

**FUNC
PARAM**

FUNC (function) graphing plots functions where **Y** is expressed in terms of **X** (Chapter 4).

PARAM (parametric) graphing plots relations where **X** and **Y** are each expressed in terms of **T** (Chapter 5).

**CONNECTED
DOT**

CONNECTED draws line segments between the calculated points of the selected functions.

DOT plots only the calculated points of the selected functions.

**SEQUENTIAL
SIMUL**

SEQUENTIAL graphing evaluates and plots one function completely before the next function is evaluated and plotted.

SIMUL (simultaneous) graphing evaluates and plots all selected functions for a single value of **X**, one at a time. In Parametric mode, **X** and **Y** are selected pairs. They are evaluated and plotted a **T** value at a time.

Variable Names

On the TI-80 you can enter, name, and use several types of data: numeric values (including fractions), lists, functions, and statistical plots.

Variables and Defined Items

The TI-80 uses both user-assigned and pre-assigned names for variables and other items saved in memory.

Variable Type	Names
Numeric values (including fractions)	A , B , ..., Z , 0 (single character only)
Lists	L1 , L2 , L3 , ..., L6 , L7 , L8 (on the keyboard)
Functions	Y1 , Y2 , ..., Y6 (on the Y= editor in FUNC mode)
Parametric equations	X1 (T), Y1 (T), ..., X6 (T), Y6 (T) (on the Y= editor in PARAM mode)
Statistical plots	PLOT1 , PLOT2 , PLOT3 (on the STAT PLOT menu)
System variables	XMN , EMAX , and others (on various menus)

Programs also have user-defined names and share memory with variables. Program names can be up to seven characters long. Programs are entered and edited from the program editor (Chapter 10).

You can store to lists (Chapters 8), system variables such as **EMAX** (Chapter 4) or **TOLIM** (Chapter 6), and all **Y=** functions (Chapters 4 and 5) from the Home screen or from a program. You can store to lists (Chapters 8 and 9) and functions (Chapters 4 and 5) from editors. You can also store to a list element (Chapter 8).

For more information about system variables, see Appendix A.

Storing and Recalling Variable Values

Values are stored to and recalled from memory using variable names. When an expression containing the name of a variable is evaluated, the value of the variable at that time is used.

Storing Values in a Variable

You can store a value to a variable from the Home screen or a program using the **STO** key. Begin on a blank line.

- 1 Enter the value that you want to store (this can be an expression).
- 2 Press **STO**. The symbol \rightarrow is copied to the cursor location.
- 3 Press **ALPHA** and then the single letter of the variable to which you want to store the value.
- 4 Press **ENTER**. If you entered an expression, it is evaluated. The value is stored in the variable.



5+48-5.2 Z1

Displaying a Variable Value

To display the value of a variable, enter the variable name on a blank line on the Home screen, and then press **ENTER**. You can enter the name of the variable in one of the following ways.

- Press **ALPHA** and the letter of the variable (for user-defined variables).
- Press **2ND** and the name of the list.
- Press **2ND** and select the type and name of the variable (for system variables).
- Press **2ND** [F1-F6] and select the type and name of the function.

Using a Variable in an Expression

To use the current value of a variable in an expression, just enter the variable name in the expression.



5.1-E Z1
5.1-E 42
CLX 25 350

Last Entry

When you press **2ND** **MEM** on the Home screen to evaluate an expression or execute an instruction, the expression or instruction is stored in an area called Last Entry, which you can recall. When you turn the TI-80 off, Last Entry is retained in memory.

Using Last Entry

You can recall Last Entry and edit it from the Home screen. Press **2ND** **MEM**. The current line is cleared, and the Last Entry is copied in the line. The cursor is positioned at the end of the entry. Because the TI-80 updates the Last Entry storage area only when you press **2ND** **MEM**, you can recall the previous entry even if you have begun entering the next expression. However, when you recall Last Entry, it replaces what you have typed.



8 ÷ 7	5-7	12
2ND MEM		
2ND MEM	5-7B	

Displaying a Previous Entry

The TI-80 keeps previous entries (up to a total of 80 bytes) in Last Entry. You can display and edit those entries by continuing to press **2ND** **MEM**. Last Entry displays previous entries in a loop, beginning with newest entry and moving to the oldest entry. Once the oldest item is displayed, **2ND** **MEM** displays the newest item again.



1 2ND ALPHA A	5-7B	1
2ND MEM	2-7B	2
2 2ND ALPHA B	0-7C	3
2ND MEM	0-7CB	
3 2ND ALPHA C		
2ND MEM		
2ND MEM		

When you press **2ND** **MEM** again, the previous item replaces the item on the current line.

	5-7B	1
	2-7B	2
	0-7C	3
2ND MEM	2-7CB	

Re-executing the Previous Entry

To execute Last Entry, press **ENTER** on a blank line on the Home screen. The entry is executed, but it does not reappear.




Multiple Entries
not in List

To enter more than one expression or instruction on a line, separate them with a colon (:). They are all stored together in Last Entry.

If the previous entry contained more than one expression or instruction, separated with a colon (page 1-6), they are all recalled. You can recall all entries on a line, edit any of them, and then execute all of them.



Using the equation $A = \pi r^2$, use trial and error to find the radius of a circle that covers 200 square centimeters. Use 8 as your first guess.



Share your ideas.



Continue until the output is as accurate as you need.

Last Answer

When an expression is evaluated successfully from the Home screen or from a program, the TI-80 stores the answer to a variable, **ANS** (Last Answer). **ANS** may be a decimal number, a fraction, or a list. When you turn the TI-80 off, the value in **ANS** is retained in memory.

Using Last Answer (ANS) in an Expression

You can use the variable **ANS** to represent the last answer in most places. When you press $\boxed{\text{2ND}} \boxed{\text{ANS}}$, the variable name **ANS** is copied to the cursor location. When the expression is evaluated, the TI-80 uses the value of **ANS** as the calculation.



Calculate the area of a garden plot 1.7 meters by 4.2 meters. Then calculate the yield per square meter if the plot produces a total of 147 tomatoes.

```
1.7  $\boxed{\text{MC}}$  4.2  
 $\boxed{\text{ENTER}}$   
147  $\boxed{\text{MC}}$   $\boxed{\text{2ND}} \boxed{\text{ANS}}$   
 $\boxed{\text{ENTER}}$ 
```

1.7=4.2	
147÷4.2	7.14
24.58823529	

Continuing an Expression

You can use the value in **ANS** as the first entry in the next expression without entering the value again or pressing $\boxed{\text{MC}} \boxed{\text{ANS}}$. On a blank line on the Home screen, enter the fraction. The TI-80 "types" the variable name **ANS** followed by the fraction.



```
8  $\boxed{\text{MC}}$  2  
 $\boxed{\text{ENTER}}$   
 $\boxed{\text{MC}}$  9.8  
 $\boxed{\text{ENTER}}$ 
```

8÷2	
80÷9.8	2.5
24.75	

Storing Answers

To store an answer, store **ANS** to a variable before you evaluate another expression.



Calculate the area of a circle of radius 5 meters. Then calculate the volume of a cylinder of radius 5 meters and height 1.3 meters. Store the result in the variable **V**.

```
 $\boxed{\text{2ND}} \boxed{\text{MC}}$  5  $\boxed{\text{MC}}$  5  
 $\boxed{\text{ENTER}}$   
 $\boxed{\text{MC}}$  1.3  
 $\boxed{\text{ENTER}}$   
 $\boxed{\text{STO-}}$   $\boxed{\text{ALPHA}}$  V  
 $\boxed{\text{ENTER}}$ 
```

70.5	
AN5=)	70.53882354
259.1823939	
AN5=)	259.1823939
259.1823939	

To leave the keyboard uncluttered, the TI-80 uses full-screen menus to give you access to many additional operations. The use of specific menus is described in the appropriate chapters.

Moving from One Menu to Another

Some menu keys, such as **[ALT]**, display more than one menu. The names of the menus appear on the top line. The current menu is highlighted and the items in that menu are displayed.

Press **⌘** or **⌘** to move the cursor to a different page.

Collecting and storing from a library

The number of the current menu is highlighted. If there are more than seven items on the menu, a 4 appears on the hot line in place of the : (colon) between the menu number and name. Menu items, such as **WAKE WINDOW**, that end in **—** (ellipses marks) display another menu.

There are two methods of selecting from a matrix:

- Press the number of the item you want to select.
- Press **[←]** and **[→]** to move the cursor to the item you want to select, and then press **[ENTER]**.



1. *Indica* (Cannabis indica)

3. **Parse DATE** to display the **DATE** name.



- To select 3^4 , you may either press 4 or press $\boxed{3}$ $\boxed{^{\wedge}}$ $\boxed{4}$ $\boxed{=}$.
- Enter 27, and then press $\boxed{=}$ to evaluate the expression.



Leaving a Menu without Making a Selection

There are several ways to leave a menu without making a selection from the menu.

- To return to the Home screen, press **[2nd][QUIT]**.
- To return to the screen where you were, press **[2][F10]**.
- To display a different menu, press the appropriate key, such as **[2][F1]**.
- To select another screen, press the appropriate key, such as **[F6][PAGE]**.

The VARS and Y-VARS Menus

You may want to use the names of system variables (such as **XMIN**) and functions (such as **Y1**) in an expression. You may also want to store values directly to those variables. Use the **VARS** or **Y-VARS** menus to access the names.

VARS Menu

The **VARS** menu displays the names of window variables such as **XMIN** and **TSTEP**, statistics variables such as **Σ** and **Qs**, and table variables such as **TBLMIN**.

Press **[2ND]** **[VARS]** to display the **VARS** menu. Some of the items display more than one menu of variable names.

VARS

1: WINDOW	Names of X, Y, and T variables
2: STATISTICS	Σ , Y1 , EQ , and BOX variables
3: TABLE	TBLMIN and TBL variables
4: SIMPFACTOR	Factor list used by SIMP function

Y-VARS Menu

The **Y-VARS** menus display the names of functions and the instructions to select or deselect functions from a program or the Home screen.

Press **[2ND]** **[Y-VARS]** to display the **Y-VARS** menu. Then press **[2]** or **[1]** to select the type of variable you want.

Y	Displays a menu of names of Ys functions.
EQ/Y1	Displays a menu of names of Eq/Y1 / T equations.
ON/OFF	lets you select/deselect functions.

Copying a Name from a VARS or Y-VARS Menu

To copy a variable name from a **VARS** or **Y-VARS** menu.

1. Press **[2ND]** **[VARS]** or **[2ND]** **[Y-VARS]**. The **VARS** or **Y-VARS** menu is displayed.
2. Select the type of variable you want.
3. Press **[ENTER]** to select the name you want from the menu. It is copied to the cursor location.

EOS (Equation Operating System)

The Equation Operating System (EOS™) defines the order of operations for the calculator—that is, the order in which the TI-80 evaluates functions in expressions. EOS lets you enter numbers and functions in a simple, straightforward sequence.

Order of Evaluation

A function returns a value. EOS evaluates the functions in an expression in the following order:

- 1 Functions that are entered after the argument, such as A^2 , 2^3 , 321 , 45^2 , 2×1 , and $\div 6MP$.
- 2 Powers and roots, such as 2^*5 or 5^{-1} , 32 .
- 3 Implied multiplication where the second argument is a number, variable name, or list, or begins with an open parenthesis, such as $4A$, $(A+B)4$, or $4(A+B)$.
- 4 Single-argument functions that precede the argument, such as $-A$, $\sqrt{5}$, $\sin 3$, or $\log 2$.
- 5 Implied multiplication where the second argument is a multi-argument function or a single-argument function that precedes the argument, such as $2\text{NDERN}(A^2 A)$ or $A\sin 2$.
- 6 Permutations (nPr) and combinations (nCr).
- 7 Multiplication and division (including $\text{INT}()$).
- 8 Addition and subtraction.
- 9 Test functions, such as $>$ or $=$.
- 10 Conversion functions, $\div \text{FRAC}$, $\div \text{DEC}$, $\div \text{B}_1/\text{B}_2$, and $\div \text{B}/\text{C}$.

Within a priority group, EOS evaluates functions from left to right. However, two or more single-argument functions that precede the same argument are evaluated from right to left. For example, $\sin(\text{PART LN } 8)$ is evaluated as $\sin(\text{PART}(\text{LN } 8))$.

Calculations within a pair of parentheses are evaluated first. Multi-argument functions, such as $\text{NDERN}(A^2 A, 8)$, are evaluated as they are encountered.

The conversion functions $\div \text{FRAC}$, $\div \text{DEC}$, $\div \text{B}_1/\text{B}_2$, and $\div \text{B}/\text{C}$ can only be used at the end of a command line, with one exception: they can be followed by a store instruction.

Implied Multiplication

The TI-80 recognizes implied multiplication. For example, it understands $2x$, $45W$, $45 \cdot 3(1+2)$, and $(2+5)^2$ as implied multiplication.

Parentheses

All calculations inside a pair of parentheses are completed first. For example, in the expression $4(1+2)$, FDX first evaluates the portion inside the parentheses, $1+2$, and then multiplies the answer, 3, by 4.

You can omit any right (closing) parentheses at the end of an expression. All "open" parenthetical elements are closed automatically at the end of an expression and preceding the \rightarrow (store) or display-conversion instructions.

Note: Parentheses are also used to enclose the arguments for certain functions, for example, $\text{RNDN}(A^2, A, B)$. In these cases, parentheses do not indicate implied multiplication.

Negation

To enter a negative number, use the negation function. Press \square , and then enter the number. On the TI-80, negation is in the fourth group in the FDX hierarchy. Functions in the first group—such as squaring—are evaluated before negation.

For example, -3^2 is a negative number (or 0). -3^2 is -9 (i.e., parentheses to square a negative number: $(-3)^2$).

-23	
\square -23	-4
\square -4	4
\square -4 \square -4	-16

Note: Use the \square key for subtraction and the \square key for negation. If you press \square to enter a negative number, as in $\text{F} \square 7$, or if you press \square to indicate subtraction, as in $\text{F} \square 7$, it is an error. If you press $\text{A} \square 7 \square \text{A}$ \square $\text{A} \square 7 \square \text{B}$, it is interpreted as implied multiplication ($A \cdot B$).

Error Conditions

The TI-80 detects any errors at the time it evaluates an expression, executes an instruction, plots a graph, or stores a value. Calculations stop and an error message with a menu is displayed immediately. Error codes and conditions are described in detail in Appendix B.

Diagnosing an Error

If the TI-80 detects an error, it displays the error screen.



```
FREE SYNTAX
00:0018
11:4031
```

The top line indicates the general type of error, such as **SYNTAX** or **DOMAIN**. For additional information about each error message, see Appendix B.

- If you select **GOTO**, the cursor is displayed at the location where the error was detected.

Note: If a syntax error was detected in the contents of a **Y=** function during program execution, **GOTO** returns the user to the **Y=** editor, not to the program.

- If you select **QUIT** or press **2ND** **QUIT** or **2ND** **ENTER**, you return to the Home screen.

Correcting an Error

To correct an error:

1. Note the type of the error.
2. Select **GOTO**, if that option is available, and look at the expression for syntax errors, especially at and before the cursor location.
3. If the error in the expression is not readily apparent, turn to Appendix B and read the information about the error message.
4. Correct the expression.

Chapter 2: Math, Angle, and Test Operations

This chapter describes the math, angle, and relational operations available on the TI-80. The most commonly used functions are accessed from the keyboard; others are accessed through menus.

Chapter	Getting Started: Library Functions . . .	2-2
Contents	Using the TI-80 Functions . . .	2-3
	Keyboard Math Operations . . .	2-4
	MATH MATH Operations . . .	2-7
	MATH NUM (Number) Operations . . .	2-10
	MATH PRB (Probability) Operations . . .	2-12
	ANGLE Operations . . .	2-14
	TEST (Relational) Operations . . .	2-16

Getting Started: Lottery Chances

Getting Started is a fast-paced introduction. Read the chapter for details.

Suppose you want to enter a lottery where six numbers will be drawn from 50. To win, you must pick all six numbers (in any order). What is the probability of winning if you buy one ticket? What is the probability of winning if you buy five tickets?

1. Determine the number of combinations possible. On the Home screen, press **50** to enter the total number of items. Press **[MATH]****[>]** to display the **MATH PRB** menu. Press **3** to select **nCr**. Press **6** to enter the number of items selected.



50 nCr 6

2. Press **[ENTR]** to evaluate the expression. This is the total number of possible combinations of 6 numbers drawn from a set of 50 numbers. With one ticket, you have one chance in 15,890,700 of winning.



50 nCr 6
15890700

3. To calculate the probability of winning with one ticket, press **1** **[÷]** **[50]** **[=]** **[ENTR]**. The answer is too large to display in fixed notation, therefore, it is shown in scientific notation. 0.000000063508462 is the decimal equivalent.



50 nCr 6
15890700
1 ÷ 50 =
6.3508462E-06

4. To calculate the probability of winning with five tickets, press **5** **[×]** **[ENTR]**. Again, the answer is too small to display in fixed notation. The decimal equivalent is 0.0000031754231 .



50 nCr 6
15890700
1 ÷ 50 =
6.3508462E-06
5 ×
3.1754231E-05

Using the TI-80 Functions

This page contains some general information you should know about the TI-80 functions described in Chapter 1.

Using Lists with Functions

Functions that are valid for lists return a list calculated on an element-by-element basis. If two lists are used in the same expression, they must be the same length. For more information about lists, see Chapter 5.



```
(L1+2)-(L3+4)
{4 8}
Z=(L1+2)*3
{12 4 8}
```

Using Fractions with Functions

Some math functions (+, -, \times , \div , x^2 , $\frac{b}{c}$, $\frac{a-b}{c}$, $\frac{a}{b+c}$) accept fractions as input values. All other functions convert fractions to decimals before operating on them. For more information about fractions, see Chapter 3.



```
1/2+1/3
5/6
1/2*1/3
.4754255166
1/4*5
.6666666667
```

Keyboard Math Operations

The most commonly used math functions are on the keyboard. The keyboard math operations can be used with decimal numbers, fractions (except as noted), expressions, and lists.

+ (Add)
- (Subtract)
× (Multiply)
/ (Divide)

The basic arithmetic functions are addition ($+$), subtraction ($-$), multiplication (\times), and division (\div). Each argument for these functions can be a list.

*valueA+valueB, valueA-valueB,
valueA×valueB, valueA÷valueB*



```
7+5=12
12÷2=6
```

Trig Functions

The trigonometric functions are interpreted according to the current **RADIAN/DEGREE** mode setting. (Refer to page 1-9 for instructions on changing the mode setting.) For example, **SIN 30** in **RADIAN** mode returns $\sim.0980172841$, in **DEGREE** mode, it returns **.5**. Each argument for the trigonometric functions may be a list.

SIN value, **COS** value, **TAN** value

SIN⁻¹, **COS⁻¹**, and **TAN⁻¹** are the inverse trig functions (arcsine, arccosine, and arctangent).

SIN⁻¹ value, **COS⁻¹** value, **TAN⁻¹** value

RADIAN Mode



```
DEG < 90
SIN 1.5708
COS 1.5708
TAN 1.5708
```

⁻¹ (Inverse)

⁻¹ (Inverse, $\frac{\square}{\square}$) may be used with numbers, expressions, or lists. The multiplicative inverse is the equivalent of the reciprocal, $1/x$.

value⁻¹



```
5^-1
1÷2=0.5
```

\wedge (Power)
 \square^2 (Square)
 $\sqrt{\square}$ (Square Root)

\wedge (power, \square), \square^2 (square, \square), and $\sqrt{\square}$ (square root, \square) may be used with decimal numbers, fractions, expressions, or lists. When used with a fraction, $\sqrt{\square}$ (square root, \square) returns a decimal number.

$\text{value}^\wedge \text{power}$, value^\square , $\sqrt{\text{value}}$

Note: Raising a negative number to a noninteger power can result in a complex number, which returns an error.

\square^2	
4883	625
$\sqrt{16.2 \times 10^{-3}}$	25
OK	

LOG
 10^\square
LN

These functions find the logarithm (\square), power of ten (\square), and natural log (\square) of the specified value or list of values.

LOG value, **10^\wedgepower** , **LN** value

LOG 88	
$10^\wedge 88$	1.819142934
LN -15.73	88
OK	

e^\square

e^\square (\square) returns the constant e raised to a power or list of powers. e^1 returns the value of the constant e .

$e^\wedge \text{power}$

$e^\wedge 5$	
$e^\wedge 1$	148.4131591
OK	

Keyboard Math Operations (Continued)

- (Negation) The **(negation, \square)** returns the negative of a number, expression, or list. The narrow negation symbol (\square) distinguishes negation from the subtraction or minus ($-$)

-value

ICE rules (Chapter 1) determine when negation is evaluated. For example, $\square A^2$ returns a negative number because squaring is evaluated before negation. Use parentheses to square a negated number, $\square(A)^2$.



$$\begin{array}{l} (-4)^2 + (-4)^2 - 29 + 1 \\ 24 \end{array}$$

ABS **ABS** (absolute value, \square) **ABS** returns the absolute value of a number, expression, or list.

ABS value



$$\begin{array}{l} \text{ABS } -256 \\ 256 \\ \text{ABS } (1.28, -5.875) \\ 5.875 \end{array}$$

π (PI) **PI** (\square) **PI** is stored as a constant in the TI-80. Press \square to copy the stored π to the cursor location. The number 3.141592654 is displayed for π , but 3.1415926535898 is used internally in calculations.



$$\begin{array}{l} 2\pi \\ 6.283185307 \\ 70\pi \\ 219.9114854 \end{array}$$

MATH MATH Operations

To display the **MATH MATH** menu, press **[MATH]**. When you select a menu item, the name is copied to the cursor location. Functions that are valid for lists return a list calculated on an element-by-element basis.

MATH MATH Menu

MATH	ROM	POS
1: INT÷		Displays quotient and remainder
2: →DEC		Displays answer in decimal form
3: √		Cube
4: √		Cube root
5: n^{th} root		n^{th} root
6: DERIV(Numerical derivative

INT÷

On the Home screen or from a program, **INT÷** (integer divide, **MATH MATH**, item 1) returns the quotient (or quotient and remainder) resulting from the division of two integers. Each argument can be a list.

integer ÷ INT÷(integer)

When **INT÷** is executed on the Home screen, it displays the symbols **Q=** for the quotient and **R=** for the remainder.

Note: If **INT÷** is embedded in an expression, **Q=** and **R=** may not be displayed.

When used with lists, **INT÷** returns a list of quotients only.

If the result of **INT÷** is used in subsequent calculations, the remainder is dropped, and only the quotient is used.

The quotient from **INT÷** is returned to **ANS**.



►DEC

►DEC (convert to decimal) **MATH MATH**, item 3) displays an answer in decimal form. **►DEC** can only be used after a value and at the end of an expression. *value* can be a list.

value►DEC

expression►DEC

$$\begin{array}{|l|} \hline 1/2+1/3 \\ \hline \text{MATH►DEC} \\ \hline .8333333333 \\ \hline \end{array}$$

³ (Cube)

³ (cube, **MATH MATH**, item 3) returns the cube of a number, expression, or list.

*value*³

$$\begin{array}{|l|} \hline (2, 3, 4) \text{ } ^3 \\ \hline \text{CB } 27 \ 64 \ 125 \\ \hline \end{array}$$

³√ (Cube Root)

³√ (cube root, **MATH MATH**, item 4) returns the cube root of a number, expression, or list.

³√*value*

$$\begin{array}{|l|} \hline (2, 3, 4) \text{ } ^3\sqrt{} \\ \hline \text{CB } 2 \ 3 \ 4 \\ \hline \end{array}$$

ⁿ√ (Root)

ⁿ√ (root, **MATH MATH**, item 5) returns the *n*th real root of a number, expression, or list.

*n*throotⁿ√*value*

$$\begin{array}{|l|} \hline 4^{\text{th}}\sqrt{(1+16 \cdot 81)} \\ \hline \text{CB } 2 \ 3 \\ \hline \end{array}$$

NDEPV()

NDEPV() (numerical derivative, **MATH** **MATH**, A10.5) returns an approximate derivative of an expression with respect to a specified variable, given the value at which to evaluate the derivative, and x (optional, if none is specified, 1/-3 is used).

NDEPV(expression, variable, value) or

NDEPV(expression, variable, value, x)

NDEPV uses the symmetric difference quotient method (as shown in the formula below), which approximates the numerical derivative value as the slope of the secant line through the points

$$f'(x) = \frac{f(x + \epsilon) - f(x - \epsilon)}{2\epsilon}$$

As ϵ gets smaller, the approximation usually becomes more accurate.

NDEPV (x^2 , x , 3.5, 1)
75.000001
NDEPV (x^2 , x , 3.5, 5e-001)
75

Because of the method used, **NDEPV** can return a false derivative value at a nondifferentiable point.

MATH NUM (Number) Operations

To display the MATH NUM menu, press **MATH** **NUM** **▢**. When you select a menu item, the name is copied to the cursor location. Functions that are valid for lists return a list calculated on an element-by-element basis.

MATH NUM Menu

MATH NUM	PRG
1: ROUND	Round
2: IPART	Integer part
3: FPART	Fractional part
4: INT	Greatest integer
5: MIN	Minimum value
6: MAX	Maximum value
7: REMAINDER	Remainder of a division result

ROUND

ROUND (MATH NUM item 1) returns a number, expression, or list rounded to a specified number of decimals (0-9). If the number of decimals is omitted, the number is rounded to the digits that are displayed, a maximum of 10 digits.

ROUND(value, #decimals)

ROUND 35.45
35.45
ROUND 35.45 2
35.45
ROUND 35.45 3.1427
35.45

ROUND(list, #dec)

ROUND {1.23456789, 12.35}
{1.23456789, 12.35}
ROUND {C, 123456789, 12.35}
{C, 123456789, 12.35}

IPART FPART

IPART (integer part, MATH NUM item 2) returns the integer part or parts of a number, expression, or list. **FPART** (fractional part, MATH NUM item 3) returns the fractional part or parts of a number, expression, or list.

IPART value

IPART 35.45
35
IPART {35.2, 35.45}
{35, 35}

FPART value

FPART 35.45
.45
FPART {35.2, 35.45}
{.2, .45}

INT

INT (greatest integer, MATH NUM item 4) returns the largest integer less than or equal to a number, expression, or list. The value is the same as **IPART** for nonnegative numbers and negative integers, but one integer less than **IPART** for negative noninteger numbers.

INT value

INT 35.45
35
INT 35.45
35

MIN
MAX

MIN (minimum value, **MATH NUM** item 5) returns the smaller of two values or the smallest element in a list. If two lists are compared, it returns a list of the smaller of each pair of elements. If a list and a value are compared, it compares each element in the list with the value.

MAX (maximum value, **MATH NUM** item 6) returns the larger of two values or the largest element in a list. If two lists are compared, it returns a list of the larger of each pair of elements. If a list and a value are compared, it compares each element in the list with the value.

MIN (valueA,valueB)	MAX (valueA,valueB)
MIN (list)	MAX (list)
MIN (listA,listB)	MAX (listA,listB)
MIN (value,list)	MAX (value,list)
MIN (list,value)	MAX (list,value)

```
MIN (3+2+2)      3
MIN (2+4+5+4)    4
MAX (4+5+6)      6
```

Note: **MIN** and **MAX** are also available on the **LIST MATH** menu.

REMAINDER

REMAINDER (**MATH NUM** item 7) returns the remainder resulting from the division of two integers, each of which can be a list. (See **INTs**, page 2-7.)

REMAINDER (valueA,valueB)	REMAINDER (listA,listB)
REMAINDER (value,list)	REMAINDER (list,value)

If a list is used as one or both arguments, the result is a list of remainders.

```
REMAINDER (6+4)  2
REMAINDER (11+14  2
              17+5)  0  2
```

MATH PRB (Probability) Operations

To display the MATH PRB menu, press **2ND** **[7]**. When you select a menu item, the name is copied to the cursor location. Functions that are valid for lists return a list calculated on an element-by-element basis.

MATH PRB Menu

MATH PRB

1: RAND	Random number generator
2: nPr	Number of permutations
3: nCr	Number of combinations
4: !	Factorial
5: RANDINT	Random integer generator

RAND

RAND (random number **MATH PRB**, item 1) generates and returns a random number greater than 0 and less than 1 (as in the first example below). A random number is generated from a seed value. To control a random number sequence, first store an integer seed value in **RAND**. In the second example below, 1 is stored to **RAND** so that the TI-80 uses 1 as the seed value for generating random numbers.

```
RAND
.08044007
.049589073
.049589073
.876571691
.077548484
.526921844
```

```
1→RAND
1
RAND
.601878064
.808032484
.487957009
.807448969
```

Notes: When you reset the TI-80, **RAND** is set to the factory seed value, which is 0.

nPr
nCr

nPr (number of permutations, **MATH PRB**, item 2) returns the number of permutations of items taken number at a time. Items and number must be nonnegative integers. Both items and number can be lists.

nCr (number of combinations, **MATH PRB**, item 3) returns the number of combinations of items taken number at a time. Items and number must be nonnegative integers. Both items and number can be lists.

Items **nPr** number

Items **nCr** number

5 nPr 2	20
5 nCr 2	10
(1,2,3) nCr (2,3)	1

! (Factorial)

! (factorial, **MATH PRB**, item 4) returns the factorial of a positive integer or list of integers between 0 and 69.

object

5!	120
(1,2,3,4,5)!	120
(1,2,3,4,5)	120

RANDINT(

RANDINT(random integer, **MATH PRB**, item 5) generates a random integer within a specified range. It requires two arguments: the lower and upper boundaries of the range (in any order). Both arguments must be integers. Both arguments can be negative. Both arguments can be lists.

RANDINT(lower,upper)

RANDINT(1,5)*5+666	
RANDINT(1,6)	4
RANDINT(1,2)*33+	
(7,8,9)	4 3 83

ANGLE Operations

To display the **ANGLE** menu, press $\boxed{\text{2ND}} \boxed{\text{ANGLE}}$. The **ANGLE** menu displays angle indicators and instructions. When you select an item from the menu, the name is copied to the cursor location.

ANGLE Menu	ANGLE
	1) ° Degree notation
	2) ° Radian notation
	3) R↔Y Returns R given X and Y
	4) Y↔R Returns Y given X and Y
	5) R↔X Returns X given R and Y
	6) Y↔X Returns Y given R and X

° (Degree) ° (degree, **ANGLE**, item 1) lets you designate an angle or list of angles as degrees, regardless of the current angle mode setting. In **RADIAN** mode, ° can also be used to convert degrees to radians.

angle[°]

```
SIN 45°
1.7071067812
SIN (45, 30, 90)°
CO .5 12
```

RADIAN Mode

```
45°
.7853981634
```

° (Radians) ° (radians, **ANGLE**, item 2) lets you designate an angle or list of angles as radians regardless of the current angle mode setting. In **DEGREE** mode, ° can also be used to convert radians to degrees.

angle[°]

```
SIN (PI/4)°
.7071067812
SIN (4, PI/3)°
CO .5 12
```

DEGREE Mode

```
(PI/4)°
45
```


R→P(
P→R(
P→R(
P→P(

Note: When converting from one coordinate system to the other, be sure that the angle mode setting, **DEGREE** or **RADIAN**, is appropriate for your angle measurements. (Press **MODE** to check the current setting.)

R→P((**ANGLE**, item 3) converts the given rectangular coordinates to polar coordinates and returns **R**.

P→P((**ANGLE**, item 4) converts the given rectangular coordinates to polar coordinates and returns **θ**.

Both **X** and **Y** can be lists.

R→P((**A**, **Y**)
P→P((**A**, **Y**)

RADIAN Mode

R→P(("1,0)	1
P→P(("1,0)	3.141592654

P→R((**ANGLE**, item 5) converts the given polar coordinates to rectangular coordinates and returns **X**.

P→P((**ANGLE**, item 6) converts the given polar coordinates to rectangular coordinates and returns **Y**.

Both **R** and **θ** can be lists.

P→R((**R**, **θ**)
P→P((**R**, **θ**)

RADIAN Mode

P→R((1, π)	-1
P→P((1, π)	0

TEST (Relational) Operations

To display the TEST menu, press $\boxed{\text{TEST}}$. When you select from the menu, the name is copied to the cursor location. These functions are valid for lists: they return a list calculated on an element-by-element basis.

TEST Menu	TEST	True If:
	1:=	Equal to
	2:≠	Not equal to
	3:>	Greater than
	4:	Greater than or equal to
	5:<	Less than
	6:≤	Less than or equal to

Relational operators compare `valued` and `valuedf` and return 1 if the test is true or 0 if the test is false. `valued` and `valuedf` can be numbers, expressions, or lists.

Relational operators are often used in programs to control program flow and in graphing to control the graph of a function over specific values.

relative to the world
 relative to the world
 relative to the world
 relative to the world
 relative to the world
 relative to the world

$$\begin{aligned} 2-5 &= 2-2 \\ -C(1+2) &= 2(3-C) \\ -C(1+2) &= 2(3-C) \\ -C(1+2) &= 2(3-C) \end{aligned}$$

Using Tests	Relational expressions are evaluated after mathematical functions according to EBN rules (Chapter 1)
--------------------	--

- The expression $2+3*2+3$ returns 8. The TI-80 does the addition first because of EXOS rules, and then it compares 4 to 5.
- The expression $2+(2*2)+3$ returns 8. The TI-80 first performs the relational test because it is in parentheses, then it adds 2, 1, and 3.

Chapter 3: Fractions

This chapter describes how to use the fraction operations on the TI-80.

Chapter Contents	Getting Started: Working with Fractions	3-2
	Setting Modes for Fraction Results	3-4
	Entering and Using Fractions in Calculations	3-5
	The FRACTION Menu	3-6

Getting Started: Working with Fractions

Getting Started is a fast-paced introduction. Read the chapter for details.

Enter the expression $1\frac{27}{32} + 1\frac{19}{32}$. Evaluate the expression, simplify the result, and then use the conversion options on the FRACTION menu to convert the result.

This example is performed in **MANSIMP** (manual simplification) mode. **MANSIMP** mode is especially useful for students when they are learning fraction concepts. When **MANSIMP** mode is selected, the **SIMP** function (from the **FRACTION** menu) can be used to simplify fractions, step-by-step.

1. Select **MANSIMP** mode.



2. From the Home screen, press $1 \left[\frac{\Box}{\Box} \right] 27 \left[\frac{\Box}{\Box} \right] 32 + 1 \left[\frac{\Box}{\Box} \right] 19 \left[\frac{\Box}{\Box} \right] 32$ to enter the mixed fraction expression, $1\frac{27}{32} + 1\frac{19}{32}$.



3. Press $\left[\frac{\Box}{\Box} \right]$ to evaluate the expression. The $\frac{1}{1}$ indicates that the fraction can be simplified.



4. Press $\left[\frac{\Box}{\Box} \right]$ 1 to select **SIMP** (simplify). **MANSIMP** is copied to the cursor location.



5. Press $\left[\frac{\Box}{\Box} \right]$ to simplify the fraction.

In **MANSIMP** mode, the TI-84 uses the lowest common denominator for simplification. The simplification factor is displayed. The $\frac{1}{1}$ preceding the result indicates that the fraction can be simplified further. Continue pressing $\left[\frac{\Box}{\Box} \right]$ until $\frac{1}{1}$ is no longer displayed.



The TI-82 uses the lowest common denominator for simplification. If you want to choose the simplification factor yourself, you can enter it as part of the expression.

- 6 Press $\boxed{\frac{\square}{\square}} \boxed{\frac{\square}{\square}}$ to clear the screen. Reenter the expression, or press $\boxed{\text{DEL}}$ $\boxed{\text{ENTER}}$ until you see the expression
- $$1.4727 + 1.179$$

$$1.4727 + 1.179$$

- 7 Press $\boxed{\text{Frac}} \boxed{\square} \boxed{\text{Frac}} \boxed{9} \boxed{\square} \boxed{\text{Frac}} \boxed{\square} \boxed{+} \boxed{\square}$.
This adds the simplification factor 9 and places the expression in parentheses.

$$(1.4727 + 1.179 \cdot 9)$$

- 8 Press $\boxed{\text{Frac}} \boxed{1}$ to copy **Frac1** to the cursor line, above

$$(1.4727 + 1.179 \cdot 9)$$

Frac1

- 9 Press $\boxed{\text{Frac}} \boxed{9}$ to simplify the fraction result. The simplification factor is displayed

$$(1.4727 + 1.179 \cdot 9)$$

Frac1

Frac9 2.143

- 10 Press $\boxed{\text{Frac}} \boxed{\text{Ans}} \boxed{\text{Frac}} \boxed{2} \boxed{\text{Frac}} \boxed{1}$ to convert the mixed-fraction result to a simple fraction

$$(1.4727 + 1.179 \cdot 9)$$

Frac1

Frac9 2.143

Frac2 143

- 11 Press $\boxed{\text{Frac}} \boxed{\text{Ans}} \boxed{\text{Frac}} \boxed{5} \boxed{\text{Frac}} \boxed{1}$ to convert the fraction result to its decimal equivalent

$$(1.4727 + 1.179 \cdot 9)$$

Frac1

Frac9 2.143

Frac2 143

Frac5 2.333333333

Setting Modes for Fraction Results

From the **MODE** screen, you can select simplification and display format options for fraction results.

AUTOSIMP Mode with b/a/c and a. b/c Modes

AUTOSIMP mode simplifies fractions automatically. Simplification takes place before the expression is evaluated. Then the result is simplified to its lowest terms. For example, $12/18$ is simplified to $2/3$ when you press **ENTER**.

There are two formats for displaying fractions results.

- **b/a/c** mode displays fraction results in simple fraction (a fraction without a whole number) format, for example, $25/4$.



The calculator screen shows the expression $25 \div 4 = 25 \div 4$ on the top line. The result $6 \frac{1}{4}$ is displayed on the bottom line, where the whole number 6 is on the left and the fraction $1/4$ is on the right.

- **a. b/c** displays fraction results in mixed-fraction (a whole number with a fraction) format, for example, $6 \frac{1}{4}$.



The calculator screen shows the expression $25 \div 4 = 25 \div 4$ on the top line. The result $6 \frac{1}{4}$ is displayed on the bottom line, where the whole number 6 is on the left and the fraction $1/4$ is on the right.

MANSHIP Mode with a.b/c Mode

MANSHIP mode lets you simplify fractions manually. MANSHIP was designed for teaching and learning fractions concepts. In MANSHIP mode, you can simplify fractions and the results of expressions using fractions, step-by-step.

When a fraction result is not expressed in its lowest terms, a down arrow (\downarrow) is displayed to remind you that you can simplify the result. Use **F&SIMP** from the **FRACTION** menu to simplify the fraction. You can then use **Fb/c** or **Fa.b/c** to change the display format of the fraction result.



The calculator display shows the following steps for simplifying the fraction 23/144:

$$\frac{23}{144} \div \frac{23}{23} = \frac{1}{6.216}$$
$$\frac{1}{6.216} \div \frac{1}{1} = \frac{1}{6.216}$$
$$\frac{1}{6.216} \div \frac{1}{1} = \frac{1}{6.216}$$

Typically, you use the MANSHIP simplification mode with the a.b/c display format made for teaching or learning fraction concepts. The display format of fraction results can vary when you are using MANSHIP and a.b/c.

- When you simply enter a fraction and press **ENTER**, the format in which you entered the fraction is preserved.



The calculator display shows the fraction 3/4 in the a.b/c format:

$$\frac{3}{4}$$

- When you add or subtract using a mixed fraction, calculation takes place on the whole-number and fractional part of the mixed-fraction separately. The result is displayed in a mixed fraction.



The calculator display shows the addition of two mixed fractions:

$$1\frac{2}{3} + 2\frac{4}{6} = 3\frac{8}{6}$$

- When you multiply or divide using a mixed fraction, the result is displayed as a simple fraction.



The calculator display shows the multiplication of two mixed fractions:

$$1\frac{2}{3} \times 2\frac{1}{3} = \frac{11}{3}$$

Entering and Using Fractions in Calculations

The TI-83 lets you enter fractions directly from the keyboard.

Entering Simple Fractions

A simple fraction is a fraction with no whole-number part, for example, $\frac{3}{4}$ or $\frac{4}{3}$.

To enter a simple fraction:

- 1 Enter the numerator (up to six digits), and then press $\frac{\Box}{\Box}$ [a].
- 2 Enter the denominator (up to and including 1000).

For example, press 3 $\frac{\Box}{\Box}$ [a] 3 to enter $\frac{3}{3}$.

Entering Mixed Fractions

A mixed fraction is a fraction that has both a whole-number and a fractional part, for example $1\frac{1}{3}$.

To enter a mixed fraction:

- 1 Enter the units (up to three digits), and then press $\frac{\Box}{\Box}$ [a].
- 2 Enter the numerator (up to three digits), and then press $\frac{\Box}{\Box}$ [a].
- 3 Enter the denominator (up to and including 1000).

For example, press 5 $\frac{\Box}{\Box}$ [a] 2 $\frac{\Box}{\Box}$ [a] 3 to enter $5\frac{2}{3}$.

In general, you can use fractions in expressions just as you would use other numbers. The results of the expressions, however, may or may not be fractions.

Using Fractions in Expressions

The absolute value of a fraction on the TI-80 cannot be ± 999 .

$\frac{\square}{\square}$, $\frac{\square}{\square}$, $\frac{\square}{\square}$, $\frac{\square}{\square}$, $\frac{\square}{\square}$, $\frac{\square}{\square}$, and $\frac{\square}{\square}$ [Frac] [Frac] accept fraction entries and return fraction results. If the absolute value of a fraction result is ± 1000 , or if the results of operations with these functions are not within the limits shown on page 3-6, the results are given in decimal form.

Other functions accept fraction entries, but convert them to decimal form before operating on them. The results are given in decimal form. For example, $\sqrt{4/9}$ returns .666666667, not $2/3$.

If you use $\rightarrow\text{SIMP}$ with a fraction that has been converted to a decimal, an error occurs.

If an expression contains both a fraction and a decimal number, the result is displayed as a decimal number.

You can also enter fractions in a list, but the results are returned as decimal values.

$1+1/2 \div .25$	1.75
$1+1/2 \div 1$	1.5
$(1/4) \div (1/4) \div (1/4)$	1.5

The FRACTION Menu

To display the FRACTION menu, press $\boxed{\text{Frac}}$. The menu items let you simplify and convert fractions. When you select a menu item, the name is copied to the cursor location.

FRACTION Menu

FRACTION

- 1: \rightarrow SIMP Simplifies the fraction
- 2: \rightarrow D \rightarrow F Converts to a simple fraction
- 3: \rightarrow M \rightarrow L \rightarrow F Converts to a mixed fraction
- 4: \rightarrow D \rightarrow FAC Converts a decimal to a fraction based on mode
- 5: \rightarrow DEC Converts a fraction to a decimal

Simplifying Fractions

\rightarrow SIMP

\rightarrow SIMP (simplify fractions, FRACTION item 1) simplifies the specified fraction and displays it, along with the simplification factor.

Note: \rightarrow SIMP can only be used in **MANDSIMP** mode.

You have two options for simplifying fractions:

- You can let the calculator simplify the fraction, step-by-step, using the lowest common denominator (LCD), or

(fraction \rightarrow SIMP)

10/1440 \rightarrow SIMP	\rightarrow 5/720
Factor=1	
MULT \rightarrow SIMP	
Factor=5	1/144

- You can choose a factor (an integer) for simplifying the fraction.

(fraction_factor \rightarrow SIMP)

10/1440 \rightarrow SIMP	\rightarrow 5/720
Factor=5	
MULT \rightarrow SIMP	
Factor=2	1/144

Both simplification options update the variable **FACTOR**.

Converting
Simple and
Mixed Fractions
→b/c
←a.b/c

→b/c (convert to simple fraction, **FRACTION**, item 2) converts value to a simple fraction

←a.b/c (convert to mixed fraction, item 3) converts value to a mixed fraction

value→b/c

value←a.b/c

47/7←a.b/c	1_6/7
4_3/20←a.b/c	5_1/2
880/64/c	11_1/2

Both →b/c and ←a.b/c can be used only at the end of an expression. A **GETC()** instruction, however, can follow them.

The FRACTION Menu (Continued)

Converting Decimals and Fractions ►FRAC ◄DEC

►FRAC (convert to fraction, **FRACTION** item 4) converts a decimal value to its fraction equivalent and displays it. The decimal may be a number, expression, or list.

In **MAHSIMP** mode, ►FRAC first attempts to return a fraction in terms of 10ths, 100ths, or 1000ths. If this is not possible, ►FRAC converts the decimal to its fraction equivalent as it would in **AUTOSIMP** mode. If the value cannot be converted or if the denominator of the equivalent fraction is greater than 1000, the decimal equivalent is returned.

The form of the ►FRAC result depends on the current fraction display format. For example, 1.25 ►FRAC returns 1 1/4 if a./b/c is selected or 5/4 if b/c is selected.

If the decimal value for ►FRAC is a list, the list is displayed as fractions, but it is still stored internally as decimal form.

◄DEC (convert to decimal, **FRACTION** item 5) converts a fraction value to its decimal form and displays it.

decimal►FRAC

fraction◄DEC

AUTOSIMP & a./b/c

4P10÷7P1	1.4P1
ANS◄DEC	1.8
ANS►FRAC	1.4P1

MAHSIMP & a./b/c

4P10÷7P1	+18P10
ANS◄DEC	1.8
ANS►FRAC	+1.8P10

AUTOSIMP & b/c

4P10÷7P1	5P1
ANS◄DEC	1.8
ANS►FRAC	5P1

MAHSIMP & b/c

4P10÷7P1	+18P10
ANS◄DEC	1.8
ANS►FRAC	+18P10

Both ►FRAC and ◄DEC are valid only at the end of an expression. A \rightarrow **DIS**(**DE**) instruction, however, can follow them.

Chapter 4: Function Graphing

This chapter describes function graphing on the TI-80 in detail. It also lays the foundation for using the parametric graphing features described in Chapter 5.

Chapter	Getting Started: Graphing a Circle	4-2
Contents	Defining a Graph	4-3
	Setting Graph Modes	4-4
	Defining Functions in the Y= List	4-5
	Evaluating Y= Functions in Expressions	4-7
	Selecting Functions	4-8
	Defining the Viewing Window	4-9
	Displaying a Graph	4-11
	Exploring a Graph with the Free-Moving Cursor	4-12
	Exploring a Graph with TRACE	4-13
	Exploring a Graph with ZOOM	4-15
	Setting the Zoom Factors	4-18

Getting Started: Graphing a Circle

Getting Started is a fast-paced introduction. Read the chapter for details.

Graph a circle of radius 10, centered on the origin in the standard viewing window. To graph a circle, you must enter separate formulas for the upper and lower portions of the circle. Then use **ZSQUARE** to adjust the display to make the functions appear as a circle.

Make sure that your TI-80 is in **FUNC** mode and all **STAT PLOTS** are turned off.

1. Press **[Y=]** to display the Y= edit screen. Press **[2nd][X-1]** **[+]** **[100]** **[+]** **[2nd][X-2]** **[+]** **[0]** **[+]** **[0]** **[+]** **[0]** to enter the expression $Y1 = \sqrt{100 - X^2}$ to define the top half of the circle.

The bottom half of the circle is defined by $Y2 = -\sqrt{100 - X^2}$. However, you can also define one function in terms of another, so to define $Y2 = -Y1$, press **[+]** **[2nd][Y-Var]** (to display the Y= variables menu) **[1]** (to select $Y1$).



2. Press **[2nd][0]** **[8]** to select **ZSTANDARD**. This is a quick way to reset the Window variables to the standard values. It also graphs the functions; you do not need to press **[GRAPH]**.

Notice that the functions appear as an ellipse in the standard viewing window.



3. To adjust the display so each "dot" represents an equal width and height, press **[TIOFF]**, and then **[8]** to select **ZSQUARE**. The functions are replotted and now appear as a circle on the display.



4. To see the **ZSQUARE** Window variables, press **[2nd][0]** **[5]** and note the values for **XMIN**, **XMAX**, **YMIN**, and **YMAX**.



5. If you want to see the graph again, press **[GRAPH]**.

Defining a Graph

To define a graph, you set the modes, enter and select the functions to graph, and define the viewing window and the graphing format. Once you have defined a graph, you can plot it, display it, and explore it.

Steps in Defining a Graph

There are six basic steps to defining a graph, although you may not need to take all of the steps each time you define a graph. The procedures are described in detail on the following pages.

1. Set the mode to **FUNC** graphing (Chapter 1)
2. Enter or edit a function in the **Y=** list (page 4-5).
3. Select the **Y=** function you want to graph (page 4-8)
4. Define the viewing window (page 4-8)
5. Set the graphing format (page 4-11)
6. Deselect **STAT PLOTS** if appropriate (Chapter 9)

Exploring a Graph

Once you have defined a graph, you can display it and use several tools on the TI-80 to explore the behaviour of the function or functions. These tools are described later in this chapter.

Setting Graph Modes

Pressing **MODE** displays the current mode settings, as described in Chapter 1. For function graphing, the graphing mode must be set to **FUNC**. Before you graph a function, check to make sure that the mode settings are appropriate.

Checking and Changing Graphing Modes

Press **MODE** to display the mode settings. The current settings are highlighted.

The TI-80 has two graphing modes.

- **FUNC** (function graphing)
- **PARAM** (parametric graphing)

To graph functions, you must select **FUNC** (function graphing).

The basics of graphing on the TI-80 are described in this chapter. Differences in parametric graphing are described in Chapter 5.

The mode settings can affect how functions are graphed.

- **RADIAN** or **DEGREE** mode may affect how some functions are interpreted.
- **CONNECTED** or **DOT** affects how the selected functions are plotted.
- **SEQUENTIAL** or **SMUL** affects how functions are plotted if you have selected more than one function.

Setting Modes from a Program

You can set the graphing mode and other modes from a program.

Begin on a blank line in the program editor. Press **MODE** to display the **MODE** screen. Press **→** and **←** to place the cursor on the mode that you want to select, and then press **ENTER**. The name of the mode is copied to the cursor location.

Defining Functions in the Y= List

Pressing Y= displays the Y= edit screen. This is where you enter the functions to graph. You can store up to four functions in memory at one time. You can graph one or more of these functions at a time.

Displaying the Functions in the Y= List

Press Y= to display the Y= edit screen. In the example below, the Y1 and Y2 functions are defined.



Defining a New Function

To define a new function in the Y= list,

1. Press Y= to display the Y= edit screen.
2. Move the cursor to the function in the Y= list you want to define. If necessary, press DEL to erase a previously entered function.
3. Enter the expression to define the function.
 - You may use functions and variables (including Rtc) in the expression. If the expression evaluates to a value that is not a real number, that point is not plotted, an error does not occur.
 - The independent variable in the function is X . You may press X,T , rather than pressing ALPHA X , to enter the X variable. (P/ABC mode defines the independent variable as X .)
 - The expression is stored as one of the four user-defined functions in the Y= list as you enter it.
4. When you complete the expression, press ENTER to move to the beginning of the next function.

Note: When you enter a function, it is automatically selected for graphing in the Y= list. This is indicated by the highlighted equal sign. For details on selecting and deselecting functions, see page 4-5.

Defining Functions in the Y= List (Continued)

Editing a Function

To edit a function in the Y= list:

1. Press **(F1)** to display the Y= list and move the cursor to the function you want to change.
2. Make the changes. You can also press **(CLEAR)** to erase the expression, and then enter a new expression.

The expression is stored in the Y= list and selected (turned on) as you edit it.

Clearing a Function

To clear or erase a function on the Y= edit screen, position the cursor anywhere on the function, and then press **(CLEAR)**.

Defining Functions from the Home Screen or a Program

To define a function from the Home screen or from a program, begin on a blank line:

1. Press **(ALPHA)** **(F1)** **[]**, enter the expression, and then press **(ALPHA)** **(F1)** **[]** again.
2. Press **(RTN)**.
3. Press **(F2)** **[Y-VARS]**, and then select the name of the function from the Y menu. The name is copied to the cursor location.
4. Press **(RTN)** to complete the instruction.

"expression"→Y_n



When the instruction is executed, the TI-84 stores the expression in the Y= list, selects (turns on) the function, and displays the message **DONE**.

Leaving the Y= Edit Screen

To leave the Y= edit screen:

- Select another screen by pressing the appropriate key, such as **(ALPHA)** **(F1)** or **(RTN)**.
- Press **(F2)** **[Quit]** to return to the Home screen.

Evaluating Y= Functions in Expressions

You can calculate the value of a Y= function at a specified value of X.

Entering the Functions in the Y= List



To display the Y= list, press 2ND Y= . Enter these functions for Y1, Y2, and Y3: X^2 , $X+2$, and $Y1(Y2(X))$.

Y= X^2
 Y= $\text{X}+2$
 Y= $\text{Y1}(\text{Y2}(\text{X}))$

Y= X^2
 Y= $\text{X}+2$
 Y= $\text{Y1}(\text{Y2}(\text{X}))$
 Y=

Evaluating Functions



To evaluate the functions, first specify the value of X. Note that X may be a list.

2ND Y= X 1,2,3
 Y= Y1 Y2 X 1,2,3
 Y= Y1 Y2 X 1,2,3
 Y= Y1 Y2 X 1,2,3
 Y= Y1 Y2 X 1,2,3

$\text{Y2}(\text{X})$
 $\text{Y2}(\text{X})$ 8
 $\text{Y2}(\text{X})$ 3
 $\text{Y2}(\text{X})$ 9
C9 16 25

Evaluating Functions without Parentheses



You can also evaluate functions without using parentheses by storing a value to X.

2ND Y= X 1,2,3
 Y= Y1 Y2 X 1,2,3

$\text{X}=\text{X}$
 Y1 3
 Y2 9

Selecting Functions

Only functions that are selected (turned on) are graphed.
All four functions may be selected at one time.

Turning a Function "On" or "Off"

You can select and deselect ("turn on" and "turn off") functions on the **Y=** edit screen. The α sign on a selected function is highlighted.

To change the selection status of a function,

1. Display the **Y=** list and move the cursor to the function whose status you want to change.
2. Press $\boxed{\alpha}$ to place the cursor over the α sign of the function.
3. Press $\boxed{\text{ON/OFF}}$ to change the status. If the function was selected, it is now deselected. If it was deselected, it is now selected.

Note: When you enter or edit a function, it is selected automatically. When you clear a function, it is deselected.

Selecting Functions from the Home Screen or a Program

To select functions from the Home screen or a program, begin on a blank line.

1. Press $\boxed{\text{ON/OFF}}$ [**Y=**], and then press $\boxed{\alpha}$ to select **ON/OFF**. The **ON/OFF** menu is displayed.
2. Select the instruction you want, **FROM** or **FN:OFF**. It is copied to the cursor location.
3. To turn specific functions on or off, enter the number(s) of the function(s) separated by commas.

FROM function#,function#,
FN:OFF function#/function#,

For example, in **FUNC** mode, **FN:OFF 1,3** turns off functions **Y1** and **Y3**.

FN:OFF 1,3 **NAME**

Defining the Viewing Window

The Window variables determine the boundaries and other attributes of the viewing window. The window variables are shared by all graphing modes.

The Viewing Window

The viewing window of the TI-80 is the portion of the coordinate plane defined by $XMIN$, $XMAX$, $YMIN$, and $YMAX$. The distance between tick marks is defined by $XSCAL$ for the X axis and $YSCAL$ for the Y axis.



Checking the Viewing Window

Press **2ND** **WINDOW** to display the current Window variable values. The values shown here are the default values.



Changing a Window Variable Value

To change a Window variable value:

1. Press **2ND** **WINDOW** to move to the Window variable you want to change.
2. To enter a real value (which can be an expression), you may do any of the following:
 - Position the cursor, and then make the changes.
 - Press **2ND** **ENTER** to clear the value, and then enter a new value.
 - Begin entering a new value. The original value is cleared automatically when you begin typing.
3. Press **2ND** **ENTER**, **□**, or **□**. If you entered an expression, it is evaluated. The new value is stored.

$XMIN$ must be less than $XMAX$, and $YMIN$ must be less than $YMAX$, or you will get an error message when you press **2ND** **ENTER**. To turn off the tick marks, set $XSCAL=0$ and $YSCAL=0$.

Leaving the Window Screen

To leave the Window screen:

- Select another screen by pressing the appropriate key, such as $\boxed{\text{ZOOM}}$ or $\boxed{\text{F1}}$.
- Press $\boxed{\text{2nd}} \boxed{\text{EXIT}}$ to return to the Home screen.

Storing to a Window Variable from the Home Screen or a Program

To store to a Window variable from the Home screen or from a program, begin on a blank line:

1. Enter the value (which can be an expression) that you want to store.
2. Press $\boxed{\text{STO}}$.
3. Press $\boxed{\text{VAR}}$ to display the **VAR** menu.
4. Select **WINDOW** to display the Window variables.
5. Select the Window variable. The name of the variable is copied to the cursor location.
6. Press $\boxed{\text{ENTER}}$ to complete the instruction.

```

15→XMIN
┌──────────┐
└──────────┘

```

Note: You can use a Window variable in an expression by performing steps 1, 4, and 5.

ΔX and ΔY

The variables ΔX and ΔY define the distance between the centres of two adjoining pixels on a graph (graphing accuracy).

$$\Delta X = \frac{(X_{\text{MAX}} - X_{\text{MIN}})}{62} \qquad \Delta Y = \frac{(Y_{\text{MAX}} - Y_{\text{MIN}})}{46}$$

ΔX and ΔY are not on the Window screen, however they are accessible through the **VAR** **WINDOW** menu. ΔX and ΔY are calculated from X_{MIN} , X_{MAX} , Y_{MIN} , and Y_{MAX} when a graph is displayed.

You can store values directly to ΔX and ΔY (7 and 8 on the **VAR** **WINDOW** menu), in which case X_{MAX} and Y_{MAX} are immediately calculated from ΔX , X_{MIN} , ΔY , and Y_{MIN} .

```

1→ΔX
┌──────────┐
└──────────┘

```

Pressing **[GRAPH]** graphs any functions selected on the Y= edit screen. The current mode settings apply, and the current values of the Window variables define the viewing window.

Turning the Grid Points On and Off

Grid points correspond to the axis tick marks. To turn the grid points on and off use **GRIDON** and **GRIDOFF**. The default for the TI-80 is **GRIDOFF**.

1. From the Home screen, press **[2nd]** **[STAT]** to display the **DRAW** menu.
2. Press **6** to select **GRIDON**, or press **0** to select **GRIDOFF**.
3. Press **[ENTER]**. The message **DONE** is displayed.

Displaying a New Graph

Press **[GRAPH]** to display the graph of the selected function or functions. (Some operations, such as **TRACE** and the Zoom instructions, display the graph automatically.) As a graph is plotted, the busy indicator is on and **X** and **Y** are updated.

Smart Graph

When you press **[GRAPH]**, Smart Graph displays the graph screen immediately if nothing has changed that requires the functions to be replotted since the last time the graph was displayed.

If you have changed any of the following since the graph was last displayed, pressing **[GRAPH]** replots the graph based on the new values:

- Changed a mode setting that affects graphs.
- Changed a function in the current picture.
- Deselected a function in the current picture.
- Changed the value of a variable in a selected function.
- Changed a Window variable or format setting.
- Cleared drawings by selecting **CLEAR** (Chapter 7).
- Changed or turned off a **STAT PLOT** definition (Chapter 9).

Note: **CLEAR** is a fast way to replot a graph.

Overlaying Functions on a Graph

The TI-80 lets you graph one function at a time without reploting every function. For example, enter **SIN X** as **Y1** and press **[GRAPH]**. Then enter **COS X** as **Y2** and press **[GRAPH]** again. The second function is graphed on top of the original function.

Exploring a Graph with the Free-Moving Cursor

While a graph is displayed, you can move the free-moving cursor anywhere on the graph and display the coordinates of any location on the graph.

Free-Moving Cursor

You can press \leftarrow , \rightarrow , \uparrow , or \downarrow to move the cursor around the graph. When you first display the graph, no cursor is visible. As soon as you press \leftarrow , \rightarrow , \uparrow , or \downarrow , the cursor moves from the centre of the viewing window.

As you move the cursor around the graph, the values of the variables X and Y are updated, and the coordinate values of the cursor location are displayed at the bottom of the screen. Coordinate values generally appear in floating decimal format. The numeric display settings on the **MODE** screen do not affect coordinate display.

To see the graph without the cursor or coordinate values, press **GRAPH** or **2ND** **GRAPH**. When you press \leftarrow , \rightarrow , \uparrow , or \downarrow , the cursor begins to move from the same position.

Graphing Accuracy

The free-moving cursor moves from dot to dot on the screen. When you move the cursor to a dot that appears to be "on" the function, it may be near, but not on, the function; therefore, the coordinate value displayed at the bottom of the screen is not necessarily a point on the function. To move the cursor along a function, use **TRACE** (page 4-13).

The displayed coordinate values of the free-moving cursor approximate actual math coordinates accurate to within the width/height of the dot. As **XMIN** and **XMAX** (and **YMIN** and **YMAX**) get closer together (after a **ZOOM IN**, for example), graphing accuracy increases, and the coordinate values more closely represent the math coordinates.



- Free-moving cursor "on" the curve

Exploring a Graph with TRACE

TRACE moves the cursor from one plotted point to the next, along a function. The cursor coordinates are displayed at the bottom of the screen.

Beginning a Trace

Press **[TRACE]** to begin a trace. If the graph is not displayed already, the TI-86 displays it. The cursor is on the first selected function in the **Y=** list at the middle **X** value on the screen. The number of the function appears at the top right of the display.

Note: If any **STAT PLOTS** are turned on, the TI-86 attempts to trace the first stat plot.

Moving along a Function

Press **[←]** and **[→]** to move the cursor along the function. Each press moves the cursor from one plotted point to the next. Press **[2nd]** **[F1]** and **[2nd]** **[F2]** to move the cursor five plotted points at a time. Tracing updates and displays the values of the variables **X** and **Y**. The **Y** value is calculated from the **X** value; that is, $Y = Y_n(X)$. If the function is undefined at an **X** value, the **Y** value is blank.



- Trace cursor on the curve

If the **Y** value of a function is above or below the viewing window, the cursor disappears as you move it to that portion of the function. However, the coordinate values at the bottom of the screen indicate the cursor coordinates.

Panning to the Left or Right

If you trace a function off the left or right edge of the screen, the viewing window automatically pans to the right or left. **XMIN** and **XMAX** are updated to correspond to the new viewing window.

Note: The screen does not pan if a **STAT PLOT** is on.

QuickZoom

While tracing, you can press **[ZOOM]** to adjust the viewing window so that the cursor location becomes the centre of a new viewing window, even if the cursor is above or below the display. This allows “panning” up and down. After QuickZoom, **TRACE** is still active.

Exploring a Graph with TRACE (Continued)

Moving from Function to Function

To trace another selected function on the graph, press \leftarrow or \rightarrow to move the cursor to that function. The cursor moves to the new function at the same X value. The function number in the top right corner of the display changes.

The cursor movement is based on the order of the selected functions in the Y= list, not the appearance of the functions as graphed on the screen.

Leaving TRACE

To leave TRACE:

- Select another screen by pressing the appropriate key, such as WINDOW or ZOOM .
- Press GRAPH or CLIO to see the graph without the Trace cursor.
- Press $\text{2ND} \text{ } \text{QUIT}$ to return to the Home screen.

The Trace cursor remains in the same location if you leave TRACE and return, as long as Smart Graph has not caused the graph to be replotted.

Using TRACE in a Program

On a blank line in the program editor, press TRACE . The instruction TRACE is copied to the cursor location. When the instruction is encountered during program execution, the graph is displayed with the Trace cursor on the first selected function. As you trace, the cursor coordinate values are updated. When you finish tracing functions, press ENTER to resume program execution.

Exploring a Graph with ZOOM

Pressing **[[ZOOM]]** displays a menu that allows you to adjust the viewing window of the graph quickly in a variety of ways. All of the Zoom instructions are accessible from programs.

ZOOM Menu

ZOOM		
1: ZBOX	Draws box to define viewing window	
2: ZOOM IN	Magnifies graph around cursor	
3: ZOOM OUT	Views more of graph around cursor	
4: ZDECIMAL	Sets 1 as decimal	
5: ZSQUARE	Sets equal-sized dots on X and Y axes	
6: ZSTANDARD	Sets standard Window variables	
7: ZTRIG	Sets built-in trig Window variables	

ZBOX

ZBOX lets you use the cursor to select opposite corners of a box to define a new viewing window.

1. Select **ZBOX** from the **ZOOM** menu. The diamond type of cursor at the centre of the screen indicates that you are using a Zoom instruction.
2. Move the cursor to any corner of the box you want to define, and then press **[[ENTER]]**. As you move the cursor away from the point just selected, you see a small square dot, indicating that the first corner is selected.
3. Move the cursor to the opposite diagonal corner of the box you want to define. As you move the cursor, the boundaries of the box change on the screen.



Note: Before you press **[[ENTER]]**, you can cancel **ZBOX** at any time by pressing **[[2ND]]**.

4. When the box is defined as you want it, press **[[ENTER]]** to replot the graph.



You can repeat steps 2 to 4 to do another **ZBOX**.

ZOOM IN ZOOM OUT

ZOOM IN magnifies the graph around the cursor location. The **XFACT** and **YFACT** settings determine the extent of the zoom (page 4-18). The default value for both **XFACT** and **YFACT** is 4.

- 1 After checking or changing **XFACT** and **YFACT**, select **ZOOM IN** from the **ZOOM** menu.

Notice the different type of cursor. It indicates that you are using a Zoom instruction.

- 2 Move the cursor to the point that you want as the center of the new viewing window, and then press **ENTER**.

The TI-80 adjusts the viewing window by **XFACT** and **YFACT**, updates the Window variables, and replots the selected functions centered on the cursor location.

- 3 **ZOOM IN** is still turned on. To zoom in on the graph again:
 - At the same point, press **ENTER**.
 - At a new point, move the cursor to the point that you want as the center of the new viewing window, and then press **ENTER**.

ZOOM OUT displays a greater portion of the graph centered on the cursor location to provide a more global view. The procedure for **ZOOM OUT** is the same as for **ZOOM IN**.

Leaving ZOOM IN or ZOOM OUT

To leave **ZOOM IN** or **ZOOM OUT**:

- Select another screen by pressing the appropriate key, such as **TABLE** or **PPPP**.
- Press **END** **QUIT** to return to the Home screen.

ZDECIMAL	ZDECIMAL replots the functions immediately, updates the window variables to preset values that set ΔX and ΔY equal to 1, and defines the X and Y value of each panel as one decimal.
	$XMIN = -3.1$ $YMIN = -2.3$ $XMAX = 3.1$ $YMAX = 2.3$ $XCCL = 1$ $YCCL = 1$
ZSQUARE	ZSQUARE replots the functions immediately, redefining the window based on the current Window variables, but adjusted in only one direction so that $\Delta X = \Delta Y$. This makes the graph of a circle look like a circle. $XCCL$ and $YCCL$ remain unchanged. The midpoint of the current graph (not the intersection of the axes) becomes the midpoint of the new graph.
ZSTANDARD	ZSTANDARD replots the functions immediately, updating the Window variables to the standard values.
	$XMIN = -10$ $YMIN = -10$ $XMAX = 10$ $YMAX = 10$ $XCCL = 1$ $YCCL = 1$
ZTRIG	ZTRIG replots the functions immediately, updating the Window variables to preset values appropriate for plotting trig functions in RADIAN mode. These are:
	$XMIN = -(5\pi/12) \approx -4.115791...$ $YMIN = -2$ (-2) $XMAX = (5\pi/12) \approx 4.115791...$ $YMAX = 2$ (2) $XCCL = (\pi/2) \approx 1.570796...$ $YCCL = 1$ (1)

Setting the ZOOM Factors

The Zoom factors, **XFACT** and **YFACT**, determine the extent of the change for the viewing window created by **ZOOM IN** or **ZOOM OUT** on a graph.

Zoom Factors

Zoom factors are positive numbers (not necessarily integers) greater than or equal to 1. They define the magnification or reduction factor used to **ZOOM IN** or **ZOOM OUT** around a point.

Checking Zoom Factors

To review the current values of the Zoom factors (**XFACT** and **YFACT**):

1. Press **[F5]**, and then press 1 to select **WINDOW**.
2. Press 8 to select **XFACT** or 9 to select **YFACT**. **XFACT** or **YFACT** is copied to the cursor location.
3. Press **[F5]**. The Zoom factor is displayed:

```
1->XFACT      3
2->YFACT      3
```

Setting Zoom Factors from the Home Screen or a Program

To set the zoom factors **XFACT** and **YFACT** from the Home screen or a program:

1. Enter the factor, and then press **[F5]**.
2. Press **[F5]**, and then press 1 to select **WINDOW**.
3. Press 8 to select **XFACT** or 9 to select **YFACT**. **XFACT** or **YFACT** is copied to the cursor location on the Home screen.
4. Press **[F5]** to store the Zoom factor to the variable

```
XFACT      4
2->XFACT    2
```

Chapter 5: Parametric Graphing

This chapter describes how to graph parametric equations on the TI-80. Before going on to parametric graphing, you should be familiar with Chapter 4, *Function Graphing*.

Chapter	Getting Started: Path of a Ball	5-2
Contents	Defining and Displaying a Parametric Graph	5-3
	Exploring a Parametric Graph	5-6

Defining and Displaying a Parametric Graph

Parametric equations consist of an X component and a Y component, each expressed in terms of the same independent variable T . They are often used to graph equations over time. Up to three pairs of parametric equations can be defined and graphed at a time.

Defining a Parametric Graph

The steps for defining a parametric graph are the same as those for defining a function graph (page 4-3). The differences are listed below.

Setting Parametric Graph Modes

Press **[MODE]** to display the mode settings. To graph parametric equations, you must select **PARAM** before you enter Window variables or enter the components of parametric equations. Normally, you should also select **CONNECTED** to obtain a more meaningful parametric graph.

Displaying Parametric Equations

After selecting **PARAM** mode, press **[F2]** to display the parametric **Y=** edit screen.



On this screen, you display and enter both the X and Y components. The TI-80 allows three parametric equations, each defined in terms of T .

Defining Parametric Equations

Follow the same procedures as for function graphing (pages 4-5 to 4-6) to enter the two components that define a new parametric equation.

- You must define both the X and Y components in a pair.
- The independent variable in each component is T . You may press **[T]**, rather than pressing **[ALPHA]** **[T]**, to enter the parametric variable T (PARAM mode defines the independent variable as T).

Selecting Parametric Equations

The TI-80 graphs only those parametric equations you select. The highlighted **a** sign on both components of an equation indicates that the equation is selected.

You may select any or all of the equations on the parametric **Y=** edit screen.

To change the selection status of a parametric equation, press **[Δ]** to move the cursor onto the **a** sign of either the **X** or **Y** component and press **[ENTER]**. The status of both the **X** and **Y** components changes.

Note: When you enter both components of an equation or edit either component, that equation is selected automatically.

Setting Window Variables

Press **[WINDOW]** to display the current Window variable values. The Window variables define the viewing window. The values shown are the standard values in **RADIAN** mode.

TMIN=0	Smallest T value to evaluate
TMAX=6.283185307	Largest T value to evaluate
TSHP= 1.206996938898	T value increment
XMIN=-10	Smallest X value to be displayed
XMAX=10	Largest X value to be displayed
XSC=1	Spacing between X tick marks
YMIN=-10	Smallest Y value to be displayed
YMAX=10	Largest Y value to be displayed
YSC=1	Spacing between Y tick marks

To change a Window variable value, follow the steps given for function graphing (page 4-8).

Note: You may want to change the T variable values to ensure that sufficient points are plotted.

Displaying a Graph

When you press **GRAPH**, the TI-80 plots the selected parametric equations. It evaluates both the **X** and the **Y** components for each value of **T** (from **TMIN** to **TMAX** in intervals of **TSTEP**) and then plots each point defined by **X** and **Y**. The Window variables define the viewing window.

As a graph is plotted, the TI-80 updates **X**, **Y**, and **T**.

Note: Smart Graph applies to parametric graphs also (page 4-11).

VARS WINDOW and Y-VARS Menus

By means of the **VARS WINDOW** and **Y-VARS** menus, you can:

- Access functions by using the name of the component of the equation as a variable.
- Select or deselect parametric equations from a program, using the **FNON** and **FNOFF** commands (page 4-5).
- Store parametric equations.
- Store values directly to Window variables.



Exploring a Parametric Graph

As in Function graphing, three tools are available for exploring a graph: the free-moving cursor, tracing, and zooming.

Free-Moving Cursor

The free-moving cursor works the same in parametric graphing as in function graphing (page 4-12).

Tracing a Parametric Graph

Pressing **TRACE** puts the Trace cursor on the first selected equation, at **TMIN**. You can then trace along the equation.

▢ or ▢	Moves the cursor one TSTEP at a time.
▢ ▢ or ▢	Moves the cursor five TSTEP s at a time.
▢ or ▢	Changes to the previous or next equation. The equation number is displayed in the top right of the display.
2ND QUIT	Cancels tracing.

For each value of **T**, the calculator displays values for **X** and **Y**.

The values for **X**, **Y**, and **T** are updated as you move the Trace cursor. If the cursor moves off the top or bottom of the screen, the coordinate values continue to change appropriately.

The Trace cursor remains in the same location if you leave **TRACE** and return, unless Smart Graph replaces the graph.

QuickZoom is available in parametric graphing, but panning is not (page 4-13).

Zooming In on a Parametric Graph

Pressing **QZ** works the same in parametric graphing as in function graphing (page 4-15).

Parametric graphing adds the Window variables **TMIN**, **TMAX**, and **TSTEP**. These variables are not affected by zooming unless you select **ZSTANDARD**, where **TMIN** = 0, **TMAX** = $6.283185307 (2\pi)$, and **TSTEP** = $1.000000000E-6 (1/1,000,000)$.

Chapter 8: Tables

This chapter describes how to use tables on the TI-80. A table evaluates the selected functions from the Y= list and displays each value for the independent variable along with the evaluated value for each corresponding dependent variable.

Chapter	Getting Started: Basics of a Function	0-2
Contents	Defining the Independent Variable	0-3
	Defining the Dependent Variable	0-4
	Displaying the Table	0-6

Getting Started: Roots of a Function

Getting Started is a fast-paced introduction. Read the chapter for details.

Evaluate the function $Y=X^2-4X+3$ at each integer between -10 and 10. How many sign changes are there and where do they occur?

1. If necessary, select **FUNC** from the **MODE** screen. Press $\boxed{\text{2ND}} \boxed{\text{[TblSet]}}$ to display the **TABLE SETUP** screen. Press $\boxed{\text{10}}$ to set **TBLMIN=-10**. Leave **ΔTBL=1**.



```
TABLE SETUP
TBLIND=-10
ΔTBL=1
```

2. Press $\boxed{\text{Y=}} \boxed{\text{X}^2} \boxed{-} \boxed{4} \boxed{\text{X}} \boxed{+} \boxed{3}$ to enter the function $Y1=X^2-4X+3$.



```
Y1=X^2-4X+3
Y2=
Y3=
Y4=
```

3. Press $\boxed{\text{2ND}} \boxed{\text{[Tab]}}$ to display the table screen.



X	Y1
-10	143
-9	126
-8	111
-7	96
-6	81
-5	66
-4	51
-3	36
-2	21
-1	6
0	-3
1	-4
2	-3
3	0
4	3
5	8
6	15
7	24
8	35
9	48
10	63

4. Press $\boxed{\text{2ND}} \boxed{\text{[Tab]}}$ repeatedly to view the changes in the value of **Y1**.



X	Y1
-10	143
-9	126
-8	111
-7	96
-6	81
-5	66
-4	51
-3	36
-2	21
-1	6
0	-3
1	-4
2	-3
3	0
4	3
5	8
6	15
7	24
8	35
9	48
10	63

Defining the Independent Variable

The independent variable for a table is the independent variable in the current graphing mode (X for FUNC mode and T for PARAM mode). You define the minimum value and the incremental value for the independent variable on the TABLE SETUP screen.

TABLE SETUP Screen

To display the **TABLE SETUP** screen, press $\boxed{\text{2ND}} \boxed{\text{TABLE}}$ (TbSet).
The default values are shown below.



```
TABLE SETUP
TBLMIN=0
ΔTBL=1
```

TBLMIN and ΔTBL

TBLMIN (table minimum) defines the initial value for the independent variable X (FUNC mode) or T (PARAM mode).

ΔTBL (table step) defines the increment for the independent variable.

To change **TBLMIN** and **ΔTBL**, simply enter the values at the flashing cursor. To move between **TBLMIN** and **ΔTBL**, press $\boxed{\text{D}} \boxed{\text{C}}$ and $\boxed{\text{D}} \boxed{\text{B}}$.

Setting Up a Table from the Home Screen or a Program

You can also store values to **TBLMIN** and **ΔTBL** from the Home screen or a program. The variable names are on the **VARS** **TABLE...** menu.

To change **TBLMIN** or **ΔTBL** from the Home screen or a program, begin on a blank line.

1. Enter the value for **TBLMIN** or **ΔTBL**.
2. Press $\boxed{\text{STO}} \boxed{\text{D}}$.
3. Press $\boxed{\text{2ND}} \boxed{\text{VARS}}$ to display the **VARS** menu.
4. Press 3 to select **TABLE...**
5. Select the table variable (**TBLMIN** or **ΔTBL**). The name of the variable is copied to the cursor location.
6. Press $\boxed{\text{2ND}} \boxed{\text{ENTER}}$ to store the value for the table variable.



```
14->TBLMIN    -10
3->ΔTBL        1
```

Defining the Dependent Variable

The selected functions from the **Y=** list define the dependent variables. You can have as many dependent variables as there are functions in the current graphing mode (four for **FUNC** mode and six for **PARAM** mode).

From the **Y=**
Editor

Enter the functions to define the dependent variables in the **Y=** editor.

FUNC Mode

Y1= x^2
Y2=
Y3=
Y4=

PARAM Mode

T1= $\sin(T)$	T2= $\cos(T)$
T3= $\sin(2T)$	T4= $\cos(2T)$
T5= $\sin(3T)$	T6= $\cos(3T)$
T7=	T8=
T9=	T10=

In **PARAM** mode, you must define both components of the parameter, equation (Chapter 5).

Only functions that are selected are displayed in the table. (When **x** is highlighted, the function is selected.) You can select and deselect functions from the **Y=** list, from the Home screen, or from a program. (Refer to page 4-6 for information on selecting and deselecting.)

Displaying the Table

The table displays up to six values for the independent variable, along with the six corresponding values of each dependent variable, one at a time. Once the table is displayed, you can press \leftarrow , \rightarrow , \uparrow , and \downarrow to move around and scroll through the table, displaying other independent and dependent values.

The Table

Press $\left[\text{2ND}\right]\left[\text{TABLE}\right]$ to display the table when

PWNC Mode

X	Y1
0	0
1	1
2	4
3	9
4	16
5	25

PARAM Mode

T	Y1T
0	0
1	1
2	4
3	9
4	16
5	25

The top line displays the name of the independent variable (X for PWNC mode, T for PARAM mode) and one dependent variable (Yn for PWNC mode, XnT or YnT for PARAM mode). The bottom line displays the full value of the current cell, which is indicated by the rectangular cursor. The centre portion is used to display the values of the variables, abbreviated to six digits if necessary.

Displaying More Independent Values

Press \leftarrow and \rightarrow to display additional values for the independent variable and the values for one corresponding dependent variable.

Notes: You can scroll "back" from the value entered for TBLMIN. As you scroll, TBLMIN is updated automatically to the value shown on the top line of the table. In the example below, TBLMIN=0, TBL=1 and $Y1=X^2+2$ generates and displays values of X=0, 1, 2, 3, 4, 5. You can press \leftarrow to scroll backwards and display the table for X=1, 2, 3, 4, 5, 6.

X	Y1
1	3
2	6
3	11
4	18
5	27
6	38

T	Y1T
1	3
2	6
3	11
4	18
5	27
6	38

Displaying the Table (Continued)

Displaying Other Dependent Variables

If you have defined and selected more than one function, press $\boxed{\text{2ND}} \boxed{\text{F1}}$ to display other dependent variables. In the example below, $\text{TBLMM} = 0$, $\text{TBL} = 1$, $Y_1 = X^2 + 2$, and $Y_2 = X^3 - 2$. You can press $\boxed{\text{2ND}} \boxed{\text{F2}}$ to see the values for Y_2 .



X	Y1
0	2
1	3
2	6
3	11
4	18
5	27
6	38
7	51
8	66
9	83
10	102

TBL=1



X	Y2
0	-2
1	-1
2	2
3	7
4	14
5	23
6	34
7	47
8	512
9	729
10	1000

TBL=1

Chapter 7: Draw Operations

This chapter describes how to use the DRAW operations of the TI-80. Before using the DRAW operations, you should be familiar with Chapter 4, Function Graphing.

Chapter	Getting Started: Shading a Graph	7-2
Contents	DRAW DRAW Menu	7-3
	Drawing Lines	7-4
	Drawing Horizontal and Vertical Lines	7-5
	Drawing a Function	7-6
	Shading Areas on a Graph	7-7
	Drawing Points	7-10
	Clearing a Drawing	7-12

Getting Started: Shading a Graph

Getting Started is a fast-paced introduction. Read the chapter for details.

Shade the area below the function $Y=X^2-2$ and above the functions $Y=X+1$ and $Y=-X$.

1. If necessary, select **RUNE** mode. Press $\boxed{\text{F5}}$ and enter the functions.

$Y1=X^2-2$
 $Y2=X+1$
 $Y3=-X$



(Be sure that **Y4** is cleared or turned off.)

2. Press $\boxed{\text{F2}}$ $\boxed{\text{F4}}$ to select the **DECIMAL** viewing window, clear any existing drawings, and display the viewing window and graph.



3. Press $\boxed{\text{F5}}$ $\boxed{\text{HOME}}$ to return to the Home screen.

4. Press $\boxed{\text{F5}}$ $\boxed{\text{DRAW}}$ $\boxed{7}$ to select **SHADE Y<**, which is copied to the Home screen.

5. Press $\boxed{\text{F5}}$ $\boxed{\text{VARS}}$ $\boxed{1}$ (to select **Y1**)

6. Press $\boxed{\text{F5}}$ $\boxed{\text{F1}}$ to add another instruction to this line.



7. Press $\boxed{\text{F5}}$ $\boxed{\text{DRAW}}$ $\boxed{8}$ to select **SHADE Y>**, which is copied to the Home screen.

8. Press $\boxed{\text{F5}}$ $\boxed{\text{VARS}}$ $\boxed{2}$ (to select **Y2**) $\boxed{\text{F5}}$ $\boxed{\text{VARS}}$ $\boxed{3}$ (to select **Y3**)

9. Press $\boxed{\text{F5}}$ $\boxed{\text{F1}}$ to see the functions and shading on the graph.



DRAW DRAW Menu

To display the DRAW DRAW menu, press $\boxed{\text{DRAW}}$ (DRAW). What happens when you select an item from this menu depends on whether or not a graph is displayed when you access the menu, as described under each operation.

DRAW DRAW Menu

DRAW POINTS

1: L1DRAW	Clears all drawn elements.
2: L2LINE	Draws a line between two points.
3: HORIZONTAL	Draws a horizontal line.
4: VERTICAL	Draws a vertical line.
5: DRAWF	Draws a function.
6: SHADE Y>	Shades an area.
7: SHADE Y<	Shades an area.
8: SHADE C	Shades an area.
9: GRID ON	Turns the graph grid on.
0: GRID OFF	Turns the graph grid off.

See page T-11 for an explanation of CL1DRAW.

Before Drawing on a Graph

Because Draw operations draw over the graph of currently selected functions, you may want to do one or more of the following before drawing on a graph.

- Change the mode settings.
- Enter or edit functions in the Y= list.
- Select or deselect functions in the Y= list.
- Change Window variable values.
- Turn STAT PLOTS on or off.
- Clear existing drawings with CL1DRAW (page T-11).

Drawing on a Graph

Draw operations can draw on FUNC and PARAM graphs. The coordinates for all Draw instructions are always the X-coordinate and Y-coordinate values of the display.

You can use most of the operations from the DRAW DRAW and DRAW POINTS menus to draw directly onto a graph, using the cursor to identify coordinates, or you can execute these instructions from the Home screen or a program.

Drawing Lines

While a graph is displayed, **LINE** lets you use the cursor to define a line on the graph. If a graph is not displayed, the instruction is copied to the Home screen.

Directly on a Graph

To define a line directly on a graph.

1. When a graph is displayed, select **LINE** from the **DRAW** screen (Item 2).
2. Position the cursor at the beginning point of the line you want to draw. Press **ENTER**.
3. Move the cursor to the end point of the line you want to draw. The line is displayed as you move the cursor. Press **ENTER**.



To continue to draw lines, repeat steps 2 and 3. To cancel **LINE**, press **ESC**.

From the Home Screen or a Program

LINE (DRAW DRAW, Item 2) draws a line between the coordinates $(X1, Y1)$ and $(X2, Y2)$. The values may be entered as expressions.

LINE($X1, Y1, X2, Y2$)

For example, enter **LINE**(0,0,3,3) on the Home screen and then press **ENTER**.



Drawing Horizontal and Vertical Lines

While a graph is displayed, **HORIZONTAL** and **VERTICAL** let you define lines on the graph using the cursor. If a graph is not displayed, the instruction is copied to the Home screen.

Directly on a Graph

To draw horizontal and vertical lines directly on a graph:

1. When a graph is displayed, select **HORIZONTAL** (item 3) or **VERTICAL** (item 4) from the **DRAW DRAW** menu.
2. A line is displayed that moves as you move the cursor. Position the cursor where you want to draw the line. Press **ENTER**. The line is drawn on the graph.



To continue to draw lines, repeat steps 1 and 2. To cancel **HORIZONTAL** or **VERTICAL**, press **ESC**.

From the Home Screen or a Program

HORIZONTAL (**DRAW DRAW**, item 3) draws a horizontal line at $Y=Y$ (which can be an expression, but not a list).

HORIZONTAL Y

VERTICAL (**DRAW DRAW**, item 4) draws a vertical line at $X=X$ (which can be an expression, but not a list).

VERTICAL X



Note: In the example above, the horizontal line is drawn first, and then the vertical line.

Drawing a Function

DRAWF (draw function) draws a function on the current graph. **DRAWF** must be entered on the Home screen or in the program editor.

Drawing a Function

DRAWF (draw function, **DRAW DRAW**, item 3) is not an interactive operation. It draws the specified expression as a function in terms of X on the current graph.

DRAWF expression

For example, if $Y1 = 2X^2 - 2X + 6$ is the only selected function, **DRAWF Y1-6** plots $Y1$ and then draws the function $Y1-6$ when you press **ENTER**.



Note: You cannot trace on **DRAWF** functions.

Using GRIDON and GRIDOFF

GRIDON (**DRAW DRAW**, item 7) and **GRIDOFF** (**DRAW DRAW**, item 8) set graphs to be drawn with the grid points on or off, respectively. The grid points correspond to the tick marks on the axes. The default for the TI-80 is **GRIDOFF**.

1. From the Home Screen, press **2ND** **DRAW** to display the **DRAW** menu.
2. Press **7** to select **GRIDON**, or press **8** to select **GRIDOFF**.
3. Press **ENTER**. The message **DONE** is displayed. The next time the graph is displayed, the grid points will be on if you selected **GRIDON** or off if you selected **GRIDOFF**.



Shading Areas on a Graph

There are three shading instructions on the DRAW/DRAW menu: SHADE Y>, SHADE Y<, and SHADE(). These instructions are not interactive; they must be entered on the Home screen or in the program editor.

Shading Areas above a Function

SHADE Y> (DRAW/DRAW item 6) takes up to four arguments (functions of X):

SHADE Y>f(x)
SHADE Y>f(x), g(x), h(x), i(x)

When executed, SHADE Y> plots the specified function(s) on the graph and shades the area above the function with a pattern.

The patterns are automatically assigned in the following order:

Function 1	Vertical pattern.
Function 2	Diagonal pattern, bottom left to top right.
Function 3	Diagonal pattern, top left to bottom right.
Function 4	Horizontal pattern.

When you specify multiple functions, the shading is done sequentially.



Shading Areas on a Graph (Continued)

Shading Areas below a Function

SHADE Yc (**DRAW DRAW** lines Y) takes up to four arguments (functions of X):

SHADE Yc/fn1

SHADE Yc/fn1/fn2/fn3/fn4

When executed, **SHADE Yc** plots the specified function(s) on the graph and shades the area below the function with a pattern.

The patterns are automatically assigned in the following order:

Function 1	Horizontal pattern
Function 2	Diagonal pattern, top left to bottom right
Function 3	Diagonal pattern, bottom left to top right
Function 4	Vertical pattern

Note that the patterns are assigned in reverse order from the **SHADE Yc** patterns.

When you specify multiple functions, the shading is done sequentially.

```
SHADE Y<C31N X:0  
=2
```



Shading a Graph

SHADE (**DRAW DRAW** area 8) shades the area on a graph that is below one specified function and above another, between two X values. **SHADE** is not an interactive operation. It draws *lowerfunc* and *upperfunc* in terms of X on the current graph and shades the area that is specifically above *lowerfunc* and below *upperfunc*. Only the areas where *lowerfunc* < *upperfunc* are shaded.

You can specify the shading resolution (an integer between 1 and 9). If none is specified, 1 is used. *resolution*=1 shades every pixel, *resolution*=2 shades every second pixel, *resolution*=3 shades every third pixel, and so on.

Optionally, you can specify *Xleft* (the left boundary) and *Xright* (the right boundary) for the shaded area. If *Xleft* or *Xright* is not specified, *XMIN* and *XMAX* are used.

SHADE(*lowerfunc*,*upperfunc*)

SHADE(*lowerfunc*,*upperfunc*,*resolution*)

SHADE(*lowerfunc*,*upperfunc*,*resolution*,*Xleft*)

SHADE(*lowerfunc*,*upperfunc*,*resolution*,*Xleft*,*Xright*)

```
GRAPH>SE-3,0-1.5  
SHADE: 8-1,SE-2,2  
GRAPH>0.0
```



Drawing Points

To display the **DRAW POINTS** menu, press $\boxed{\text{DRAW}} \boxed{\text{2}}$. What happens when you select an item from this menu depends on whether or not a graph is displayed when you access the menu, as described under each operation.

DRAW POINTS Menu

DRAW POINTS

1: PT-ON

Turn on a point.

2: PT-OFF

Turn off a point.

3: PT-CHANGE

Toggle a point on or off.

Drawing a Point Directly on a Graph

To draw points directly on a graph:

1. When a graph is displayed, select **PT-ON** from the **DRAW POINTS** menu (Item 1).
2. Position the cursor at the location on the display where you want to draw the point. Press $\boxed{\text{ENTER}}$. The point is drawn.



To continue to draw points, repeat step 2. To cancel **PT-ON**, press $\boxed{\text{ENTER}}$.

PT-OFF
PT-CHANGE

The procedures for using **PT-OFF** (point off) **DRAW POINTS**, item 2) to turn off (erase) a point and **PT-CHANGE** (point change) to toggle (reverse) a point on and off are the same as for **PT-ON**.

From the Home Screen or a Program

When you use these instructions from the Home screen or a program, you must specify the X-coordinate and the Y-coordinate of the point as arguments for the instructions.

PT-ON turns on the point at (X=X,Y=Y). **PT-OFF** turns the point off, and **PT-CHANGE** toggles the point between on and off.

```
PT-ON(X,Y)  
PT-OFF(X,Y)  
PT-CHANGE(X,Y)
```

```
PT-ON(2,5)  
PT-OFF(2,5)  
PT-CHANGE(2,5)
```

Clearing a Drawing

All points, lines, and shading drawn on a graph with **DRAW** operations are temporary. They remain only until you execute a **CLRDRAW** (clear drawing) instruction or a change prompts Smart Graph to replot the graph, at which time all drawn elements are erased.

When a Graph Is Displayed

To clear drawings from the currently displayed graph, select **CLRDRAW** from the **DRAW DRAW** menu (item 1). The current graph is plotted and displayed immediately with no drawn elements.

Note that **CLRDRAW** is a quick way to replot the current graph, in addition to clearing the current drawings.

From the Home Screen or a Program

Begin on a blank line on the Home screen or in the program editor. Select **CLRDRAW** from the **DRAW DRAW** menu (item 1). The instruction is copied to the cursor location.

When the instruction is executed, it clears all drawings from the current graph and displays the message **DONE**. The next time you display the graph, all drawn points, lines, and shaded areas will be gone.



```
CLRDRAW      DONE
```

This chapter describes the list features of the TI-80. The TI-80 can store up to six lists. A list, depending on available memory, may contain up to 99 elements.

Chapter	Getting Started: Generating a Sequence . . .	8-2
Contents	About Lists	8-3
	LIST OPS Operations	8-6
	LIST MATH Operations	8-9

Getting Started: Generating a Sequence

Getting Started is a fast-paced introduction. Read the chapter for details.

Calculate the first eight terms of the sequence $1/A^2$ and display them in fraction form.

The **SEQ** function returns a list of values based on five arguments: an expression, a variable to be incremented, a beginning value, an ending value, and an increment.

For this example, the beginning value is 1, the ending value is 8, and the increment is 1.

1. Begin on a blank line on the Home screen. Press **(2nd)** **(LIST)** to display the **LIST OPS** menu.
2. Press **4** to select **SEQ**. The function name is copied to the cursor location on the Home screen.
3. Press **1** **(F1)** **(Frac)**, **A** **(F1)** **(Frac)**, **A** **(F1)** **(Frac)**, **1** **(F1)** **(Frac)**, **8** **(F1)** **(Frac)**, **1** **(F1)** **(Frac)**. Press **(ENTER)** to generate the list and store it in **L1**. The list is displayed on the Home screen.
4. Use **(↓)** to scroll through the list to see all of the elements.
5. Press **(2nd)** **(F4)** to select **FPRAC**. On the Home screen, **ANS** is typed automatically, followed by **FPRAC**.
6. Press **(ENTER)** to show the sequence in fraction form. Use **(↓)** to scroll through the list to see all of the elements.



```
1:2ND
2:LIST
3:SECTRC
4:SEQ
5:R1R8
6:2:5:8
```



```
SEQ(1÷A÷1÷A÷1÷A÷1
1÷A÷1
A÷1÷A÷1÷A÷1÷A÷1
1÷A÷1÷A÷1÷A÷1÷A÷1
```



```
SEQ(1÷A÷1÷A÷1÷A÷1
1÷A÷1
A÷1÷A÷1÷A÷1÷A÷1
1÷A÷1÷A÷1÷A÷1÷A÷1
1÷A÷1÷A÷1÷A÷1÷A÷1
```



```
SEQ(1÷A÷1÷A÷1÷A÷1
1÷A÷1
A÷1÷A÷1÷A÷1÷A÷1
1÷A÷1÷A÷1÷A÷1÷A÷1
1÷A÷1÷A÷1÷A÷1÷A÷1
```


About Lists

The TI-89 has six list variables: L1, L2, L3, L4, L5, and L6. On the Home screen or in a program, you can use, enter, store, and display lists. The list names are on the keyboard. A list may contain a maximum of 99 elements.

Using a List in an Expression

To use a list in an expression, you may:

- Use the name of the list (L1, L2, L3, L4, L5, or L6) in the expression.

$$3+L1$$

- Enter the list directly in the expression.

$$3+(L1,2,3)$$

Entering a List in an Expression

1. Press $\left[\frac{\square}{\square}\right]$ $\left[\left[\frac{\square}{\square}\right]\right]$ to indicate the beginning of the list.
2. Enter a value (which can be an expression) for each element in the list, separated by commas.
3. Press $\left[\frac{\square}{\square}\right]$ $\left[\left[\frac{\square}{\square}\right]\right]$ to indicate the end of the list.

$$3+(L1,2+3,4) \\ \text{C2 10 323}$$

The expression is evaluated when the entry is executed. Commas are required on entry to separate elements, but they are not displayed on output.

Saving a List in Memory

You can save a list in memory in two ways.

- Enter the list in the STAT list editor (Chapter 9).
- Enter the list on a blank line on the Home screen or in a program, press $\left[\frac{\square}{\square}\right]$ $\left[\left[\frac{\square}{\square}\right]\right]$, and then enter the name of the list (L1, L2, L3, L4, L5, or L6).

$$3+(L1,2+3,4)=L2 \\ \text{C2 10 323}$$

Copying One List to Another

To copy a list, store it to another list.

$$L4=L1 \\ \text{C2 10 323}$$

About Lists (Continued)

Displaying a List on the Home Screen

To display the contents of a list on the Home screen, enter the name of the list and press **[2ND]****[F1]**.

An open brace ({) shows a corresponding close brace (}) indicates that a list is too long to be displayed in its entirety. Press **[2]** and **[2]** to display the rest of the list.

Storing to or Recalling a List Element

You can store a value to or recall a value from a specific list element. Enter the name of the list, followed by the number of the element in parentheses. You can store to any element within the currently defined list dimensions, or one beyond.

listname(element)

You can also edit a list by means of the **STAT** list editor (Chapter 4).

Lists in Graphing

You can use a list in a **Y=** expression. However, the list must be used in such a way that it resolves to a single value, for example, **Y1=X+SUM(1/(1.1^(1,2,3)))**.

Note: Unlike the TI-82 and TI-85, you cannot use a list to graph a family of curves.

Notes about Using Math Functions with Lists

A list can be used to input several values for certain functions. (Other chapters and Appendix A state when a list is valid.) The function is evaluated for each element in the list, and a list is returned.

- If a list is used with a function, the function must be valid for every element in the list.

$$\boxed{1 \div (1 + 0) = 1}$$

- This returns an error because 1 is divided by 0.

- If two lists are used with a two-argument function, the lengths of the lists must be the same. The answer is a list in which each element is calculated by evaluating the function according to the corresponding elements in the lists.

$$\boxed{(1 + 2) \cdot 3 = (4 \cdot 5)} \\ (5 \cdot 7 \cdot 9)$$

- If a list and a value are used with a two-argument function, the value is used with each element in the list.

$$\boxed{(1 + 2) \cdot 3 = 4} \\ (5 \cdot 6 \cdot 7) \\ 4(1 + 2) \cdot 3 \\ (4 \cdot 8 \cdot 12)$$

LIST OPS Operations

Press **[F5]** **[LIST]** to display the list operations on the LIST OPS menu.

LIST OPS Menu

OPS	RATH
1: SORTA	Sorts lists in ascending order
2: SORTD	Sorts lists in descending order
3: DIM	Accesses the list dimension
4: SEQ	Create a sequence

Note: SORTA and SORTD are the same as SORTA and SORTD on the STAT EDIT menu.

SORTA SORTD

SORTA (sort ascending, LIST OPS, item 1) and **SORTD** (sort descending, LIST OPS, item 2) have two uses:

- With one list name, they sort the elements of an existing list and update the list in memory.
- With two to six list names, they sort the first list and then sort the remaining lists as dependent lists, placing their elements in the same order as their corresponding elements in the first list. This allows you to keep sets of related data in the same order when you sort lists.

All of the lists to be sorted must be the same length. The sorted lists are updated in memory.

Note: You can reference a specific list only once in these instructions.

SORTA(*listname*)

SORTA(*listname,dependent1,dependent1,L*)

SORTD(*listname*)

SORTD(*listname,dependent1,dependent1,L*)

(5 → 4) → L3	
CS	8 40
SORTA(L3)	
	8000
L3	
	(4 → 4)

SORTA(L3)	
L3	8000
	(8 → 4)

(5 → 4) → L4	
(8 → 3) → L5	
CS	8 40
CS	2 20

=

SORTA(L4,L5)	
L4	8000
	(4 → 8)
L5	(3 → 2)

Accessing List Dimensions with DIM

DIM (dimension) **LIST OPS** item 3) returns the length (number of elements) of the specified list.

DIM list

```
PR C1,3,5,75 4
```

Creating a List with DIM

DIM is used with **LIST** to create a new list with a specified number of elements. The elements of the new list are zeros.

length=DIM listname

```
3->PR L2 3
L2
00 00
```

Redimensioning a List with DIM

DIM is also used with **LIST** to redimension an existing list.

- The elements in the old list that are within the new dimension are not changed.
- Any elements in the old list that are outside the new dimension are eliminated.
- Any additional elements that are created are zeros.

length=DIM listname

```
C1,3,5,75->L4
      C1 3 5 75
3->PR L4L4
      C1 3 5 75
3->PR L4L4
      C1 3 5
```

SEQ

SEQ (sequence, LIST OPS, item 4) requires five arguments: an expression, a variable to be incremented, a beginning value, an ending value, and an increment. SEQ returns a list in which each element is the value of expression evaluated at increments for variable from begin to end.

SEQ(*expression, variable, begin, end, increment*)

The variable need not be defined in memory. The increment can be negative.

```
SEQ(A^2-8, I, 11, 15)  
CL 14 45 1443
```

SEQ can be used to generate a list of index numbers. This kind of list can be useful in data analysis.

```
SEQ(A-8, 1994, 200  
1994 1995 1996
```

LIST MATH Operations

Pressing \square [LIST] \square accesses the list math operations on the LIST MATH menu.

LIST MATH Menu

OPS	MATH	
1: MIN		Returns minimum element of a list.
2: MAX		Returns maximum element of a list.
3: MEAN		Returns mean of a list.
4: MEDIAN		Returns median of a list.
5: SUM		Returns sum of all elements in a list.
6: PROD		Returns product of all elements in a list.

Notes: MIN and MAX are the same as MIN and MAX on the MATH NUM menu.

MIN MAX

MIN (minimum, LIST MATH, item 1) or MAX (maximum, LIST MATH, item 2) returns the smallest or largest element of the specified list. If two lists are compared, it returns a list of the smaller or larger of each pair of elements in the two lists.

MIN(List) MAX(List)
MIN(ListA,ListB) MAX(ListA,ListB)

```

MIN(C1+2,33)
-----
MIN(C1+2,33+C2+
3+33)
-----
C1+2+33

```

MEAN MEDIAN

MEAN (LIST MATH, item 3) returns the mean value of the list. MEDIAN (LIST MATH, item 4) returns the median value of the list.

MEAN(List) or MEDIAN(List)

If a second list is given, it is interpreted as the frequency of the elements in the list.

MEAN(List,frequency) or MEDIAN(List,frequency)

```

MEAN(C1+3,33)
-----
MEAN(C1+2,33+C2+
2+33)
-----
1.571428571

```

```

MEDIAN(C1+2,33)
-----
MEDIAN(C1+2,33+C2+
3+33)
-----
1.5

```

LIST MATH Operations (Continued)

SUM (summation, LIST MATH, item 5) returns the sum of the elements in the specified list.

SUM list

```

[SET 2 33 51 4
SUM L1      91]

```

PROD (product, LIST MATH, item 6) returns the product of the elements of the list.

PROD list

```

[PROD 2 3 33
24]

```

Sum and Products of Numeric Sequences

You can combine SUM or PROD with SEQ to obtain

$\sum_{x=lower}^{upper}$

$\sum_{x=lower}^{upper} expression(x)$

$\prod_{x=lower}^{upper}$

$\prod_{x=lower}^{upper} expression(x)$

To evaluate $\sum 2^{N-1}$ from $N=1$ to 4.

```

[SUM SEQ(2^(N-1),
N,1,4)
15]

```


This chapter describes the tools for analyzing statistical data on the TI-80. These include entering lists of data, calculating statistical results, matching data to a model, and plotting data.

Chapter Contents	Getting Started: Building Height and City Size	9-2
	Setting Up a Statistical Analysis	9-6
	The STAT List Editor	9-9
	Viewing, Erasing, and Editing Lists	9-10
	Sorting and Clearing Lists	9-13
	Statistical Analysis	9-14
	Types of Statistical Analysis	9-15
	Statistical Variables	9-17
	Statistical Plotting	9-18
	Statistical Analysis in a Program	9-22
	Statistical Plotting in a Program	9-23

Getting Started: Building Height and City Size

Getting Started is a fast-paced introduction. Read the chapter for details.

Determine a linear equation to match the data below. Enter the data, and perform a linear regression. Then plot the data. Predict how many buildings of more than 12 stories you would expect to find in a city of 300 thousand people.

Population in Thousands	Buildings > 12 Stories
150	4
500	31
600	42
320	9
150	20
750	66

1. To clear any existing lists, press **[STAT]** 4 to copy **CLUST** to the home screen.



2. Press **[2ND]** **[1]** **[=]** **[2ND]** **[2]** **[=]** **[2ND]** **[3]** **[=]** **[2ND]** **[4]** **[=]** **[2ND]** **[5]** **[=]** **[2ND]** **[6]** **[=]** **[2ND]** **[7]** **[=]** **[2ND]** **[8]** **[=]** **[2ND]** **[9]** **[=]** **[2ND]** **[0]** **[=]** **[2ND]** **[.]** **[=]** **[2ND]** **[/]** **[=]** **[2ND]** **[*]** **[=]** **[2ND]** **[-]** **[=]** **[2ND]** **[+]** **[=]** **[2ND]** **[=]** **[2ND]** **[<]** **[2ND]** **[>]** **[2ND]** **[F1]** **[F2]** **[F3]** **[F4]** **[F5]** **[F6]** **[F7]** **[F8]** **[F9]** **[F10]** **[F11]** **[F12]** **[F13]** **[F14]** **[F15]** **[F16]** **[F17]** **[F18]** **[F19]** **[F20]** **[F21]** **[F22]** **[F23]** **[F24]** **[F25]** **[F26]** **[F27]** **[F28]** **[F29]** **[F30]** **[F31]** **[F32]** **[F33]** **[F34]** **[F35]** **[F36]** **[F37]** **[F38]** **[F39]** **[F40]** **[F41]** **[F42]** **[F43]** **[F44]** **[F45]** **[F46]** **[F47]** **[F48]** **[F49]** **[F50]** **[F51]** **[F52]** **[F53]** **[F54]** **[F55]** **[F56]** **[F57]** **[F58]** **[F59]** **[F60]** **[F61]** **[F62]** **[F63]** **[F64]** **[F65]** **[F66]** **[F67]** **[F68]** **[F69]** **[F70]** **[F71]** **[F72]** **[F73]** **[F74]** **[F75]** **[F76]** **[F77]** **[F78]** **[F79]** **[F80]** **[F81]** **[F82]** **[F83]** **[F84]** **[F85]** **[F86]** **[F87]** **[F88]** **[F89]** **[F90]** **[F91]** **[F92]** **[F93]** **[F94]** **[F95]** **[F96]** **[F97]** **[F98]** **[F99]** **[F100]** **[F101]** **[F102]** **[F103]** **[F104]** **[F105]** **[F106]** **[F107]** **[F108]** **[F109]** **[F110]** **[F111]** **[F112]** **[F113]** **[F114]** **[F115]** **[F116]** **[F117]** **[F118]** **[F119]** **[F120]** **[F121]** **[F122]** **[F123]** **[F124]** **[F125]** **[F126]** **[F127]** **[F128]** **[F129]** **[F130]** **[F131]** **[F132]** **[F133]** **[F134]** **[F135]** **[F136]** **[F137]** **[F138]** **[F139]** **[F140]** **[F141]** **[F142]** **[F143]** **[F144]** **[F145]** **[F146]** **[F147]** **[F148]** **[F149]** **[F150]** **[F151]** **[F152]** **[F153]** **[F154]** **[F155]** **[F156]** **[F157]** **[F158]** **[F159]** **[F160]** **[F161]** **[F162]** **[F163]** **[F164]** **[F165]** **[F166]** **[F167]** **[F168]** **[F169]** **[F170]** **[F171]** **[F172]** **[F173]** **[F174]** **[F175]** **[F176]** **[F177]** **[F178]** **[F179]** **[F180]** **[F181]** **[F182]** **[F183]** **[F184]** **[F185]** **[F186]** **[F187]** **[F188]** **[F189]** **[F190]** **[F191]** **[F192]** **[F193]** **[F194]** **[F195]** **[F196]** **[F197]** **[F198]** **[F199]** **[F200]** **[F201]** **[F202]** **[F203]** **[F204]** **[F205]** **[F206]** **[F207]** **[F208]** **[F209]** **[F210]** **[F211]** **[F212]** **[F213]** **[F214]** **[F215]** **[F216]** **[F217]** **[F218]** **[F219]** **[F220]** **[F221]** **[F222]** **[F223]** **[F224]** **[F225]** **[F226]** **[F227]** **[F228]** **[F229]** **[F230]** **[F231]** **[F232]** **[F233]** **[F234]** **[F235]** **[F236]** **[F237]** **[F238]** **[F239]** **[F240]** **[F241]** **[F242]** **[F243]** **[F244]** **[F245]** **[F246]** **[F247]** **[F248]** **[F249]** **[F250]** **[F251]** **[F252]** **[F253]** **[F254]** **[F255]** **[F256]** **[F257]** **[F258]** **[F259]** **[F260]** **[F261]** **[F262]** **[F263]** **[F264]** **[F265]** **[F266]** **[F267]** **[F268]** **[F269]** **[F270]** **[F271]** **[F272]** **[F273]** **[F274]** **[F275]** **[F276]** **[F277]** **[F278]** **[F279]** **[F280]** **[F281]** **[F282]** **[F283]** **[F284]** **[F285]** **[F286]** **[F287]** **[F288]** **[F289]** **[F290]** **[F291]** **[F292]** **[F293]** **[F294]** **[F295]** **[F296]** **[F297]** **[F298]** **[F299]** **[F300]** **[F301]** **[F302]** **[F303]** **[F304]** **[F305]** **[F306]** **[F307]** **[F308]** **[F309]** **[F310]** **[F311]** **[F312]** **[F313]** **[F314]** **[F315]** **[F316]** **[F317]** **[F318]** **[F319]** **[F320]** **[F321]** **[F322]** **[F323]** **[F324]** **[F325]** **[F326]** **[F327]** **[F328]** **[F329]** **[F330]** **[F331]** **[F332]** **[F333]** **[F334]** **[F335]** **[F336]** **[F337]** **[F338]** **[F339]** **[F340]** **[F341]** **[F342]** **[F343]** **[F344]** **[F345]** **[F346]** **[F347]** **[F348]** **[F349]** **[F350]** **[F351]** **[F352]** **[F353]** **[F354]** **[F355]** **[F356]** **[F357]** **[F358]** **[F359]** **[F360]** **[F361]** **[F362]** **[F363]** **[F364]** **[F365]** **[F366]** **[F367]** **[F368]** **[F369]** **[F370]** **[F371]** **[F372]** **[F373]** **[F374]** **[F375]** **[F376]** **[F377]** **[F378]** **[F379]** **[F380]** **[F381]** **[F382]** **[F383]** **[F384]** **[F385]** **[F386]** **[F387]** **[F388]** **[F389]** **[F390]** **[F391]** **[F392]** **[F393]** **[F394]** **[F395]** **[F396]** **[F397]** **[F398]** **[F399]** **[F400]** **[F401]** **[F402]** **[F403]** **[F404]** **[F405]** **[F406]** **[F407]** **[F408]** **[F409]** **[F410]** **[F411]** **[F412]** **[F413]** **[F414]** **[F415]** **[F416]** **[F417]** **[F418]** **[F419]** **[F420]** **[F421]** **[F422]** **[F423]** **[F424]** **[F425]** **[F426]** **[F427]** **[F428]** **[F429]** **[F430]** **[F431]** **[F432]** **[F433]** **[F434]** **[F435]** **[F436]** **[F437]** **[F438]** **[F439]** **[F440]** **[F441]** **[F442]** **[F443]** **[F444]** **[F445]** **[F446]** **[F447]** **[F448]** **[F449]** **[F450]** **[F451]** **[F452]** **[F453]** **[F454]** **[F455]** **[F456]** **[F457]** **[F458]** **[F459]** **[F460]** **[F461]** **[F462]** **[F463]** **[F464]** **[F465]** **[F466]** **[F467]** **[F468]** **[F469]** **[F470]** **[F471]** **[F472]** **[F473]** **[F474]** **[F475]** **[F476]** **[F477]** **[F478]** **[F479]** **[F480]** **[F481]** **[F482]** **[F483]** **[F484]** **[F485]** **[F486]** **[F487]** **[F488]** **[F489]** **[F490]** **[F491]** **[F492]** **[F493]** **[F494]** **[F495]** **[F496]** **[F497]** **[F498]** **[F499]** **[F500]** **[F501]** **[F502]** **[F503]** **[F504]** **[F505]** **[F506]** **[F507]** **[F508]** **[F509]** **[F510]** **[F511]** **[F512]** **[F513]** **[F514]** **[F515]** **[F516]** **[F517]** **[F518]** **[F519]** **[F520]** **[F521]** **[F522]** **[F523]** **[F524]** **[F525]** **[F526]** **[F527]** **[F528]** **[F529]** **[F530]** **[F531]** **[F532]** **[F533]** **[F534]** **[F535]** **[F536]** **[F537]** **[F538]** **[F539]** **[F540]** **[F541]** **[F542]** **[F543]** **[F544]** **[F545]** **[F546]** **[F547]** **[F548]** **[F549]** **[F550]** **[F551]** **[F552]** **[F553]** **[F554]** **[F555]** **[F556]** **[F557]** **[F558]** **[F559]** **[F560]** **[F561]** **[F562]** **[F563]** **[F564]** **[F565]** **[F566]** **[F567]** **[F568]** **[F569]** **[F570]** **[F571]** **[F572]** **[F573]** **[F574]** **[F575]** **[F576]** **[F577]** **[F578]** **[F579]** **[F580]** **[F581]** **[F582]** **[F583]** **[F584]** **[F585]** **[F586]** **[F587]** **[F588]** **[F589]** **[F590]** **[F591]** **[F592]** **[F593]** **[F594]** **[F595]** **[F596]** **[F597]** **[F598]** **[F599]** **[F600]** **[F601]** **[F602]** **[F603]** **[F604]** **[F605]** **[F606]** **[F607]** **[F608]** **[F609]** **[F610]** **[F611]** **[F612]** **[F613]** **[F614]** **[F615]** **[F616]** **[F617]** **[F618]** **[F619]** **[F620]** **[F621]** **[F622]** **[F623]** **[F624]** **[F625]** **[F626]** **[F627]** **[F628]** **[F629]** **[F630]** **[F631]** **[F632]** **[F633]** **[F634]** **[F635]** **[F636]** **[F637]** **[F638]** **[F639]** **[F640]** **[F641]** **[F642]** **[F643]** **[F644]** **[F645]** **[F646]** **[F647]** **[F648]** **[F649]** **[F650]** **[F651]** **[F652]** **[F653]** **[F654]** **[F655]** **[F656]** **[F657]** **[F658]** **[F659]** **[F660]** **[F661]** **[F662]** **[F663]** **[F664]** **[F665]** **[F666]** **[F667]** **[F668]** **[F669]** **[F670]** **[F671]** **[F672]** **[F673]** **[F674]** **[F675]** **[F676]** **[F677]** **[F678]** **[F679]** **[F680]** **[F681]** **[F682]** **[F683]** **[F684]** **[F685]** **[F686]** **[F687]** **[F688]** **[F689]** **[F690]** **[F691]** **[F692]** **[F693]** **[F694]** **[F695]** **[F696]** **[F697]** **[F698]** **[F699]** **[F700]** **[F701]** **[F702]** **[F703]** **[F704]** **[F705]** **[F706]** **[F707]** **[F708]** **[F709]** **[F710]** **[F711]** **[F712]** **[F713]** **[F714]** **[F715]** **[F716]** **[F717]** **[F718]** **[F719]** **[F720]** **[F721]** **[F722]** **[F723]** **[F724]** **[F725]** **[F726]** **[F727]** **[F728]** **[F729]** **[F730]** **[F731]** **[F732]** **[F733]** **[F734]** **[F735]** **[F736]** **[F737]** **[F738]** **[F739]** **[F740]** **[F741]** **[F742]** **[F743]** **[F744]** **[F745]** **[F746]** **[F747]** **[F748]** **[F749]** **[F750]** **[F751]** **[F752]** **[F753]** **[F754]** **[F755]** **[F756]** **[F757]** **[F758]** **[F759]** **[F760]** **[F761]** **[F762]** **[F763]** **[F764]** **[F765]** **[F766]** **[F767]** **[F768]** **[F769]** **[F770]** **[F771]** **[F772]** **[F773]** **[F774]** **[F775]** **[F776]** **[F777]** **[F778]** **[F779]** **[F780]** **[F781]** **[F782]** **[F783]** **[F784]** **[F785]** **[F786]** **[F787]** **[F788]** **[F789]** **[F790]** **[F791]** **[F792]** **[F793]** **[F794]** **[F795]** **[F796]** **[F797]** **[F798]** **[F799]** **[F800]** **[F801]** **[F802]** **[F803]** **[F804]** **[F805]** **[F806]** **[F807]** **[F808]** **[F809]** **[F810]** **[F811]** **[F812]** **[F813]** **[F814]** **[F815]** **[F816]** **[F817]** **[F818]** **[F819]** **[F820]** **[F821]** **[F822]** **[F823]** **[F824]** **[F825]** **[F826]** **[F827]** **[F828]** **[F829]** **[F830]** **[F831]** **[F832]** **[F833]** **[F834]** **[F835]** **[F836]** **[F837]** **[F838]** **[F839]** **[F840]** **[F841]** **[F842]** **[F843]** **[F844]** **[F845]** **[F846]** **[F847]** **[F848]** **[F849]** **[F850]** **[F851]** **[F852]** **[F853]** **[F854]** **[F855]** **[F856]** **[F857]** **[F858]** **[F859]** **[F860]** **[F861]** **[F862]** **[F863]** **[F864]** **[F865]** **[F866]** **[F867]** **[F868]** **[F869]** **[F870]** **[F871]** **[F872]** **[F873]** **[F874]** **[F875]** **[F876]** **[F877]** **[F878]** **[F879]** **[F880]** **[F881]** **[F882]** **[F883]** **[F884]** **[F885]** **[F886]** **[F887]** **[F888]** **[F889]** **[F890]** **[F891]** **[F892]** **[F893]** **[F894]** **[F895]** **[F896]** **[F897]** **[F898]** **[F899]** **[F900]** **[F901]** **[F902]** **[F903]** **[F904]** **[F905]** **[F906]** **[F907]** **[F908]** **[F909]** **[F910]** **[F911]** **[F912]** **[F913]** **[F914]** **[F915]** **[F916]** **[F917]** **[F918]** **[F919]** **[F920]** **[F921]** **[F922]** **[F923]** **[F924]** **[F925]** **[F926]** **[F927]** **[F928]** **[F929]** **[F930]** **[F931]** **[F932]** **[F933]** **[F934]** **[F935]** **[F936]** **[F937]** **[F938]** **[F939]** **[F940]** **[F941]** **[F942]** **[F943]** **[F944]** **[F945]** **[F946]** **[F947]** **[F948]** **[F949]** **[F950]** **[F951]** **[F952]** **[F953]** **[F954]** **[F955]** **[F956]** **[F957]** **[F958]** **[F959]** **[F960]** **[F961]** **[F962]** **[F963]** **[F964]** **[F965]** **[F966]** **[F967]** **[F968]** **[F969]** **[F970]** **[F971]** **[F972]** **[F973]** **[F974]** **[F975]** **[F976]** **[F977]** **[F978]** **[F979]** **[F980]** **[F981]** **[F982]** **[F983]** **[F984]** **[F985]** **[F986]** **[F987]** **[F988]** **[F989]** **[F990]** **[F991]** **[F992]** **[F993]** **[F994]** **[F995]** **[F996]** **[F997]** **[F998]** **[F999]** **[F1000]** **[F1001]** **[F1002]** **[F1003]** **[F1004]** **[F1005]** **[F1006]** **[F1007]** **[F1008]** **[F1009]** **[F1010]** **[F1011]** **[F1012]** **[F1013]** **[F1014]** **[F1015]** **[F1016]** **[F1017]** **[F1018]** **[F1019]** **[F1020]** **[F1021]** **[F1022]** **[F1023]** **[F1024]** **[F1025]** **[F1026]** **[F1027]** **[F1028]** **[F1029]** **[F1030]** **[F1031]** **[F1032]** **[F1033]** **[F1034]** **[F1035]** **[F1036]** **[F1037]** **[F1038]** **[F1039]** **[F1040]** **[F1041]** **[F1042]** **[F1043]** **[F1044]** **[F1045]** **[F1046]** **[F1047]** **[F1048]** **[F1049]** **[F1050]** **[F1051]** **[F1052]** **[F1053]** **[F1054]** **[F1055]** **[F1056]** **[F1057]** **[F1058]** **[F1059]** **[F1060]** **[F1061]** **[F1062]** **[F1063]** **[F1064]** **[F1065]** **[F1066]** **[F1067]** **[F1068]** **[F1069]** **[F1070]** **[F1071]** **[F1072]** **[F1073]** **[F1074]** **[F1075]** **[F1076]** **[F1077]** **[F1078]** **[F1079]** **[F1080]** **[F1081]** **[F1082]** **[F1083]** **[F1084]** **[F1085]** **[F1086]** **[F1087]** **[F1088]** **[F1089]** **[F1090]** **[F1091]** **[F1092]** **[F1093]** **[F1094]** **[F1095]** **[F1096]** **[F1097]** **[F1098]** **[F1099]** **[F1100]** **[F1101]** **[F1102]** **[F1103]** **[F1104]** **[F1105]** **[F1106]** **[F1107]** **[F1108]** **[F1109]** **[F1110]** **[F1111]** **[F1112]** **[F1113]** **[F1114]** **[F1115]** **[F1116]** **[F1117]** **[F1118]** **[F1119]** **[F1120]** **[F1121]** **[F1122]** **[F1123]** **[F1124]** **[F1125]** **[F1126]** **[F1127]** **[F1128]** **[F1129]** **[F1130]** **[F1131]** **[F1132]** **[F1133]** **[F1134]** **[F1135]** **[F1136]** **[F1137]** **[F1138]** **[F1139]** **[F1140]** **[F1141]** **[F1142]** **[F1143]** **[F1144]**

5. Enter the remaining elements of L1. Press:

500 **[ENTER]**
 800 **[ENTER]**
 250 **[ENTER]**
 550 **[ENTER]**
 750 **[ENTER]**

L1	L2
150	
500	
800	
250	
550	
750	
L1 L2	

6. Press **[←]** to move to the first element of list L2.

L1	L2
150	
500	
800	
250	
550	
750	
L1 L2	

Enter the elements (number of buildings with more than 12 stories) of L2. Press:

4 **[ENTER]**
 31 **[ENTER]**
 42 **[ENTER]**
 9 **[ENTER]**
 20 **[ENTER]**
 55 **[ENTER]**

L1	L2
150	4
500	31
800	42
250	9
550	20
750	55
L1 L2	

7. You can sort the data according to city size. Press **[2ND][QUIT]** **[2ND][F8]** to return to a clear Home screen. Press **[2ND][8]** **[2]** to select **SORTA**, which is copied to the Home screen. Press **[2ND][1]** **[1]** to select the independent list and then press **[1][2ND][1]** **[1]** to select the dependent list. Press **[2ND][ENTER]**. The message **DONE** is displayed. The lists have now been updated in memory.

SORTA(L1,L2)
DONE

8. Press **[2ND][1]** **[1]** to display the sorted lists in the **STAT** list editor.

L1	L2
150	4
250	9
500	31
550	20
750	55
800	42
L1 L2	

Getting Started: Building Height and City Size (Cont.)

After entering and sorting the data, define the STAT PLOTS and Window variables; then perform a linear regression ($ax + b$).

- 10 Press **2ND** **[STAT PLOT]** to display the STAT PLOTS screen.

```
1: PLOT1 OFF L1 L2 =
2: PLOT2 OFF L1 L2 =
3: PLOT3 OFF L1 L2 =
4: PLOT4 OFF L1 L2 =
```

- 11 Press **1** to display the PLOT1 screen. Move the cursor to **ON**, if necessary, and press **ENTER** to turn PLOT1 on. Leave TYPE as scatter plot (•), XL (independent list) as L1, YL (dependent list) as L2, and MARK as \square .

```
PLOT1
ON OFF
TYPE: SC L1 L2
PL: 1 2 L1 L2
YL: 1 2 L1 L2
MARK: □
```

- 12 Press **WINDOW** to display the Window variables. Enter the following values:
8 for XMIN
1000 for XMAX
100 for XSCL
-55 for YMIN
100 for YMAX
10 for YSCL

```
WINDOW
XMIN=8
XMAX=1000
XSCL=100
YMIN=-55
YMAX=100
YSCL=10
```

- 13 Press **STAT** **[1]** to display the STAT CALC menu.

```
EDIT [1] [2]
REG-ON STATC
Y2-ON STATC
3: LINREG(ax+b)
4: LOGREG
5: LINREG(ax+b)
6: LOGREG
7: LOGREG
```

- 14 Press **3** to select **LINREG(ax+b)**, which is copied to the Home screen. Press **(2nd)** **[F1]** **(2nd)** **[F1]** **(2nd)** **[F1]**.

```
LINREG(ax+b)
r=.9254
a=.000708824
b=-8.01801843
r=.9254084565
```

The least-squares linear regression is calculated; the display shows the values for a (slope), b (y-intercept), and r (correlation coefficient).

Store the regression equation in the Y₁ list and graph it.

15. In **FUNC** mode, press $\boxed{\text{Y=}}$ to display the Y₁ editor. Press $\boxed{\text{DEL}}$ to clear Y₁, if necessary. Turn off all other functions, if necessary.

Y1=
Y2=
Y3=
Y4=

16. Press $\boxed{\text{STAT}}$ to display the **VARS** menu.

EQ1
EQ2
EQ3
EQ4
EQ5
EQ6
EQ7
EQ8
EQ9
EQ10
EQ11
EQ12
EQ13
EQ14
EQ15
EQ16
EQ17
EQ18
EQ19
EQ20
EQ21
EQ22
EQ23
EQ24
EQ25
EQ26
EQ27
EQ28
EQ29
EQ30
EQ31
EQ32
EQ33
EQ34
EQ35
EQ36
EQ37
EQ38
EQ39
EQ40
EQ41
EQ42
EQ43
EQ44
EQ45
EQ46
EQ47
EQ48
EQ49
EQ50
EQ51
EQ52
EQ53
EQ54
EQ55
EQ56
EQ57
EQ58
EQ59
EQ60
EQ61
EQ62
EQ63
EQ64
EQ65
EQ66
EQ67
EQ68
EQ69
EQ70
EQ71
EQ72
EQ73
EQ74
EQ75
EQ76
EQ77
EQ78
EQ79
EQ80
EQ81
EQ82
EQ83
EQ84
EQ85
EQ86
EQ87
EQ88
EQ89
EQ90
EQ91
EQ92
EQ93
EQ94
EQ95
EQ96
EQ97
EQ98
EQ99
EQ100

17. Press **2** to select **STATISTICS...** and press $\boxed{\text{ENTER}}$ to display the **VARS** EQ menu.

EQ1
EQ2
EQ3
EQ4
EQ5
EQ6
EQ7
EQ8
EQ9
EQ10
EQ11
EQ12
EQ13
EQ14
EQ15
EQ16
EQ17
EQ18
EQ19
EQ20
EQ21
EQ22
EQ23
EQ24
EQ25
EQ26
EQ27
EQ28
EQ29
EQ30
EQ31
EQ32
EQ33
EQ34
EQ35
EQ36
EQ37
EQ38
EQ39
EQ40
EQ41
EQ42
EQ43
EQ44
EQ45
EQ46
EQ47
EQ48
EQ49
EQ50
EQ51
EQ52
EQ53
EQ54
EQ55
EQ56
EQ57
EQ58
EQ59
EQ60
EQ61
EQ62
EQ63
EQ64
EQ65
EQ66
EQ67
EQ68
EQ69
EQ70
EQ71
EQ72
EQ73
EQ74
EQ75
EQ76
EQ77
EQ78
EQ79
EQ80
EQ81
EQ82
EQ83
EQ84
EQ85
EQ86
EQ87
EQ88
EQ89
EQ90
EQ91
EQ92
EQ93
EQ94
EQ95
EQ96
EQ97
EQ98
EQ99
EQ100

18. Press **5** to select **REGEQ**, which copies the linear regression to the Y₁ editor screen.

Note: Each time you calculate a regression, the regression equation (**REGEQ**) is updated.

EQ1
EQ2
EQ3
EQ4
EQ5
EQ6
EQ7
EQ8
EQ9
EQ10
EQ11
EQ12
EQ13
EQ14
EQ15
EQ16
EQ17
EQ18
EQ19
EQ20
EQ21
EQ22
EQ23
EQ24
EQ25
EQ26
EQ27
EQ28
EQ29
EQ30
EQ31
EQ32
EQ33
EQ34
EQ35
EQ36
EQ37
EQ38
EQ39
EQ40
EQ41
EQ42
EQ43
EQ44
EQ45
EQ46
EQ47
EQ48
EQ49
EQ50
EQ51
EQ52
EQ53
EQ54
EQ55
EQ56
EQ57
EQ58
EQ59
EQ60
EQ61
EQ62
EQ63
EQ64
EQ65
EQ66
EQ67
EQ68
EQ69
EQ70
EQ71
EQ72
EQ73
EQ74
EQ75
EQ76
EQ77
EQ78
EQ79
EQ80
EQ81
EQ82
EQ83
EQ84
EQ85
EQ86
EQ87
EQ88
EQ89
EQ90
EQ91
EQ92
EQ93
EQ94
EQ95
EQ96
EQ97
EQ98
EQ99
EQ100

19. Press $\boxed{\text{GRAPH}}$. The data points are plotted (\bullet), then the regression line is drawn.



20. Press $\boxed{\text{TRACE}}$ and then $\boxed{\text{ENTER}}$ to trace the points in **PLOT1**, as indicated by **P1** in the upper right hand corner of the display.

Press $\boxed{\text{ENTER}}$ to move to Y₁, and continue tracing the function.



Getting Started: Building Height and City Size (Cont.)

You can enter expressions to define lists in the STAT list editor. For example, you can now define predicted values and residuals (the differences between the observed values and the predicted values) for this problem.

21. Press $\boxed{\text{STAT}} \boxed{1}$ to display the STAT list editor. Press $\boxed{\text{F1}} \boxed{\text{F2}} \boxed{\text{F3}}$ to move the cursor onto the name L3.

L2	NAME
1	
2	
3	
4	
5	
6	
7	
8	
9	
10	
11	
12	
13	
14	
15	
16	
17	
18	
19	
20	
21	
22	
23	
24	
25	
26	
27	
28	
29	
30	
31	
32	
33	
34	
35	
36	
37	
38	
39	
40	
41	
42	
43	
44	
45	
46	
47	
48	
49	
50	
51	
52	
53	
54	
55	
56	
57	
58	
59	
60	
61	
62	
63	
64	
65	
66	
67	
68	
69	
70	
71	
72	
73	
74	
75	
76	
77	
78	
79	
80	
81	
82	
83	
84	
85	
86	
87	
88	
89	
90	
91	
92	
93	
94	
95	
96	
97	
98	
99	
100	

22. Press $\boxed{\text{2ND}} \boxed{\text{Y-VARS}} \boxed{1}$ to select Y1, and then press $\boxed{\text{F1}} \boxed{\text{F2}} \boxed{\text{F3}}$. This defines L3 as the values predicted by the **LMREG** line.

L2	NAME
1	
2	
3	
4	
5	
6	
7	
8	
9	
10	
11	
12	
13	
14	
15	
16	
17	
18	
19	
20	
21	
22	
23	
24	
25	
26	
27	
28	
29	
30	
31	
32	
33	
34	
35	
36	
37	
38	
39	
40	
41	
42	
43	
44	
45	
46	
47	
48	
49	
50	
51	
52	
53	
54	
55	
56	
57	
58	
59	
60	
61	
62	
63	
64	
65	
66	
67	
68	
69	
70	
71	
72	
73	
74	
75	
76	
77	
78	
79	
80	
81	
82	
83	
84	
85	
86	
87	
88	
89	
90	
91	
92	
93	
94	
95	
96	
97	
98	
99	
100	

23. Press $\boxed{\text{ENTER}}$ to store the values in L3.

L2	NAME
1	
2	
3	
4	
5	
6	
7	
8	
9	
10	
11	
12	
13	
14	
15	
16	
17	
18	
19	
20	
21	
22	
23	
24	
25	
26	
27	
28	
29	
30	
31	
32	
33	
34	
35	
36	
37	
38	
39	
40	
41	
42	
43	
44	
45	
46	
47	
48	
49	
50	
51	
52	
53	
54	
55	
56	
57	
58	
59	
60	
61	
62	
63	
64	
65	
66	
67	
68	
69	
70	
71	
72	
73	
74	
75	
76	
77	
78	
79	
80	
81	
82	
83	
84	
85	
86	
87	
88	
89	
90	
91	
92	
93	
94	
95	
96	
97	
98	
99	
100	

24. To store the residuals in L4, press $\boxed{\text{F1}} \boxed{\text{F2}}$ to move the cursor onto the name L4. To enter $L4 = L2 - L3$, press $\boxed{\text{2ND}} \boxed{\text{L2}}$ (the observed values) $\boxed{-}$ $\boxed{\text{2ND}} \boxed{\text{L3}}$ (the predicted values) $\boxed{\text{ENTER}}$.

L2	NAME
1	
2	
3	
4	
5	
6	
7	
8	
9	
10	
11	
12	
13	
14	
15	
16	
17	
18	
19	
20	
21	
22	
23	
24	
25	
26	
27	
28	
29	
30	
31	
32	
33	
34	
35	
36	
37	
38	
39	
40	
41	
42	
43	
44	
45	
46	
47	
48	
49	
50	
51	
52	
53	
54	
55	
56	
57	
58	
59	
60	
61	
62	
63	
64	
65	
66	
67	
68	
69	
70	
71	
72	
73	
74	
75	
76	
77	
78	
79	
80	
81	
82	
83	
84	
85	
86	
87	
88	
89	
90	
91	
92	
93	
94	
95	
96	
97	
98	
99	
100	

25. Press $\boxed{\text{2ND}} \boxed{\text{ZOOM}} \boxed{\text{PLOT}} \boxed{1}$ to select **PL0T1**. Move the cursor to **OFF**, and press $\boxed{\text{ENTER}}$ to turn the plot off.

PL0T1
OFF
TYPE
MARK
NAME
Y1
Y2
Y3
Y4
Y5
Y6
Y7
Y8
Y9
Y10
Y11
Y12
Y13
Y14
Y15
Y16
Y17
Y18
Y19
Y20
Y21
Y22
Y23
Y24
Y25
Y26
Y27
Y28
Y29
Y30
Y31
Y32
Y33
Y34
Y35
Y36
Y37
Y38
Y39
Y40
Y41
Y42
Y43
Y44
Y45
Y46
Y47
Y48
Y49
Y50
Y51
Y52
Y53
Y54
Y55
Y56
Y57
Y58
Y59
Y60
Y61
Y62
Y63
Y64
Y65
Y66
Y67
Y68
Y69
Y70
Y71
Y72
Y73
Y74
Y75
Y76
Y77
Y78
Y79
Y80
Y81
Y82
Y83
Y84
Y85
Y86
Y87
Y88
Y89
Y90
Y91
Y92
Y93
Y94
Y95
Y96
Y97
Y98
Y99
Y100

26. Press $\boxed{\text{2ND}} \boxed{\text{ZOOM}} \boxed{\text{PLOT}} \boxed{2}$ to select **PL0T2**. Move the cursor to **ON** and press $\boxed{\text{ENTER}}$ to turn the plot on, if necessary. Press $\boxed{\text{F1}} \boxed{\text{F2}}$ to define **X1** as **L1**. Press $\boxed{\text{F1}} \boxed{\text{F2}}$ to define **Y1** as **L4**. Press $\boxed{\text{F1}} \boxed{\text{F2}}$ to set **MARK** as **+**.

PL0T2
ON
TYPE
MARK
NAME
Y1
Y2
Y3
Y4
Y5
Y6
Y7
Y8
Y9
Y10
Y11
Y12
Y13
Y14
Y15
Y16
Y17
Y18
Y19
Y20
Y21
Y22
Y23
Y24
Y25
Y26
Y27
Y28
Y29
Y30
Y31
Y32
Y33
Y34
Y35
Y36
Y37
Y38
Y39
Y40
Y41
Y42
Y43
Y44
Y45
Y46
Y47
Y48
Y49
Y50
Y51
Y52
Y53
Y54
Y55
Y56
Y57
Y58
Y59
Y60
Y61
Y62
Y63
Y64
Y65
Y66
Y67
Y68
Y69
Y70
Y71
Y72
Y73
Y74
Y75
Y76
Y77
Y78
Y79
Y80
Y81
Y82
Y83
Y84
Y85
Y86
Y87
Y88
Y89
Y90
Y91
Y92
Y93
Y94
Y95
Y96
Y97
Y98
Y99
Y100

Plot the residuals, and predict how many buildings of 12 or more stories there are in a city with a population of 300 thousand.

27. Press $\boxed{2\text{nd}} \boxed{\text{DEL}}$ to turn off Y1.

```
Y1= .0079588355
X48= 18.817407843
34
Y1=
Y1=
Y1=
Y1=
```

28. Press $\boxed{\text{WINDOW}}$, and change the Window variable values to best show the residuals. Use the minimum and maximum values of L4 (10.51452745 and 10.74019339) as guidelines for setting YMIN and YMAX.

```
WINDOW
XMIN=0
XMAX=1000
YMIN=-10
YMAX=10
YCL=2
```

29. Press $\boxed{\text{ZOOM}}$ to plot the residuals. \star marks each residual value.



30. Press $\boxed{\text{2nd}} \boxed{\text{QUIT}} \boxed{\text{EDIT}}$ to return to a clear home screen. Press $\boxed{\text{2nd}} \boxed{\text{Y-VARS}}$ 1 to select Y1. Then press $\boxed{\text{2nd}} \boxed{\text{DEL}}$.

```
Y1(344)
12.87115486
```

The value of Y1 (the linear regression equation) for $X=300$ (which represents 300 thousand city population) is shown. Remember to round off the number mentally to an integer (13) to represent whole buildings.

Setting Up a Statistical Analysis

The data for statistical analyses is stored in lists. The TI-80 has six list variables (L1 to L6) that you can use in STAT calculations. Several types of statistical analysis are available.

- Steps:** Follow these basic steps to perform statistical analyses.
1. Enter the statistical data in lists (pages 9-9 to 9-11)
 2. Select the type of statistical calculations you want to do (pages 9-14 to 9-16), and specify the list names for the data.
 3. Calculate the statistical variables, or match the data to a model (page 9-17)
 4. Plot the data (pages 9-18 to 9-21)

Pressing **[STAT]** accesses the **STAT** list editor and several instructions for use with lists (L1 to L6). The instructions are discussed on page 9-13.

STAT EDIT

Menu

EDIT: CALL

- | | |
|-------------|--------------------------------|
| 1: EDIT... | Displays list editor |
| 2: SORTA | Sorts list in ascending order |
| 3: SORTD | Sorts list in descending order |
| 4: CLR LIST | Delete all elements of list. |

Displaying the STAT List Editor

The **STAT** list editor gives you an easy environment in which to enter or edit lists. You can also create lists directly from the keyboard (Chapter 8), if you prefer.

To display the **STAT** list editor, press **[STAT]** and then press 1 or **[F1]** to select **EDIT...** from the **STAT EDIT** menu.

L1	L2
0.0	0
1.0	1
2.0	2
3.0	3
4.0	4
5.0	5
6.0	6
7.0	7
8.0	8
9.0	9
10.0	10
11.0	11
12.0	12
13.0	13
14.0	14
15.0	15
16.0	16
17.0	17
18.0	18
19.0	19
20.0	20
21.0	21
22.0	22
23.0	23
24.0	24
25.0	25
26.0	26
27.0	27
28.0	28
29.0	29
30.0	30
31.0	31
32.0	32
33.0	33
34.0	34
35.0	35
36.0	36
37.0	37
38.0	38
39.0	39
40.0	40
41.0	41
42.0	42
43.0	43
44.0	44
45.0	45
46.0	46
47.0	47
48.0	48
49.0	49
50.0	50
51.0	51
52.0	52
53.0	53
54.0	54
55.0	55
56.0	56
57.0	57
58.0	58
59.0	59
60.0	60
61.0	61
62.0	62
63.0	63
64.0	64
65.0	65
66.0	66
67.0	67
68.0	68
69.0	69
70.0	70
71.0	71
72.0	72
73.0	73
74.0	74
75.0	75
76.0	76
77.0	77
78.0	78
79.0	79
80.0	80
81.0	81
82.0	82
83.0	83
84.0	84
85.0	85
86.0	86
87.0	87
88.0	88
89.0	89
90.0	90
91.0	91
92.0	92
93.0	93
94.0	94
95.0	95
96.0	96
97.0	97
98.0	98
99.0	99
100.0	100
101.0	101
102.0	102
103.0	103
104.0	104
105.0	105
106.0	106
107.0	107
108.0	108
109.0	109
110.0	110
111.0	111
112.0	112
113.0	113
114.0	114
115.0	115
116.0	116
117.0	117
118.0	118
119.0	119
120.0	120
121.0	121
122.0	122
123.0	123
124.0	124
125.0	125
126.0	126
127.0	127
128.0	128
129.0	129
130.0	130
131.0	131
132.0	132
133.0	133
134.0	134
135.0	135
136.0	136
137.0	137
138.0	138
139.0	139
140.0	140
141.0	141
142.0	142
143.0	143
144.0	144
145.0	145
146.0	146
147.0	147
148.0	148
149.0	149
150.0	150
151.0	151
152.0	152
153.0	153
154.0	154
155.0	155
156.0	156
157.0	157
158.0	158
159.0	159
160.0	160
161.0	161
162.0	162
163.0	163
164.0	164
165.0	165
166.0	166
167.0	167
168.0	168
169.0	169
170.0	170
171.0	171
172.0	172
173.0	173
174.0	174
175.0	175
176.0	176
177.0	177
178.0	178
179.0	179
180.0	180
181.0	181
182.0	182
183.0	183
184.0	184
185.0	185
186.0	186
187.0	187
188.0	188
189.0	189
190.0	190
191.0	191
192.0	192
193.0	193
194.0	194
195.0	195
196.0	196
197.0	197
198.0	198
199.0	199
200.0	200
201.0	201
202.0	202
203.0	203
204.0	204
205.0	205
206.0	206
207.0	207
208.0	208
209.0	209
210.0	210
211.0	211
212.0	212
213.0	213
214.0	214
215.0	215
216.0	216
217.0	217
218.0	218
219.0	219
220.0	220
221.0	221
222.0	222
223.0	223
224.0	224
225.0	225
226.0	226
227.0	227
228.0	228
229.0	229
230.0	230
231.0	231
232.0	232
233.0	233
234.0	234
235.0	235
236.0	236
237.0	237
238.0	238
239.0	239
240.0	240
241.0	241
242.0	242
243.0	243
244.0	244
245.0	245
246.0	246
247.0	247
248.0	248
249.0	249
250.0	250
251.0	251
252.0	252
253.0	253
254.0	254
255.0	255
256.0	256
257.0	257
258.0	258
259.0	259
260.0	260
261.0	261
262.0	262
263.0	263
264.0	264
265.0	265
266.0	266
267.0	267
268.0	268
269.0	269
270.0	270
271.0	271
272.0	272
273.0	273
274.0	274
275.0	275
276.0	276
277.0	277
278.0	278
279.0	279
280.0	280
281.0	281
282.0	282
283.0	283
284.0	284
285.0	285
286.0	286
287.0	287
288.0	288
289.0	289
290.0	290
291.0	291
292.0	292
293.0	293
294.0	294
295.0	295
296.0	296
297.0	297
298.0	298
299.0	299
300.0	300
301.0	301
302.0	302
303.0	303
304.0	304
305.0	305
306.0	306
307.0	307
308.0	308
309.0	309
310.0	310
311.0	311
312.0	312
313.0	313
314.0	314
315.0	315
316.0	316
317.0	317
318.0	318
319.0	319
320.0	320
321.0	321
322.0	322
323.0	323
324.0	324
325.0	325
326.0	326
327.0	327
328.0	328
329.0	329
330.0	330
331.0	331
332.0	332
333.0	333
334.0	334
335.0	335
336.0	336
337.0	337
338.0	338
339.0	339
340.0	340
341.0	341
342.0	342
343.0	343
344.0	344
345.0	345
346.0	346
347.0	347
348.0	348
349.0	349
350.0	350
351.0	351
352.0	352
353.0	353
354.0	354
355.0	355
356.0	356
357.0	357
358.0	358
359.0	359
360.0	360
361.0	361
362.0	362
363.0	363
364.0	364
365.0	365
366.0	366
367.0	367
368.0	368
369.0	369
370.0	370
371.0	371
372.0	372
373.0	373
374.0	374
375.0	375
376.0	376
377.0	377
378.0	378
379.0	379
380.0	380
381.0	381
382.0	382
383.0	383
384.0	384
385.0	385
386.0	386
387.0	387
388.0	388
389.0	389
390.0	390
391.0	391
392.0	392
393.0	393
394.0	394
395.0	395
396.0	396
397.0	397
398.0	398
399.0	399
400.0	400
401.0	401
402.0	402
403.0	403
404.0	404
405.0	405
406.0	406
407.0	407
408.0	408
409.0	409
410.0	410
411.0	411
412.0	412
413.0	413
414.0	414
415.0	415
416.0	416
417.0	417
418.0	418
419.0	419
420.0	420
421.0	421
422.0	422
423.0	423
424.0	424
425.0	425
426.0	426
427.0	427
428.0	428
429.0	429
430.0	430
431.0	431
432.0	432
433.0	433
434.0	434
435.0	435
436.0	436
437.0	437
438.0	438
439.0	439
440.0	440
441.0	441
442.0	442
443.0	443
444.0	444
445.0	445
446.0	446
447.0	447
448.0	448
449.0	449
450.0	450
451.0	451
452.0	452
453.0	453
454.0	454
455.0	455
456.0	456
457.0	457
458.0	458
459.0	459
460.0	460
461.0	461
462.0	462
463.0	463
464.0	464
465.0	465
466.0	466
467.0	467
468.0	468
469.0	469
470.0	470
471.0	471
472.0	472
473.0	473
474.0	474
475.0	475
476.0	476
477.0	477
478.0	478
479.0	479
480.0	480
481.0	481
482.0	482
483.0	483
484.0	484
485.0	485
486.0	486
487.0	487
488.0	488
489.0	489
490.0	490
491.0	491
492.0	492
493.0	493
494.0	494
495.0	495
496.0	496

Viewing, Entering, and Editing Lists

The STAT list editor has two “contexts,” viewing and editing. The current context determines the result of a key press. In both contexts, the full value of the highlighted element is displayed on the bottom line.

Viewing Context



1	2
1	1
2	2
3	3
4	4
5	5
6	6
7	7
8	8
9	9
10	10

In the viewing context, you can move quickly from one list element to the next.

[←] or [→]	Moves the rectangular cursor to the previous or next list.
[↑] or [↓]	Moves the rectangular cursor within the current column. On row 1, [↑] moves the cursor to the list name.
ENTER	Activates the edit cursor on the bottom line.
CE	Clears the value on the bottom line.
Any entry character	Clears the value on the bottom line, copies the character to the bottom line.
[0] [DEL]	Inserts a list element (value is zero).
[DEL]	Deletes the current list element and closes the list.

Editing Context



1	2
1	1
2	2
3	3
4	4
5	5
6	6
7	7
8	8
9	9
10	10

In the editing context, an edit cursor is active on the bottom line and you can change the value of the current list element. You can also move the cursor onto the list name and edit the entire list at once.

[←] or [→]	Moves the edit cursor within the value.
[↑] or [↓]	Moves the value on the bottom line to the list element, moves the rectangular cursor within the column. On row 1, [↓] moves the cursor to the list name.
[ENTER]	Moves the value on the bottom line to the list element, moves the rectangular cursor to the next element.
CE	Clears the value on the bottom line.
Any entry character	Copies the character to the edit-cursor location on the bottom line. If it is the first character typed, the value on the bottom line is cleared.
[0] [DEL]	Activates the insert cursor.
[DEL]	Deletes a character.

Deleting a List

You can delete the contents of a list in several ways:

- With the **CLEARLIST** instruction (page 9-13)
- Through the **MEMORY** menu (Chapter 12)
- In the **STAT** list editor, by pressing $\boxed{\text{DEL}}$ to move onto the list name and then pressing $\boxed{\text{DEL}}$ $\boxed{\text{DEL}}$
- In the **STAT** list editor, by deleting each element
- On a command line, by entering **0=000** *listname*

Editing a List Element

To edit a list element:

1. Display the **STAT** list editor.
2. Move the rectangular cursor to the element you want to change.
3. Press $\boxed{\text{EDIT}}$ to switch to the editing context. Then:
 - Change the current value by inserting, deleting, or typing over digits.
 - Press an entry key, such as a number or letter, to begin an entry. This automatically clears the value.
 - Press $\boxed{\text{DEL}}$ to clear the entire value and then enter a new value.

Note: If you clear a value by mistake, you can immediately press $\boxed{\text{EDIT}}$ to restore the value at the rectangular cursor.
4. Press $\boxed{\text{EDIT}}$ to store the new value, and move to another element.

Notes: You may enter an expression, which is evaluated when you press $\boxed{\text{EDIT}}$, $\boxed{\text{DEL}}$, or $\boxed{\text{END}}$.

Viewing, Entering, and Editing Lists (Continued)

You can enter or edit an entire list by moving the cursor to a list name on the top line of the STAT list editor and then pressing **[ENTER]**. The bottom line displays $L_n=L_n+1$, if there is already data in the list. Type any expression that returns a list, and press **[ENTER]**. The new list is displayed.

Entering an Entire List

To enter an entire list:

1. Press **[STAT]** **[ENTER]**. Enter several elements in L1.
2. Press **[Δ]** and **[P]** as many times as necessary to move the cursor to the list name L2.

L1	L2
4	
6	
8	
10	
12	
L1 L2	

L1	L2
4	
6	
8	
10	
12	
L1 L2	

3. Press **[\square]** **[1]** **[\square]** **[2]**. This is the expression that will define the elements in L2.
4. Press **[ENTER]** to define and display L2.

L1	L2
4	
6	
8	
10	
12	
L1 L2	

L1	L2
4	4
6	6
8	8
10	10
12	12
L1 L2	

Editing an Entire List

To replace an existing list:

1. Move the cursor to the list name L2. $L2=L2+1$ is displayed.
2. Enter a new expression to replace the existing values in L2, **[\square]** **[1]** **[\square]** **[3]**, for example. Then press **[ENTER]**. The values in L2 are replaced, and the new values are displayed.

L1	L2
4	4
6	6
8	8
10	10
12	12
L1 L2	

L1	L2
4	4
6	6
8	8
10	10
12	12
L1 L2	

Sorting and Clearing Lists

Items 2 to 4 on the STAT EDIT menu—SORTA, SORTD, and CLRLIST—let you sort or clear list data. Pressing $\boxed{\text{STAT}} \boxed{\text{EDIT}}$ displays these instructions, and selecting an item copies the name of the instruction to the Home screen. Note that SORTA and SORTD are the same as SORTA and SORTD on the LIST OPS menu (Chapter 8).

SORTA
SORTD

SORTA (sort ascending, STAT EDIT, item 2) and **SORTD** (sort descending, STAT EDIT, item 3) have two uses.

- With one list name, they sort the elements of an existing list and update the list in memory.
- With two to six list names, they sort the first list and then sort the remaining lists as dependent lists, placing their elements in the same order as their corresponding elements in the first list. This lets you sort two-variable data on X and keep the data pairs together.

All of the lists to be sorted must be the same length. The sorted lists are updated in the memory.

Note: You can only reference a specific list once in these instructions.

```
SORTA(listname)  
SORTA(listname,dependlistA,dependlistB, )  
SORTD(listname)  
SORTD(listname,dependlistA,dependlistB, )
```

Year	Value
1992	1.478
1993	1.481
1994	1.484
1995	1.487
1996	1.491
1997	1.494
1998	1.497
1999	1.501
2000	1.504
2001	1.507
2002	1.511
2003	1.514
2004	1.517
2005	1.521
2006	1.524
2007	1.527
2008	1.531
2009	1.534
2010	1.537
2011	1.541
2012	1.544
2013	1.547
2014	1.551
2015	1.554
2016	1.557
2017	1.561
2018	1.564
2019	1.567
2020	1.571
2021	1.574
2022	1.577
2023	1.581
2024	1.584
2025	1.587
2026	1.591
2027	1.594
2028	1.597
2029	1.601
2030	1.604
2031	1.607
2032	1.611
2033	1.614
2034	1.617
2035	1.621
2036	1.624
2037	1.627
2038	1.631
2039	1.634
2040	1.637
2041	1.641
2042	1.644
2043	1.647
2044	1.651
2045	1.654
2046	1.657
2047	1.661
2048	1.664
2049	1.667
2050	1.671
2051	1.674
2052	1.677
2053	1.681
2054	1.684
2055	1.687
2056	1.691
2057	1.694
2058	1.697
2059	1.701
2060	1.704
2061	1.707
2062	1.711
2063	1.714
2064	1.717
2065	1.721
2066	1.724
2067	1.727
2068	1.731
2069	1.734
2070	1.737
2071	1.741
2072	1.744
2073	1.747
2074	1.751
2075	1.754
2076	1.757
2077	1.761
2078	1.764
2079	1.767
2080	1.771
2081	1.774
2082	1.777
2083	1.781
2084	1.784
2085	1.787
2086	1.791
2087	1.794
2088	1.797
2089	1.801
2090	1.804
2091	1.807
2092	1.811
2093	1.814
2094	1.817
2095	1.821
2096	1.824
2097	1.827
2098	1.831
2099	1.834
2100	1.837
2101	1.841
2102	1.844
2103	1.847
2104	1.851
2105	1.854
2106	1.857
2107	1.861
2108	1.864
2109	1.867
2110	1.871
2111	1.874
2112	1.877
2113	1.881
2114	1.884
2115	1.887
2116	1.891
2117	1.894
2118	1.897
2119	1.901
2120	1.904
2121	1.907
2122	1.911
2123	1.914
2124	1.917
2125	1.921
2126	1.924
2127	1.927
2128	1.931
2129	1.934
2130	1.937
2131	1.941
2132	1.944
2133	1.947
2134	1.951
2135	1.954
2136	1.957
2137	1.961
2138	1.964
2139	1.967
2140	1.971
2141	1.974
2142	1.977
2143	1.981
2144	1.984
2145	1.987
2146	1.991
2147	1.994
2148	1.997
2149	2.001
2150	2.004
2151	2.007
2152	2.011
2153	2.014
2154	2.017
2155	2.021
2156	2.024
2157	2.027
2158	2.031
2159	2.034
2160	2.037
2161	2.041
2162	2.044
2163	2.047
2164	2.051
2165	2.054
2166	2.057
2167	2.061
2168	2.064
2169	2.067
2170	2.071
2171	2.074
2172	2.077
2173	2.081
2174	2.084
2175	2.087
2176	2.091
2177	2.094
2178	2.097
2179	2.101
2180	2.104
2181	2.107
2182	2.111
2183	2.114
2184	2.117
2185	2.121
2186	2.124
2187	2.127
2188	2.131
2189	2.134
2190	2.137
2191	2.141
2192	2.144
2193	2.147
2194	2.151
2195	2.154
2196	2.157
2197	2.161
2198	2.164
2199	2.167
2200	2.171
2201	2.174
2202	2.177
2203	2.181
2204	2.184
2205	2.187
2206	2.191
2207	2.194
2208	2.197
2209	2.201
2210	2.204
2211	2.207
2212	2.211
2213	2.214
2214	2.217
2215	2.221
2216	2.224
2217	2.227
2218	2.231
2219	2.234
2220	2.237
2221	2.241
2222	2.244
2223	2.247
2224	2.251
2225	2.254
2226	2.257
2227	2.261
2228	2.264
2229	2.267
2230	2.271
2231	2.274
2232	2.277
2233	2.281
2234	2.284
2235	2.287
2236	2.291
2237	2.294
2238	2.297
2239	2.301
2240	2.304
2241	2.307
2242	2.311
2243	2.314
2244	2.317
2245	2.321
2246	2.324
2247	2.327
2248	2.331
2249	2.334
2250	2.337
2251	2.341
2252	2.344
2253	2.347
2254	2.351
2255	2.354
2256	2.357
2257	2.361
2258	2.364
2259	2.367
2260	2.371
2261	2.374
2262	2.377
2263	2.381
2264	2.384
2265	2.387
2266	2.391
2267	2.394
2268	2.397
2269	2.401
2270	2.404
2271	2.407
2272	2.411
2273	2.414
2274	2.417
2275	2.421
2276	2.424
2277	2.427
2278	2.431
2279	2.434
2280	2.437
2281	2.441
2282	2.444
2283	2.447
2284	2.451
2285	2.454
2286	2.457
2287	2.461
2288	2.464
2289	2.467
2290	2.471
2291	2.474
2292	2.477
2293	2.481
2294	2.484
2295	2.487
2296	2.491
2297	2.494
2298	2.497
2299	2.501
2300	2.504
2301	2.507
2302	2.511
2303	2.514
2304	2.517
2305	2.521
2306	2.524
2307	2.527
2308	2.531
2309	2.534
2310	2.537
2311	2.541
2312	2.544
2313	2.547
2314	2.551
2315	2.554
2316	2.557
2317	2.561
2318	2.564
2319	2.567
2320	2.571
2321	2.574
2322	2.577
2323	2.581
2324	2.584
2325	2.587
2326	2.591
2327	2.594
2328	2.597
2329	2.601
2330	2.604
2331	2.607
2332	2.611
2333	2.614
2334	2.617
2335	2.621
2336	2.624
2337	2.627
2338	2.631
2339	2.634
2340	2.637
2341	2.641
2342	2.644
2343	2.647
2344	2.651
2345	2.654
2346	2.657
2347	2.661
2348	2.664
2349	2.667
2350	2.671
2351	2.674
2352	2.677
2353	2.681
2354	2.684
2355	2.687
2356	2.691
2357	2.694
2358	2.697
2359	2.701
2360	2.704
2361	2.707
2362	2.711
2363	2.714
2364	2.717
2365	2.721
2366	2.724
2367	2.727
2368	2.731
2369	2.734
2370	2.737
2371	2.741
2372	2.744
2373	2.747
2374	2.751
2375	2.754
2376	2.757
2377	2.761
2378	2.764
2379	2.767
2380	2.771
2381	2.774
2382	2.777
2383	2.781
2384	2.784
2385	2.787
2386	2.791
2387	2.794
2388	2.797
2389	2.801
2390	2.804
2391	2.807
2392	2.811
2393	2.814
2394	2.817
2395	2.821
2396	2.824
2397	2.827
2398	2.831
2399	2.834
2400	2.837
2401	2.841
2402	2.844
2403	2.847
2404	2.851
2405	2.854
2406	2.857
2407	2.861
2408	2.864
2409	2.867
2410	2.871
2411	2.874
2412	2.877
2413	2.881
2414	2.884
2415	2.887
2416	2.891
2417	2.894
2418	2.897
2419	2.901
2420	2.904
2421	2.907
2422	2.911
2423	2.914
2424	2.917
2425	2.921
2426	2.924
2427	2.927
2428	2.931
2429	2.934
2430	2.937
2431	2.941
2432	2.944
2433	2.947
2434	2.951
2435	2.954
2436	2.957
2437	2.961
2438	2.964
2439	2.967
2440	2.971
2441	2.974
2442	2.977
2443	2.981
2444	2.984
2445	2.987
2446	2.991
2447	2.994
2448	2.997
2449	3.001
2450	3.004
2451	3.007
2452	3.011
2453	3.014
2454	3.017
2455	3.021
2456	3.024
2457	3.027
2458	3.031
2459	3.034
2460	3.037
2461	3.041
2462	3.044
2463	3.047
2464	3.051
2465	3.054
2466	3.057
2467	3.061
2468	3.064
2469	3.067
2470	3.071
2471	3.074
2472	3.077
2473	3.081
2474	3.084
2475	3.087
2476	3.091
2477	3.094
2478	3.097
2479	3.101
2480	3.104
2481	3.107
2482	3.111
2483	3.114
2484	3.117
2485	3.121
2486	3.124
2487	3.127
2488	3.131
2489	3.134
2490	3.137
2491	3.141
2492	3.144
2493	3.147
2494	3.151
2495	3.154
2496	3.157
2497	3.161
2498	3.164
2499	3.167
2500	3.171
2501	3.174
2502	3.177

Statistical Analysis

Pressing **STAT** **[1]** accesses the **STAT CALC** menu, where you select and perform statistical calculations. The **Ti-80** can analyse one-variable or two-variable statistics. Both can have associated frequency lists.

STAT CALC Menu

EDIT	NAME	
1	1-VAR STATS	Calculates 1-variable statistics.
2	2-VAR STATS	Calculates 2-variable statistics.
3	LINE(GX+Y)	Matches data to linear model.
4	QUADREG	Matches data to quadratic model.
5	LINE(GX+GX)	Matches data to linear model.
6	LNREG	Matches data to logarithmic model.
7	EXPREG	Matches data to exponential model.
8	POWERG	Matches data to power model.

Selecting and Performing a Statistical Calculation

To select and perform statistical calculations:

1. Select a calculation type by pressing its corresponding number on the **STAT CALC** menu. The name of the calculation is copied to the Home screen.
2. Enter the name(s) of the list(s) to be used in the calculation. If you enter more than one list name, separate them with commas.
3. Press **ENTER** to perform the calculation and display the results.

Frequency of Occurrence for Data Points

For all of the calculation types, you can include a list of data occurrences, or frequencies. These indicate how many times the corresponding data points or data pairs occur in the data set you are analysing.

For example, if **L1={15.5,12.1,9.8,14.7,18}** and **L2={1,4,1,3,2}**, then the instruction **1-VAR STATS L1,L2** would assume that 15.5 occurred one time, 12.1 occurred four times, 9.8 occurred one time, and so on.

Frequencies must be greater than or equal to zero. At least one frequency in the list must be greater than zero.

Noninteger frequencies are valid. This is useful in entering frequencies expressed as percentages or parts that add up to 1. Noninteger frequencies, however, may prevent the calculation of certain variables.

Types of Statistical Analysis

These calculations return statistical results based on the list(s) you reference. If you reference a third list name as an argument for 2-VAR STATS or any of the regression models, the list is interpreted as the frequencies of occurrence for the data pairs in the first two lists.

1-VAR STATS

1-VAR STATS (one-variable statistics, STAT CALC, item 1) analyzes data with one measured variable and calculates statistical results as indicated on page 9-17.

If you reference two list names, the second list is interpreted as the frequency of occurrence for each data point in the first list.

1-VAR STATS *ListName*

1-VAR STATS *ListName*, *FreqListName*

```
1-VAR STATS [L1]
[2]
```

2-VAR STATS

2-VAR STATS (two-variable statistics, STAT CALC, item 2) analyzes pairs of data between which there is a relationship. This option calculates statistical results as indicated on page 9-17.

The first list you reference is the independent variable (X list). The second list is the dependent variable (Y list). If you reference a third list name, it is interpreted as the frequency of occurrence for each data pair in the first two lists.

2-VAR STATS *ListName*, *YListName*

2-VAR STATS *ListName*, *YListName*, *FreqListName*

LNREG (aX+b)

LNREG (aX+b) (linear regression, STAT CALC, item 3) matches the data to the model $y=aX+b$ using a least-squares match, and x and y . It displays a (slope), b (y intercept), and r (correlation coefficient).

LNREG (aX+b) *ListName*, *YListName*

LNREG (aX+b) *ListName*, *YListName*, *FreqListName*

```
LNREG (aX+b) [L1]
[2]
```

```
LNREG (aX+b)
a=.0000000000000000
b=.0000000000000000
r=.0000000000000000
```

Types of Statistical Analysis (Continued)

QUADREG **QUADREG** (quadratic regression, STAT CALC, item 4) matches the data to the second-order polynomial $y = ax^2 + bx + c$. It displays **a**, **b**, and **c**. For three data points the equation is a polynomial match; for four or more, it is a polynomial regression. At least three data points are required.

QUADREG *Xlistname*, *Ylistname*

QUADREG *Xlistname*, *Ylistname*, *freqlistname*

LNREG **LNREG** (**a+bx**) (linear regression, STAT CALC, item 5) matches the data to the model equation $y = a + bx$ using a least-squares match and **x** and **y**. It displays **a**, **b**, and **r** (correlation coefficient).

LNREG (**a+bx**) *Xlistname*, *Ylistname*

LNREG (**a+bx**) *Xlistname*, *Ylistname*, *freqlistname*

LNREG **LNREG** (logarithmic regression, STAT CALC, item 6) matches the data to the model equation $y = a + b \ln(x)$ using a least-squares match and transformed values **LN(x)** and **y**. It displays **a**, **b**, and **r** (correlation coefficient).

LNREG *Xlistname*, *Ylistname*

LNREG *Xlistname*, *Ylistname*, *freqlistname*

EXPREG **EXPREG** (exponential regression, STAT CALC, item 7) matches the data to the model equation $y = ab^x$ using a least-squares match and transformed values **x** and **LN(y)**. It displays **a**, **b**, and **r** (correlation coefficient).

EXPREG *Xlistname*, *Ylistname*

EXPREG *Xlistname*, *Ylistname*, *freqlistname*

PWRREG **PWRREG** (power regression, STAT CALC, item 8) matches the data to the model equation $y = ax^b$ using a least-squares match and transformed values **LN(x)** and **LN(y)**. It displays **a**, **b**, and **r** (correlation coefficient).

PWRREG *Xlistname*, *Ylistname*

PWRREG *Xlistname*, *Ylistname*, *freqlistname*

Note: Calculations for **L**, **LX**, **LX²**, **SX**, **aX**, **y**, **LY**, **LY²**, **SY**, **aY**, and **LXY** are calculated using transformed values for **LNREG**, **EXPREG**, and **PWRREG**.

Statistical Variables

The statistical variables are calculated as indicated below. Some are displayed when 1-VAR STATS or 2-VAR STATS are calculated. You can access these variables for use in expressions through the **VAR(S) STATISTICS...** menu. If you edit a list, all statistical variables are cleared.

Variables	1-VAR STATS	2-VAR STATS	LIF LIL		VARS Menu
			REQS	QUADREQ	
\bar{X} (mean of X values)	✓	✓	✓		X/Y
ΣX (sum of X values)	✓	✓	✓		Σ
ΣX^2 (sum of X^2 values)	✓	✓	✓		Σ
SX (sample standard deviation of X)	✓	✓	✓		X/Y
σX (population standard deviation of X)	✓	✓	✓		X/Y
N (number of data points)	✓	✓	✓	✓	X/Y
\bar{Y} (mean of Y values)		✓	✓		X/Y
ΣY (sum of Y values)		✓	✓		Σ
ΣY^2 (sum of Y^2 values)		✓	✓		Σ
SY (sample standard deviation of Y)		✓	✓		X/Y
σY (population standard deviation of Y)		✓	✓		X/Y
ΣXY (sum of $X \cdot Y$)		✓	✓		Σ
$MINX$ (minimum of X values)	✓	✓			X/Y
$MAXX$ (maximum of X values)	✓	✓			X/Y
$MINY$ (minimum of Y values)		✓			X/Y
$MAXY$ (maximum of Y values)		✓			X/Y
$Q1$ (1st quartile)	✓				BOX
MED (median)	✓				BOX
$Q3$ (3rd quartile)	✓				BOX
a, b (regression/slopes coefficients)			✓		EQ
a, b, c (quadratic coefficients)				✓	EQ
r (correlation coefficient)		✓	✓		EQ
$REGEQ$ (regression equation)			✓	✓	EQ

Noninteger Frequencies

The quartile $Q1$ is the median of the ordinates to the left of MED (median). The quartile $Q3$ is the median of the ordinates to the right of MED .

Large Frequencies

If a frequency list contains noninteger values, SX and SY are undefined. No values are displayed for them in the statistical results. $Q1$, MED , and $Q3$ are also undefined if the frequency list contains noninteger values.

Zero Frequencies

If a frequency list contains a value larger than 99, $Q1$, MED , and $Q3$ will not be calculated.

If the frequency for an element or data pair is zero, the element or data pair is ignored in the calculation.

Statistical Plotting

You can plot statistical data that you have entered in lists. The types of plot available include scatter plots, x-y lines, box and whisker plots, and histograms. You can define up to three plots at a time.

Steps

To plot statistical data:

1. Enter the statistical data as lists (page 9-9 and Chapter 8).
2. Select the statistical calculations (pages 9-14 to 9-16), and calculate the statistical variables (page 9-1) or match the data to a model, if desired.
3. Select or deselect Y= equations, as appropriate (Chapter 4).
4. Define the statistical plot (page 9-20).
5. Turn the plot(s) on, if necessary (page 9-21).
6. Define the viewing window (page 9-24 and Chapter 4).
7. Display and explore the graph by pressing **GRAPH**, **TABLE**, or **TRACE**.

Scatter Plot

Scatter Plot (scatter plot) plots the data points from **XL** (X list) and **YL** (Y list) as coordinate pairs, showing each point as a box (\square), cross (+), or dot (\cdot). **XL** and **YL** must be the same length. They can be the same list.



XYLine

XYLine (XYline) is a scatter plot in which the data points are plotted and connected in the order in which they appear in **XL** and **YL**. You may want to sort the lists with **SORTA** or **SORTC** before plotting.



Box Plot

▢

▢ (box plot) plots one-variable data. The whiskers on the plot extend from the minimum data point in the set (**MIN**) to the first quartile (**Q1**) and from the third quartile (**Q3**) to the maximum point (**MAX**). The box is defined by **Q1**, the median (**MED**), and **Q3** (page 9-17).

Box plots are plotted with respect to **XMIN** and **XMAX**, but ignore **YMIN** and **YMAX**. When two box plots are plotted, the first plots at the top of the screen and the second plots in the middle. When three are plotted, the first plots at the top, the second in the middle, and the third at the bottom.



Histogram

▢

▢ (histogram) plots one-variable data. **XSC1** determines the width of each bar, beginning at **XMIN** (**XMAX - XMIN**). **XSC1** must be ≤ 30 . A value occurring on the edge of a bar is counted in the bar to the right.



Frequencies in Stat Plots

The frequency list specified for a statistical plot works just like the frequency lists specified for other statistical calculations (pages 9-14 to 9-15).

If you want to exclude an outlying data point from a plot, enter a zero for that value in the frequency list to prevent having to change the data lists.

Defining the Plots

To define plots:

1. Press **2ND** **[STAT PLOTS]**. The **STAT PLOTS** screen shows the current plot definitions.



2. Select the plot to define (**PLOT1**, **PLOT2**, or **PLOT3**).
3. If you wish to immediately plot the statistical data, select **ON**. You can define a plot at any time and leave it **OFF**. The definition will be available in the future.



4. Select the type of plot. The options change appropriately:

• L (scatter plot)	XL	YL	MARK
• LC (XYLine)	XL	YL	MARK
• ☐ (box plot)	XL	F	
• ▨ (histogram)	XL	F	

5. Depending on the type of plot, select the options:

- **XL** (list of independent data)
- **YL** (list of dependent data)
- **F** (frequency, 1 is used if no list is specified)
- **MARK** (□, *, or •)

Turning Plots Off or On

PLOTSON and **PLOTSOFF** allow you to turn statistical plots off or on from the Home screen or a program. Used without plots, they turn all plots off or all plots on. Used with plots, they turn specific plots off or on.

PLOTSOFF or **PLOTSON**

PLOTSOFF *plots,plots*,

PLOTSON *plots,plots*,

For example, **PLOTSOFF** followed by **PLOTSON 3** turns all plots off and then turns **PLOTS** on.

PLOTSOFF	NONE
PLOTSON 3	NONE

Defining the Viewing Window

Statistical plots are displayed on the current graph. You may define the viewing window by pressing **WINDOW** and then entering values for the Window variables.

Tracing a Stat Plot

When you trace a scatter plot or **XYLine**, tracing begins at the first element in the list.

When you trace a box plot, tracing begins at **MED** (the median). Press **↓** to trace to **Q1** and **MIN**. Press **↑** to trace to **Q3** and **MAX**.

When you trace a histogram, the cursor moves to the top centre of each column, starting at the first column.

When you press **→** or **←** to move to another plot or **Y=** function, the log moves to the current or starting point on that plot.

Statistical Analysis in a Program

You can enter statistical data, calculate statistical results, and match data to models from a program.

Entering Stat Data

Enter the statistical data directly into lists (Chapter 8) in the program.

```
PROGRAM STAT1
C15: 38+42+54+64
C-->L1
C C4+6+7+9+113->L
END
```

Statistical Calculations

To calculate statistical results or match data to a model from a program.

1. On a blank line in the program editor, select the type of calculation from the **STAT CALC** menu.
2. Enter the names of the lists, separated by commas, to be used in the calculation.

```
PROGRAM STAT1
C15: 38+42+54+64
C-->L1
C C4+6+7+9+113->L
L1*REG(4:38+4 ) L1
C L2
END
```

Note To display a regression equation and coefficients from a program, the regression function must be the last statement in the program. If it is not the last statement the regression equation will be evaluated and stored, but the results will not be displayed.

Statistical Plotting in a Program

To display a statistical plot, you may define the plot(s), then turn the plot(s) on, and then display the graph. If you do not define the plot, the current definitions are used.

Defining a Stat Plot in a Program

To define a statistical plot in a program,

1. Enter the data into list(s). On a blank line in the program editor, press $\boxed{\text{2ND}} \boxed{\text{FLOT}} \boxed{\text{1}}$ to display the **PLOTS** menu.
2. Select the plot to be defined. **PLOTT1**, **PLOTT2**, or **PLOTT3** is copied to the cursor location.

```
PLOTS TYPE MARK
PLOT1
PLOT2
PLOT3
PLOT3OFF
PLOT3ON
```

```
PROGRAM:STAT9
0:1+2+3+45+54.4
1:5+6+7+45+54.3
2:PLOTT1/L1+L2+L3
```

3. Press $\boxed{\text{2ND}} \boxed{\text{FLOT}} \boxed{\text{2}}$ to display the **TYPE** menu. Select the type of plot, $\boxed{\text{L}}$ (scatter), $\boxed{\text{I}}$ (XLine), $\boxed{\text{B}}$ (box), or $\boxed{\text{H}}$ (histogram) is copied to the cursor location.
4. Press $\boxed{\text{1}}$. Enter the list names, separated by commas.

```
PLOTS TYPE MARK
L1
L2
L3
```

```
PROGRAM:STAT9
0:1+2+3+45+54.4
1:5+6+7+45+54.3
2:PLOTT1/L1+L2+L3
```

5. (This step is for **L** and **I** only.) Press $\boxed{\text{1}}$. Press $\boxed{\text{2ND}} \boxed{\text{FLOT}} \boxed{\text{2}}$ to display the **MARK** menu. Select the mark $\boxed{\text{+}}$, $\boxed{\text{*}}$, or $\boxed{\text{^}}$ is copied to the cursor location.
6. Press $\boxed{\text{1}}$ and $\boxed{\text{2ND}} \boxed{\text{FLOT}} \boxed{\text{3}}$ to complete the command line.

```
PLOTS TYPE MARK
L1
L2
L3
+
```

```
PROGRAM:STAT9
0:1+2+3+45+54.4
1:5+6+7+45+54.3
2:PLOTT1/L1+L2+L3
+
3:PLOTT1/L1+L2+L3
```

7. Press $\boxed{\text{2ND}} \boxed{\text{FLOT}} \boxed{\text{3}}$ to copy **PLOTT3** to the command line and the number of the plot (1, 2, or 3) to turn on. Press $\boxed{\text{ENTER}}$ to complete the command line.

```
PROGRAM:STAT9
0:1+2+3+45+54.4
1:5+6+7+45+54.3
2:PLOTT1/L1+L2+L3
+
3:PLOTT3OFF
PLOT3ON 1
END
```

Note that **PLOTT3OFF** in the example program ensures that all other plots are turned off.

Statistical Plotting in a Program (Continued)

Displaying a Stat Plot from a Program

To display a plot, use any of the *Zoom* instructions (Chapter 4), or use the **DISPGGRAPH** instruction (Chapter 10).

```
PROGRAM:STATS
1 L1-2> 3-42->L1
2 C1-60 3-45->L2
3 PLOT1(L1>L1>L2>
4 1
5 ZSTANDARD
6 0
```

```
PROGRAM:STATS
1 PLOT:OFF
2 FREQF
3 PLOT1(L1>L1>L2>
4 PLOT:ON 1
5 DISPGGRAPH
6 0
```


Chapter 10: Programming

This chapter describes specific programming instructions and explains how to enter and execute programs on the TI-80.

Chapter	Getting Started: Rolling a Dice	10-2
Contents	About TI-80 Programs	10-4
	Creating and Executing Programs	10-5
	Editing Programs	10-6
	PRGM C/L (Control) Instructions	10-7
	PRGM IO (Input/Output) Instructions	10-11
	Calling Other Programs	10-14

7. Press **[MATH]** **[2]** to access the **MATH PRB** menu. Press **[5]** to copy **RANDINT** to the cursor location and then **1** **[]** **6** **[]** **[ENTER]** **[2]** **[]** **[ENTER]** **[1]** **[]** **[ENTER]** **[1]** **[]** **[ENTER]** to generate random integers from 1 to 6, and store them into element 1 of L1. Press **[ENTER]** to complete the instruction.

```
PROGRAM:ROLL
EO:0010 L1
EO:INPUT "ROLL L1"
EO:
EO:FOR(I,1,6-1)
EO:  RANDINT(1,6)-M
EO:I I
EO:
EO:
EO:
```

8. Press **[F5]** **[2]** to select **DISP** (display), which is copied to the cursor location. Press **[2]** **[]** **[ENTER]** **[1]** **[]** **[ENTER]**. This instruction displays the value of element 1 (the result of the last roll) in L1. Press **[ENTER]** to complete the instruction.

```
PROGRAM:ROLL
EO:INPUT "ROLL L1"
EO:
EO:FOR(I,1,6-1)
EO:  RANDINT(1,6)-M
EO:I I
EO:  DISP L1(I)
EO:
EO:
```

9. Press **[F5]** **[4]** to select **PAUSE**, which is copied to the cursor location. This pauses the program after displaying the result of the last roll. Press **[ENTER]** to complete the instruction.

```
PROGRAM:ROLL
EO:
EO:FOR(I,1,6-1)
EO:  RANDINT(1,6)-M
EO:I I
EO:  DISP L1(I)
EO:  PAUSE
EO:
EO:
```

10. Press **[F5]** **[5]** to select **END**, which is copied to the cursor location. **END** identifies the end of the group of commands in the **FOR** loop. Press **[ENTER]** to complete the instruction.

```
PROGRAM:ROLL
EO:FOR(I,1,6-1)
EO:  RANDINT(1,6)-M
EO:I I
EO:  DISP L1(I)
EO:  PAUSE
EO:END
EO:
EO:
```

11. Press **[F5]** **[2]** **[DISP]** **[1]** **[]** **[ENTER]** to display the list of all the roll results. Press **[ENTER]** to complete the instruction.

```
PROGRAM:ROLL
EO:RANDINT(1,6)-M
EO:I I
EO:  DISP L1(I)
EO:  PAUSE
EO:END
EO:  DISP L1
EO:
EO:
```

12. Press **[2D]** **[EXIT]** **[2ND]** **[F5]**. Move the cursor to the program name: **ROLL**. Press **[ENTER]**. Press **[ENTER]** again from the Home screen to execute **PRGM:ROLL**.

About TI-80 Programs

Most features of the TI-80 are accessible from programs. Programs can access all variables and named items. The number of programs that the TI-80 can store is limited only by the memory available.

Notes about Programs

Programs are identified by names of up to seven characters, beginning with a letter.

A program consists of a series of program commands, which begin with a **:** (colon). A program command can be an expression (a command, usually a combination of variables, functions, and numeric values, that returns a value to **ANS**) or an instruction (a command, such as **GRIDON** or **PT-ON**, that does not return a value to **ANS**).

The TI-80 checks for errors when you execute the program, not as you enter or edit the program.

Variables and lists saved in the memory are global, i.e., they can be accessed from all programs. Storing a new value in a variable or list in a program changes the value in the memory during program execution.

As calculations are made in programs, the TI-80 updates **ANS**, just as it would if the calculations were being carried out on the Home screen. Programs do not update Last Entry as each command is executed.

"Breaking" a Program

Pressing **▢** stops program execution. When you press **▢** during program execution, the **ERR: BREAK** menu is displayed.

- To go to where the interruption occurred, select **GOTO**.
- To return to the Home screen, select **QUIT**.

Memory Management and Erasing Programs

The size of programs you can store is limited only by the memory available. To access the **MEMORY** menu, press **▢** [MEM] from the Home screen. Memory status is displayed on the **MEMORY CHECK RAM...** screen. To increase available memory, you can delete items, including other programs, from the **MEMORY DELETE** screen (Chapter 12).

Note: Each token in a program takes 1 byte. For example, **SIN(1.23)** takes 5 bytes.

Creating and Executing Programs

Access the program editor by pressing **PF5**. Then either choose to create a new program or edit an existing program. In general, anything that can be executed from the Home screen can be included in a program. A program command always begins with a colon (:).

Creating a New Program

To create a new program:

1. Press **PF5** **[F2]** **[F2]** to display the **PRGM NEW** menu. Press **[F1]** to select **CREATE NEW**.



A screenshot of the PRGM NEW menu. It shows a rectangular box with the text "PRGM" on the top line and "NAME=" on the bottom line. The cursor is positioned at the end of the "NAME=" line.

2. The keyboard is in **ALPHA-LOCK**. Enter the name you want for the program, followed by **[ENTER]**. The name may consist of between one and seven characters (A-Z, 0-9) and must begin with a letter.
3. Enter the program commands.

Entering Program Commands

A colon (:) indicates the beginning of each program command. To enter more than one command on a line, separate them with a colon, just as you would on the Home screen. Press **[ENTER]** to indicate the end of a command line.

When a command is longer than one line on the screen, it wraps to the next line. **[F2]** **[F1]** and **[F2]** **[F1]** move the cursor to the beginning and end of a command line.

In the program editor, if you press a key that accesses a menu, the menu screen temporarily replaces the program edit screen. When you make a selection or press **[F2]** **[F1]** you are returned to the program editor.

Leaving the Program Editor

When you finish entering or editing a program, press **[F2]** **[QUIT]** to return to the Home screen. You must be on the Home screen to execute a program.

Executing a Program

To execute a program:

1. From a blank line on the Home screen, press **PF5** to display the **PRGM EXEC** menu. The names of all existing programs are listed, in alphabetical order.
2. Select a program **PRGM** and the program name are copied to the Home screen, for example, **PRGM ACAL**.
3. Press **[ENTER]** to begin program execution. While the program is being executed, the busy indicator is displayed.

Editing Programs

The program editor also lets you edit an existing program. As you edit, you can enter commands just as you did when you created the program.

Editing a Program

To edit a program:

1. Press **PRGM** **[1]** to display the **PRGM EDIT** screen.



```
PRGM EDIT
PRGM1
1: 1->A
2: 1->B
3: 5->C
```

2. Select the name of an existing program. The program editor and the commands in that program are displayed.
3. Edit the program by changing, inserting, or deleting commands, as needed.

Changing Instructions

Move the cursor to the command you want to change:

- Position the cursor, and then make the changes by typing over the command or using **[DEL]** or **[INS] [DEL]**.
- Press **[CLR] [DEL]** to clear (blank) all program commands on the command line (The initial colon is not deleted.), and then enter a new program command.

Inserting a New Command Line

To insert a new command line, position the cursor where you want to insert the new line, press **[INS] [INS]** to put the TI-80 in insert mode, and then press **[ENTER]**.

Deleting a Command Line

To delete a command line, press **[CLR] [DEL]** to clear the line, and then press **[DEL]** to delete the colon.

Notes: All programs end with a blank command line; the colon on this line cannot be deleted.

PRGM CTL (program control) instructions can only be accessed from within the program editor. They direct the flow within a program being executed, making it easy to repeat or skip commands during program execution. While the program editor is displayed, press **[F3]**. The selected menu item is copied to the cursor location.

PRGM CTL Menu

CTL 1/0 EXEC

1: IF	Creates a conditional test.
2: THEN	Used with IF
3: ELSE	Used with IF-THEN
4: FORI	Creates incrementing loop
5: END	Signifies end of loop, IF-THEN or ELSE
6: PAUSE	Pauses program execution
7: LBL	Defines a label
8: GOTO	Goes to a label.
9: PRGM	Executes a program as a subroutine
0: RETURN	Returns from a subroutine
A: STOP	Stops program execution

Controlling Program Flow

Program control instructions tell the TI-80 which command to execute next in a program. IF checks a condition that you define, to determine what command to execute next. The condition frequently uses relational tests (Chapter 2), such as **IF A<7,A+1→A**.

IF

IF (PRGM CTL, item 1) is used for testing and branching. If the condition is false (zero), the command immediately following IF is skipped. If the condition is true (nonzero), that command is executed. IF instructions can be nested

*IF condition
:command if true
:command*

```
PROGRAM:COUNT
00->0
01LBL 2
02->1->0
03IF "A IS">0
04IF 0:12
05STOP
06GOTO 2
```

```
PRGM:COUNT
A 12
1
A 12
2
END
```

PRGM CTL (Control) Instructions (Continued)

IF-THEN
END

THEN (PRGM CTL, item 3) following an IF executes a group of commands if the condition is true (nonzero)

END (PRGM CTL, item 3) identifies the end of the group

```
IF condition  
:THEN  
command if true  
:  
:END  
command
```

```
PRGM:TEST  
X=10-5Y  
IF X<0  
:THEN  
Z=1-Y  
Y=3-Y  
END  
PRGP C=10
```

```
PRGM:TEST  
X=10-5Y  
IF X<0  
:THEN  
Z=1-Y  
Y=3-Y  
END  
PRGP C=10
```

IF-THEN-ELSE
END

ELSE (PRGM CTL, item 3) following IF-THEN executes a group of commands if the condition is false (zero)

END (PRGM CTL, item 3) identifies the end of the group

```
IF condition  
:THEN  
command if true  
:  
:ELSE  
command if false  
:  
:END  
command
```

```
PRGM:TESTELS  
X=10-5Y  
IF X<0  
:THEN  
Z=1-Y  
Y=3-Y  
ELSE  
Z=1-Y  
Y=3-Y  
END  
PRGP C=10
```

```
PRGM:TESTELS  
X=10-5Y  
IF X<0  
:THEN  
Z=1-Y  
Y=3-Y  
ELSE  
Z=1-Y  
Y=3-Y  
END  
PRGP C=10
```


FOR
END

FOR (**FROM** CTL item 4) is used for looping and incrementing. It increments the variable from the start value to the finish value, by the specified increment. The finish value is a maximum or minimum value that is not to be exceeded. The increment is optional (if not specified, 1 is used) and can be negative (finish value - start value).

END identifies the end of the loop. **FOR** loops can be nested.

FOR(*variable,begin,end,increment*)
statement while end not exceeded
:
END
statement

```
PROGRAM:RUNTIME
FOR(A=0 to 10)
  DISP A
  CLEAR
END
```

```
PROGRAM:RUNTIME
FOR(A=0 to 10)
  DISP A
  CLEAR
END
```

END

END (**FROM** CTL item 7) identifies the end of a group of commands. Each **FOR** and each **IF-THEN** or **IF-THEN-ELSE** group must have an **END** at the "bottom."

PAUSE

PAUSE (**FROM** CTL item 6) suspends execution of the program so that you can see answers or graphs. During the pause, the dotted pause indicator is displayed. When **DSP** or **DISPGRAPH** is executed, the appropriate screen is displayed. Press **[EXIT]** to resume program execution.

```
PROGRAM:PAUSE
DISP "a+b="
PAUSE
DISPGRAPH
PAUSE
DISP
```


PRGM I/O (Input/Output) Instructions

The **PRGM I/O** (program input/output) instructions can only be accessed from the program editor. They control input to and output from a program, allowing you to enter values and display answers during program execution. While the program editor is displayed, press **[PRGM]**. The selected menu item is copied to the cursor location.

PRGM I/O Menu

CTL	I/O	EXEC
1	INPUT	Enters a value or displays the current graph
2	DISP	Displays text, value, or the Home screen
3	DISPGRAPH	Displays the current graph.
4	CLRHOME	Clears the Home screen

Displaying a Graph with INPUT

INPUT without a variable displays the current graph. You can move the free-moving cursor, which updates **X** and **Y**. The dotted pause indicator is displayed. Press **[ENTER]** to resume program execution.

For example, **INPUT** during program execution displays:

```
PROGRAM:GSPRT
COUNT
C:0.000000
X:0.000000
Y:0.000000
DISP  X=0
```



Storing a Variable Value with INPUT

INPUT with a variable displays a ? prompt during program execution. The value may be a real number, a list, or Yn function. Enter a value (which can be an expression of a list), and press **[ENTER]**. The value is evaluated and stored to the variable, and the program resumes execution.

INPUT *variable*

INPUT *listname*

INPUT *Yname*

```
PROGRAM:R1INPUT
R1INPUT A
R1INPUT L1
R1INPUT T1
R1ISP Y1(A)
R1ISP Y1(L1)
```

```
PRGM:R1INPUT
A=2
L1={1,2,3}
T1=2A+5A
          9
          CT 9 11.5
          DONE
```

You can enter a string of up to 30 characters up to the prompt, for the value to be entered. After the prompt, enter a value (which can be an expression of a list), and press **[ENTER]**. The value is stored in the variable, and the program resumes execution.

INPUT "string", *variable*

INPUT "string", *listname*

INPUT "string", *Yname*

```
PROGRAM:R1INPUT
R1INPUT "A="A
R1INPUT "L1="L1
R1INPUT "T1="T1
R1ISP Y1(A)
R1ISP Y1(L1)
```

```
PRGM:R1INPUT
A=2
L1={1,2,3}
T1=2A+5A
          9
          CT 9 11.5
          DONE
```

Note: When you input lists and expressions during program execution, you must include the braces {} around the list values and quotation marks (") around expressions.

Displaying the Home Screen

DSP (display, **PRGM** IQ, item 2) with no value displays the Home screen. To view the Home screen during program execution, follow the **DSP** instruction with a **PAUSE**.

Displaying Values and Messages

DSP (display, **PRGM** IQ, item 2) with one or more values displays the value of each

DSP value

DSP value1,value2

- If value is a variable, the current value is displayed.
- If value is an expression, it is evaluated and then displayed, according to the current mode settings, on the right hand side of the following line
- If value is text within " marks, it is displayed on the left hand side of the current display line

For example, **DSP** "ANSWER IS",A/2 displays:



If **PAUSE** is encountered after **DSP**, the program halts temporarily so that you can examine the screen. Press **[EXIT]** to resume program execution.

Note: A statement that results in a value will display without using **DSP** if it is the last statement (other than **STOP**, **END**, and **PAUSE**) in the program.

DISPGRAPH

DISPGRAPH (display graph, **PRGM** IQ, item 3) displays the current graph. If **PAUSE** is encountered after **DISPGRAPH**, the program halts temporarily so you can examine the screen. Press **[EXIT]** to resume execution.

CLRHOME

CLRHOME (clear Home screen, **PRGM** IQ, item 4) clears the Home screen during execution and places the cursor in the top left hand corner; however, program execution does not pause unless **PAUSE** is encountered.

Calling Other Programs

On the TI-80, any program can be called from another program, as a subroutine. Enter the name of the program to be used as a subroutine on a line of its own.

Calling a Program from Another Program

To call one program from another, begin on a blank line in the program editor and do one of the following:

- Press **PRGM** **▢** to display the **PRGM EXEC** menu, and select the name of the program. **PRGM_** and the name are copied to the cursor location, or
- Select **PRGM_** from the **PRGM CTL** menu and then type the letters of the program name.

PRGM_programname

When this instruction is encountered during program execution, the next command that the program executes is the first command in the second program. Execution continues with the subsequent command in the first program when it encounters either a **RETURN** instruction or when the implied **RETURN** at the end of the called program is encountered.

```
PRGM:MYPRG1
L1:DEFN 1011-0
L2:DEFN 1011-0
PRGM:ABCDEF
CA:0-10
CRIP 0
```

```
PRGM:ABCDEF
C: 1-10
C: 1-10-10
SETERR
```

```
PRGM:MYPRG1
End
M=1
EL:1011-10
END
```

Notes about Calling Programs

Variables are global.

A label used with **GOTO** and **LBL** is local to the program in which it is located. A label in one program is not "known" by another program. You cannot use **GOTO** to branch to a label in another program.

RETURN exits a subroutine and returns to the calling program, even if encountered within nested loops.

Chapter 11: Applications

This chapter contains application examples that incorporate the TI-80 features described in the preceding chapters. Several of the examples use programs.

Chapter	Probability Experiments: Coins, Dice, and Spinners	11-2
Contents	The Unit Circle and Trigonometric Curves	11-5
	Program: Newton's Numerical Solver Routine	11-6
	Program: Numerical Integration	11-6
	Program: Window Variables: Store and Recall	11-8
	Graphing the Inverse of a Function	11-10
	Graphing a Piece-by-Piece Function	11-12
	Graphing Inequalities	11-14
	Graphing a Polar Equation	11-15
	Program: Guess the Coefficients	11-16

Probability Experiments: Coins, Dice, and Spinners

The **RANDINT**(random integer) function can be used for probability experiments. **RANDINT** takes two arguments that define a set of integers from which to draw for the probability experiments below.

Problem Using **RANDINT** from the **MATH PRB** menu, devise probability experiments that employ the toss of a coin, the roll of two dice, and the spin of a wheel.

Procedure For the coin-tossing experiment, enter **RANDINT(0,1)** from the Home screen. 0 = tails and 1 = heads. Press **ENTER** repeatedly to generate the coin tosses.

```
RANDINT(0,1)
0
1
0
1
0
1
0
1
```

You can also write a simple program to display "heads" or "tails" for each coin toss.

```
PROGRAM COIN
:RANDINT(0,1)->R
:IF R=0
:DISP "TAILS"
:IF R=1
:DISP "HEADS"
```

```
PRGM COIN
TAILS
HEADS
HEADS
HEADS
```

You can simulate the rolling of two dice by adding together the results from each die after a roll. On the Home screen, enter **RANDINT(1,6)+RANDINT(1,6)** and press **ENTER** repeatedly.

```
RANDINT(1,6)+RANDINT(1,6)
10
4
7
6
6
```

You can simulate spinning a wheel with the numbers 1 to 100 using the **RANDINT** function. Enter **RANDINT(1,100)** on the Home screen and press **ENTER** repeatedly.

```
RANDINT(1,100)
74
98
40
25
9
66
```


The Unit Circle and Trigonometric Curves

You can use the parametric graphing feature of the TI-80 to show the relationship between the unit circle and any trigonometric curve.

Problem

Graph the unit circle and the sine curve to demonstrate graphically the relationship between them.

Any function that can be plotted in function graphing can be plotted in parametric graphing by defining the X component as T and the Y component as F(T).

Procedure

Following this procedure to solve the problem.

1. Press $\boxed{\text{MODE}}$ and select **RADIAN**, **PARAM**, and **SINGLE**.
2. Press $\boxed{\text{WINDOW}}$ and set the Window variables.

$T_{\text{MIN}} = 0$	$X_{\text{MIN}} = -2$	$Y_{\text{MIN}} = -3$
$T_{\text{MAX}} = 2\pi$	$X_{\text{MAX}} = 2\pi$	$Y_{\text{MAX}} = 3$
$T_{\text{STEP}} = .1$	$X_{\text{SCL}} = \pi/2$	$Y_{\text{SCL}} = 1$

3. Press $\boxed{\text{F1}}$ and enter the expressions to define the unit circle centered at $(-1, 0)$.

$X1 = \cos T - 1$	$Y1 = \sin T$
-------------------	---------------

Enter the expressions to define the sine curve.

$X2 = T$	$Y2 = \sin T$
----------	---------------

Turn off all other functions.

```

X1=cos T-1
Y1=sin T
X2=T
Y2=sin T
X3=
Y3=

```

4. Press $\boxed{\text{GRAPH}}$ to see the **SIN** function "unwrapped" from the unit circle.



Note: The "unwrapping" can be generalised. Replace **SIN T** in **Y2** with any other trig function to "unwrap" that function.

Program: Newton's Numerical Solve Routine

This program uses the Newton-Raphson method to find the roots (zeros) of a function numerically.

Problem Find the roots of $e^X - 3X$

Program This program uses the Newton-Raphson method to find a root of **Y1** based on an initial guess. The program prompts for the initial guess. One way to make this initial guess is to graph and trace the function, and then enter X as the guess.

```
PROGRAM: NEWTON
: INPUT "INITIAL X=", X      Input initial guess
: LBL N                      Begin loop
: X= 1/DERIV(Y1,X,X)→R      Calculate new root
: DISP R
: PAUSE
: IF ABS (X-R)>ABS (X/1E10)  Test for convergence
: STOP
: R→X                        Estimate with new root
: GOTO N
```

Procedure Follow this procedure to solve the problem

1. Press **MODE** and select **FUNC**.
2. Enter the program.
3. Press **[Y=]**. Enter the expression, $e^X - 3X$, to define **Y1**.



Y1= $e^X - 3X$
Y2=
Y3=
Y4=

4. Graph the function using **ZDecimal** from the **ZOOM** menu.



Program: Numerical Integration

This program uses Simpson's method to estimate the definite integral of a function.

Problem Estimate the definite integral of

$$\int_0^1 (x^3 - 4x^2)dx$$

and graph the area of the integral

Program The program estimates the definite integral for **Y1** using Simpson's method. It prompts for the lower and upper limits of integration and the number of divisions

```
PROGRAM: SIMPSON
: INPUT "LOWER LIMIT=" ,A      Input lower limit.
: INPUT "UPPER LIMIT=" ,B      Input upper limit
: INPUT "N DIVISIONS=" ,D      Input # of divisions.
: D→S
: (B-A)/(2*D)→W               Calculate division width.
: FOR(J,1,D,1)                 Begin calculation loop
: A+2(J-1)W→L                  Calculate left point
: A+2JW→R                      Calculate right point.
: (L+R)/2→M                    Calculate midpoint
: W(Y1(L)+4Y1(M)+Y1(R))       Calculate division sum and
/3+S→S                          add to total
: END
: DISP "AREA="                 Display results
: DISP S
```

Procedure Follow this procedure to solve the problem

1. Enter the program
2. Press **[Y=]** and enter the function in **Y1**. Turn any other functions off.



```
Y1=X^3-4X^2
Y2=
Y3=
Y4=
```

3. Set the Window variables

```

BMPSON
BMPN=-1
BMPD=3
BSEL=1
TMIN=100
TMAX=10
TSEL=1

```

4. Execute the program **BMPSON** from a clear Home screen, creating the lines and divisions as you are prompted

```

PROMPTON
LTYPE L=100
UPPER L=101+L*E
B DIVISIONS=10
AREA=
      -2.7946257E8
      DONE

```

5. You can display the calculated area graphically, using **SHADE** from a clear Home screen

```

SHADE BMD 0xT1.7x
BMD 0xT1.7xLx0.1

```



Program: Window Variables Store and Recall

The program below lets you store the values for the current Window variables, and it lets you display a graph using previously stored values. It also demonstrates a method for including menus in a program.

Program	PROGRAM-WINMEM	
	:CLRRHME	
	:DISP "WINDOW MEMORY"	} Present menu of choices
	:DISP "1:STORE WINDOW"	
	:DISP "2:RECALL WINDOW"	
	:DISP "3:QUIT"	
	:DISP " "	
	:DISP "ENTER 1,2, OR 3"	
	:INPUT H	
	:IF H=1	} Evaluate menu selection
	:GOTO S	
	:IF H=2	
	:GOTO R	
	:GOTO Q	
	:LBL S	} Store current graph Window variable values
	:XMIN→A	
	:XMAX→B	
	:XSCL→C	
	:YMIN→D	
	:YMAX→E	
	:YSCL→F	
	:DISP "WINDOW STORED"	
	:GOTO Q	
	:LBL R	} Display graph with previously stored variable values
	:A→XMIN	
	:B→XMAX	
	:C→XSCL	
	:D→YMIN	
	:E→YMAX	
	:F→YSCL	
	:DISPGRAPH	
	:GOTO Q	} Quit program
	:LBL Q	
	:STOP	

Procedure

Follow this procedure to see how the program works.

1. Execute the program **WINMEM** from a blank Home screen.



The program prompts with three options:

- Store the Window variables you are currently using
- View a graph using a previously stored set of Window variables
- Quit the program.



2. Press 1, 2, or 3 and then **ENTER** to respond to the prompts.

The Window values are stored in variables A, B, C, D, E, and F.

Graphing the Inverse of a Function

You can use the parametric graphing feature of the TI-80 to graph the inverse relation of any function, by defining the function in $X1$ and $Y1$ and its inverse in $X2$ and $Y2$.

Problem

The function $Y = 2X^3 - 2X + 6$ can be expressed in parametric form as $X1 = T$ and $Y1 = 2T^3 - 2T + 6$.

The inverse relation of the function can be expressed in parametric form as $X1 = R(T)$ and $Y1 = T$. For example, $Y = 2X^3 - 2X + 6$ would be expressed as $X1 = 2T^3 - 2T + 6$ and $Y1 = T$.

Graph the function $Y = 2X^3 - 2X + 6$ and its inverse.

Procedure

Follow this procedure to solve the problem.

1. Select **PARAM**, **CONNECTED**, and **SIMUL** modes.

2. Change the Window variable values.

TMIN = -10	XMIN = -10	YMIN = 0
TMAX = 10	XMAX = 10	YMAX = 0
TSTEP = .4	XSCAL = 1	YSCAL = 0

3. Enter the expressions to define the function in parametric form.

X1 = T
Y1 = 2T³ - 2T + 6

4. Enter the expressions to define the inverse in parametric form.

X2 = 2T³ - 2T + 6
Y2 = T

5. Enter the expressions to define the line $Y=X$, about which the graph of the function and the graph of its inverse are symmetric. That is, the reflection of the graph of the function through the line $Y=X$ produces the graph of its inverse.

$$X2T=T$$

$$Y2T=T$$



6. Press $\boxed{\text{GRAPH}}$ to plot the graph. Press $\boxed{\text{TRACE}}$, and then press $\boxed{\Delta}$ several times (until the cursor appears). Next, press $\boxed{\square}$ and $\boxed{\Delta}$ several times to move the cursor from a point on the relation to the reflected point and back again.



Note: The expressions to define the inverse can be generalized

$$X1T=Y2T$$

$$Y1T=X2T$$

Graphing a Piece-by-Piece Function

The test functions of the TI-85 can be used to build piece-by-piece defined functions.

Problem

Define and graph this piece-by-piece defined function:

$$f(x) = \begin{cases} x^2, & \text{for } x \leq 3 \\ 1.5x + 1, & \text{for } 3 < x \leq 5 \\ 6 - x, & \text{for } x \geq 5 \end{cases}$$

The **TEST** functions, which return 1 if true and 0 if false, can be used to build piece-by-piece defined functions. For example, when $x = 4$, $(x \leq 3)$ is false and will return 0.

<code>Y1(0.23)</code>
<code>Y1(3)</code>
<code>Y1(4)</code>
<code>Y1(5)</code>

<code>Y1(2)</code>	1
<code>Y1(4)</code>	0

Procedure

Follow this procedure to solve the problem.

1. Press **MODE** and select **FUNC**.
2. Enter the first piece of the function in the **Y=** editor. This piece is $f(x) = x^2$ for $x \leq 3$. It is entered as $(x^2)(x \leq 3)$. **Y1** is then equivalent to x^2 for $x \leq 3$ and $x^2 \cdot 0$ for $x > 3$.

<code>Y1(0.23)(X<=3)</code>
<code>Y1(3)</code>
<code>Y1(4)</code>
<code>Y1(5)</code>

<code>Y1(2)</code>	4
<code>Y1(4)</code>	0

3. Add the second piece of the function in the **Y=** editor. This piece is $f(x) = 1.5x + 1$ for $3 < x \leq 5$. It is entered as $(1.5x + 1)(3 < x \leq 5)$.

When x is less than 3, the test $(3 < x)$ returns 0, and the test $(x \leq 5)$ returns 1. In this case, the second piece of the function is equivalent to $(1.5x + 1)(0)$, which is 0. Only when both of these tests are true will the second piece of this function be anything but 0.

<code>Y1(0.23)(X<=3)(1.5X+1)(3<X<=5)</code>
<code>Y1(3)</code>
<code>Y1(4)</code>
<code>Y1(5)</code>

<code>Y1(2)</code>	4
<code>Y1(4)</code>	7
<code>Y1(6)</code>	0

4. Add the third piece of the function to **Y1**. This piece is $f(x)=6-x$ for $x \geq 5$. It is entered as **(6-X)(X>5)**. When x is greater than or equal to 5, the test $(x>5)$ returns 1. The third piece of the function is then equivalent to $(6-x)(1)$. When x is less than 5, the test $(x>5)$ returns 0. The third piece of the function is then equivalent to $(6-x)(0)$.

Y1= (X(X<5)=(5-X)(X<5)+	Y1(2.5)	
(5-X)(X<5)+	Y1(4)	4
(6-X)(X>5)	Y1(8)	7
Y2=		
Y3=		
Y4=		-2

5. Enter these Window variable values:

XMIN=-2	YMIN=-2
XMAX=8	YMAX=10
XSCL=2	YSCL=1

6. First graph the piece-by-piece function in **CONNECTED** and then **DOT** mode. Select **CONNECTED** on the **MODE** screen, and then press **GRAPH**. Then select **DOT** on the **MODE** screen, and press **GRAPH**.



Graphing Inequalities

Examine the inequality $4X^2 - 3X + 5 < 2X + 4$ graphically. Use the TEST functions to explore the values of X where the inequality is true and where it is false.

Procedure

1. Press **MODE**. Select **DOT**, **RECALL**, and the default mode settings. Press **2nd** **FORMAT**, and turn off all stat plots.
2. Press **Y=**, and turn off all functions. Enter the left side of the inequality as **Y1**, the right side as **Y2**, and the statement of the inequality as **Y3**. **Y3** evaluates to 1 if true and 0 if false.

```
Y1= 4X^2-3X+5
Y2= 2X+4
Y3= Y1<Y2
Y4=
```

4. Press **WINDOW** and enter the following variable values:

```
XMIN=-10      YMIN=-10
XMAX=10       YMAX=10
XSCLE=5       YSCLE=5
```

5. Press **TRACE**. Press **□** **Y3** to move to **Y3**. Trace the inequality, observing the value of **X**. **Y3** is 1 when $Y1 < Y2$, and **Y3** is 0 when $Y1 \geq Y2$.



6. Press **Y=** and turn off **Y1** and **Y2**. Enter equations to graph only the inequality.

```
Y1= 4X^2-3X+5
Y2= 2X+4
Y3= Y1<Y2 >Y4
Y4= Y1<Y2 >Y3
```

7. Press **TRACE**. Notice that the values of **Y3** and **Y4** are zero where the inequality is false.



Graphing a Polar Equation

The parametric graphing feature of the TI-89 can be used to graph polar equations. Graph the Spiral of Archimedes, the name given to the curve defined by the polar equation $r = \theta$.

Problem

A polar equation $r = f(\theta)$ can be graphed by applying the conversion formulas, $x = f(\theta) \cos(\theta)$ and $y = f(\theta) \sin(\theta)$. Thus, the Spiral of Archimedes can be expressed parametrically as

$$x = \theta \cos(\theta)$$

$$y = \theta \sin(\theta)$$

Procedure

Follow this procedure to solve the problem.

1. Select **PARAM** mode. Choose the defaults for the other mode settings.
2. Enter the expressions to define the parametric equations in terms of T



```
P1: X=T*cos(T)
P2: Y=T*sin(T)
```

3. Set the Window variables to the following values:

$$TMIN=0$$

$$XMIN=-10$$

$$YMIN=-10$$

$$TMAX=25$$

$$XMAX=10$$

$$YMAX=10$$

$$TSTEP=\pi/8$$

$$XSCL=1$$

$$YSCL=1$$

4. Press **GRAPH** to display the Spiral of Archimedes.



Program: Guess the Coefficients

This program generates a function in the form $A \cdot \sin(BX)$ with random integer coefficients between 1 and 10. Seven data points from the function are plotted. You are prompted to guess the coefficients, which are plotted as $C \cdot \sin(DX)$. The program continues until your guess is correct. It can be modified for other functions.

Program

```
PROGRAM: GUESS
:FUNC: RADIAN
: 33(4/12)→XMIN
:33(4/12)→XMAX
:4/2→XSCL
: 10→YMIN
:10→YMAX
:1→YSCL
:"A=518 (BX)"→Y1
(RANDINT(1,10)→A
(RANDINT(1,10)→B
:PLOTSOFF: FREEF
:DISPGRAPH
:SETCARH→1→AT.1.0,42.9)→L1
:Y1(L1)→L2
:POINTSL.1(L1,L2,C)
:DISPGRAPH
:PAUSE
:"C=518 (DX)"→Y2
:CLR: M
:CLRHOME
:DISP "C=518 (DX)"
:INPUT "C=",C
:INPUT "D=",D
:DISPGRAPH
:PAUSE
:IF C=A
:DISP "C IS OK"
:IF C>A
:DISP "C IS TOO HIGH"
:IF C<A
:DISP "C IS TOO LOW"
:IF D=B
:DISP "D IS OK"
:IF D>B
:DISP "D IS TOO HIGH"
:IF D<B
:DISP "D IS TOO LOW"
:PAUSE
:IF 100-A2(D-B)2=1
:STOP
:GOTO M
```

Set viewing window

Initialize coefficients

Display data points

Prompt for guesses

Display results

Quit if guesses are correct

Chapter 12: Memory Management

This chapter describes how to manage memory on the TI-83. To increase the amount of memory available for use, you may occasionally want to delete stored items that you are no longer using. You can also reset the calculator, erasing all data and programs.

Chapter	Checking Available Memory	12-2
Contents	Deleting Items from Memory	12-3
	Resetting the TI-83	12-4

Checking Available Memory

The **MEMORY CHECK RAM** screen displays the total amount of memory available and the amount of memory used by each variable type. This allows you to determine the amount of memory available for new items such as programs and the amount used by old items that you no longer need.

Displaying the MEM FREE Screen

To check the amounts of available and used memory:

1. Press **[F2]** **[MEM]** to display the **MEMORY** menu.



```
MEMORY
CHECK RAM...
AVAILABLE...
USED RAM....
```

2. Press **1** or **[F1]** to select **CHECK RAM...**



```
MEM FREE 6667
BCN      38
SCL      40
Y-DARS   554
PAGE     84
```

The amount of available memory and the number of bytes used by each variable type are shown on the right.

3. To leave the **CHECK RAM** display:
 - Press **[F2]** **[EXIT]** to go to the Home screen.
 - Press **[F2]** **[MEM]** to return to the **MEMORY** menu.

Deleting Items from Memory

You can delete the contents of any variable (real number, list, or Y= function) or program from the memory to increase available memory.

Deleting an Item

To delete an item:

1. Press **[2nd]** **[MEM]** to display the **MEMORY** menu.
2. Press 2 to select **DELETE...**. A screen showing all variables currently in use and the amount of memory used by each is displayed.



PRG1	1.4
PRG2	1.4
STOVAR5	1.4
L1	1.4
T1	1.7
EQ1+	1.4
B	1.4
C	1.4

The file names are listed in the following order:

- Program names
- List names
- Y= equation names
- Numeric variable names

3. Use **[←]** and **[→]** to position the cursor (indicated by **■** in the left column) next to the item you want to delete, and press **[DEL]**. The item is deleted immediately.

You can continue to delete individual items from this screen. To leave the **DELETE** display:

- Press **[2nd]** **[HOME]** to go to the Home screen.
- Press **[2nd]** **[MEM]** to return to the **MEMORY** menu.

Note: Some system variables—**ANS** and statistical variables such as **REGEQ**, for example—cannot be deleted. These system variables are not shown on the **DELETE** display.

Resetting the TI-80

Resetting the TI-80 restores memory to the factory settings, including deleting the contents of all variables and programs and resetting all system variables to the original settings. Because you can increase available memory by deleting individual items, you should rarely need to reset the TI-80.

Resetting

To reset the TI-80:

1. Press **[2nd]** **[MC]** to display the **MEMORY** menu.
2. Press **3** to select **RESET**.



3. Make the appropriate menu selection.
 - To go to the Home screen without resetting the memory, select **NO**.
 - To reset the memory, select **RESET**. The Home screen is displayed with the message **MEM CLEARED**.

Notes: If the screen is blank after **RESET**, adjust the display contrast. Press **[2nd]** and then press and hold **[<]** (to make the display darker) or **[2nd]** **[>]** (to make the display lighter). You can press **[2nd]** **[F8]** to clear the message on the display.

Appendix A: Tables and Reference Information

This appendix provides a list of all TI-80 functions for use in expressions and instructions that you can use on the Home screen and in programs. It also includes other reference information that can help you.

Appendix Contents

Table of TI-80 Functions and Instructions	A-1
Menu Map	A-20
TI-80 Variables	A-26

Table of TI-80 Functions and Instructions

A function (F) returns a value or a list and can be used in expressions; an instruction (I) initiates an action. Some, but not all, have arguments. † Indicates that the instruction is only available for copying from the program editor.

a.b/c	Sets the display format for fraction results to a.b/c (mixed fractions) mode (F)	$\dagger \left[\frac{\square}{\square} \right]$ (a.b/c)	I-11
valueb/c	Returns value as a mixed fraction (F)	$\left[\frac{\square}{\square} \right]$ (a.b/c)	I-9
ABS value	Returns the absolute value of value (F)	$\left[\frac{\square}{\square} \right]$ (ABS)	2-6
ABS list	Returns a list of absolute values for each element in list (F)	$\left[\frac{\square}{\square} \right]$ (ABS)	2-6
Addition value+value	Returns value 1 plus value 2 (F)	$\left[\square \right]$	2-4
Addition value+list	Returns a list in which value is added to each list element (F)	$\left[\square \right]$	2-4
Addition list+list	Returns a list of list elements plus list elements (F)	$\left[\square \right]$	2-4
AUTOSIMP	Turns on automatic simplification mode for fractions (I)	$\dagger \left[\frac{\square}{\square} \right]$ (AUTOSIMP)	I-11
b/c	Sets the display format for fraction results to b/c (simple fractions) mode (F)	$\dagger \left[\frac{\square}{\square} \right]$ (b/c)	I-11
valueb/c	Returns value as a simple fraction (F)	$\left[\frac{\square}{\square} \right]$ (b/c)	I-9
CLRDRAW	Deletes all drawn elements from a graph or drawing (I)	$\left[\frac{\square}{\square} \right]$ [DRAW] DRAW (CLRDRAW)	I-12
CLRHOME	Clears the Home screen (I)	$\dagger \left[\frac{\square}{\square} \right]$ HD (CLRHOME)	10-11
CLRLIST <i>listnameA,listnameB</i>	Deletes listnameA, listnameB, (I)	$\left[\frac{\square}{\square} \right]$ EDIT (CLRLIST)	9-11















CONNECTED	Sets connected line graphing format. (F)	$\frac{1}{\text{MODE}}$ (CONNECTED)	1-11
COS value	Returns the cosine of value. (F)	$\frac{1}{\text{COS}}$	2-4
COS list	Returns a list of the cosine for each list element. (F)	$\frac{1}{\text{COS}}$	2-4
COS^{-1} value	Returns the arccosine of value. (F)	$\frac{1}{\text{COS}}$ $\frac{1}{\text{COS}^{-1}}$	2-4
COS^{-1} list	Returns a list of the arccosine for each list element. (F)	$\frac{1}{\text{COS}}$ $\frac{1}{\text{COS}^{-1}}$	2-4
Cube value³	Returns the cube of value. (F)	$\frac{1}{\text{MATH}}$ $\frac{1}{\text{MATH}}$ (³)	2-8
Cube list³	Returns a list of the cube for each list element. (F)	$\frac{1}{\text{MATH}}$ $\frac{1}{\text{MATH}}$ (³)	2-8
Cube Root $\sqrt[3]{}$ value	Returns the cube root of value. (F)	$\frac{1}{\text{MATH}}$ $\frac{1}{\text{MATH}}$ ($\sqrt[3]{}$)	2-8
Cube Root $\sqrt[3]{}$ list	Returns a list of the cube root for each list element. (F)	$\frac{1}{\text{MATH}}$ $\frac{1}{\text{MATH}}$ ($\sqrt[3]{}$)	2-8
value+DEC	Returns value in decimal form. (F)	$\frac{1}{\text{MATH}}$ $\frac{1}{\text{MATH}}$ (DEC)	2-8
list+DEC	Returns list in decimal form. (F)	$\frac{1}{\text{MATH}}$ $\frac{1}{\text{MATH}}$ (DEC)	2-8
DEGREE	Sets degree mode. (F)	$\frac{1}{\text{MODE}}$ (DEGREE)	1-11
Degree Notation: value[°]	Interprets value as an angle in degrees. (F)	$\frac{1}{\text{2nd}}$ $\frac{1}{\text{ANGLE}}$ ([°])	2-14
DI1 list	Returns the length of list. (F)	$\frac{1}{\text{2nd}}$ $\frac{1}{\text{LIST}}$ OPS (DI1)	8-7
length+DI1 list+name	Creates (if necessary) or references list to length. (F)	$\frac{1}{\text{2nd}}$ $\frac{1}{\text{LIST}}$ OPS (DI1)	8-7
DISP	Displays the Home screen. (F)	$\frac{1}{\text{PPROM}}$ VO (DISP)	10-13
DISP "to it"	Displays list. (F)	$\frac{1}{\text{PPROM}}$ VO (DISP)	10-13
DISP valueA, valueB	Displays valueA, valueB. (F)	$\frac{1}{\text{PPROM}}$ VO (DISP)	10-13
DISP "to it", valueA, "to it", valueB	Displays list, valueA, list, valueB. (F)	$\frac{1}{\text{PPROM}}$ VO (DISP)	10-13

Table of TI-80 Functions and Instructions (Continued)

DISPGRAPH	Displays the current graph (F)	1 DISPGRAPH	10-13
Division: <i>valueA</i> / <i>valueB</i>	Returns <i>valueA</i> divided by <i>valueB</i> (F)		2-4
Division: <i>list</i> / <i>value</i>	Returns <i>list</i> elements divided by <i>value</i> (F)		2-4
Division: <i>value</i> / <i>list</i>	Returns <i>value</i> divided by <i>list</i> elements (F)		2-4
Division: <i>listA</i> / <i>listB</i>	Returns <i>listA</i> elements divided by <i>listB</i> elements (F)		2-4
DOT	Sets dot graphing format (F)	1 MODE (DOT)	1-11
DRAW <i>expression</i>	Draws <i>expression</i> (in X) on the current graph (F)	DRAW DRAW (DRAW)	7-6
E^{power}	Returns <i>e</i> raised to the value of <i>power</i> (F)	(<i>e</i> ^{<i>power</i>})	2-5
E^{list}	Returns a list of <i>e</i> raised to the power of each <i>list</i> element (F)	(<i>e</i> ^{<i>list</i>})	2-5
ELSE for IF-THEN-ELSE			
END	Identifies the end of a FOR, IF-THEN, or IF-THEN-ELSE structure (F)	1 CTL (END)	10-9
Equal: <i>valueA</i> = <i>valueB</i>	Returns 1 if <i>valueA</i> = <i>valueB</i> ; Returns 0 if <i>valueA</i> ≠ <i>valueB</i> (F)	(1) (0)	2-16
Equal: <i>listA</i> = <i>listB</i>	Applies the = test to each element of <i>listA</i> and <i>listB</i> and returns a list (F)	(1) (0)	2-16
Equal: <i>list</i> = <i>value</i> or <i>value</i> = <i>list</i>	Applies the = test to each element of <i>list</i> and <i>value</i> and returns a list (F)	(1) (0)	2-16
Exponent: <i>base</i> ^{<i>exponent</i>}	Returns 10 to the <i>exponent</i> (F)	(<i>base</i> ^{<i>exponent</i>})	1-7
Exponent: <i>value</i> ^{<i>exponent</i>}	Returns <i>value</i> times 10 to the <i>exponent</i> (F)	(<i>value</i> ^{<i>exponent</i>})	1-7
Exponent: <i>list</i> ^{<i>exponent</i>}	Returns <i>list</i> elements times 10 to the <i>exponent</i> (F)	(<i>list</i> ^{<i>exponent</i>})	1-7

EXPREG <i>Xlistname, Ylistname</i>	Fits <i>Xlistname</i> and <i>Ylistname</i> to the exponential model (E)	(STAT) CALC (EXPREG)	9-16
EXPREG <i>Xlistname, Ylistname, Freqlistname</i>	Fits <i>Xlistname</i> and <i>Ylistname</i> to the exponential model with frequency <i>Freqlistname</i> (E)	(STAT) CALC (EXPREG)	9-16
Fa, intol: valuel	Returns the factorial of value (0 ≤ integer ≤ 69) (F)	(MATH) PROB (F)	2-13
Fa, intol: listl	Returns a list containing the factorial for each list element (0 ≤ integer ≤ 69) (F)	(MATH) PROB (F)	2-13
FIX n	Sets fixed-decimal display mode for <i>n</i> decimal places (F)	2 (MODE) (FIX)	1-10
FLOAT	Sets floating-decimal display mode (F)	1 (MODE) (FLOAT)	1-10
FN OFF	Deactivates all Y= functions. (F)	(2ND) (Y VARS) ON/OFF (FN OFF)	4-8
FN OFF <i>func: funcOff,</i> <i>func: funcOff, (F)</i>	Deactivates <i>func: funcOff</i> . (F)	(2ND) (Y VARS) ON/OFF (FN OFF)	4-8
FN ON	Selects all Y= functions. (F)	(2ND) (Y VARS) ON/OFF (FN ON)	4-8
FN ON <i>func: funcOff,</i> <i>func: funcOff, (F)</i>	Selects <i>func: funcOff</i> . (F)	(2ND) (Y VARS) ON/OFF (FN ON)	4-8
FOR(<i>variable</i> <i>begin, end</i>) <i>n</i> <i>commands</i> END	Executes <i>n</i> <i>commands</i> through END , incrementing variable from <i>begin</i> by 1 until variable > <i>end</i> . (F)	1 (2ND) CTL (FOR)	10-9
FOR(<i>variable</i> <i>begin, end</i> , <i>inc</i> <i>incrate</i>) <i>n</i> <i>commands</i> END	Executes <i>n</i> <i>commands</i> through END , incrementing variable from <i>begin</i> by <i>incrate</i> until variable > <i>end</i> . (F)	1 (2ND) CTL (FOR)	10-9

Table of TI-80 Functions and Instructions (Continued)

FPART <i>value</i>	Returns the fractional part of <i>value</i> (F)	 NUM (FPART)	2-10
FPART <i>list</i>	Returns a list of the fractional parts for each list element (F)	 NUM (FPART)	2-10
value → FRAC	Returns <i>value</i> as fraction form, according to the current fraction display format (F)	 (FRAC)	3-10
list → FRAC	Displays <i>list</i> as fraction form, according to the current fraction display format (F)	 (FRAC)	3-10
FUNC	Sets function graphing mode (F)	 (FUNC)	3-11
GOTO <i>label</i>	Branches the program to <i>label</i> (F)	 CTL (GOTO)	10-10
Greater Than <i>valueA</i> > <i>valueB</i>	Returns 1 if <i>valueA</i> > <i>valueB</i> . Returns 0 if <i>valueA</i> ≤ <i>valueB</i> (F)	 (TEST) (>)	2-16
Greater Than <i>listA</i> > <i>listB</i>	Applies the > test to each element of <i>listA</i> and <i>listB</i> and returns a list (F)	 (TEST) (>)	2-16
Greater Than <i>listA</i> > <i>value</i> or <i>value</i> > <i>listA</i>	Applies the > test to each element of <i>listA</i> and <i>value</i> and returns a list (F)	 (TEST) (>)	2-16
Greater Than or Equal <i>valueA</i> ≥ <i>valueB</i>	Returns 1 if <i>valueA</i> ≥ <i>valueB</i> . Returns 0 if <i>valueA</i> < <i>valueB</i> (F)	 (TEST) (≥)	2-16
Greater Than or Equal <i>listA</i> ≥ <i>listB</i>	Applies the ≥ test to each element of <i>listA</i> and <i>listB</i> and returns a list (F)	 (TEST) (≥)	2-16
Greater Than or Equal <i>listA</i> ≥ <i>value</i> or <i>value</i> ≥ <i>listA</i>	Applies the ≥ test to each element of <i>listA</i> and <i>value</i> and returns a list (F)	 (TEST) (≥)	2-16
GRIDOFF	Turns the graph grid off (F)	 (GRID) (GRIDOFF)	4-11
GRIDON	Turns the graph grid on (F)	 (GRID) (GRIDON)	4-11
































HORIZONTAL :	Draws a horizontal line at value <i>F</i> (F)	 (DRAW) DRAW (HORIZONTAL)	2-7
IF <i>condition</i> <i>commandA</i> <i>commandB</i>	If <i>condition</i> = 0 (false), skips <i>commandA</i> (F)	↑  CTL (F)	2-3
IF <i>condition</i> THEN <i>commandA</i> END	Executes <i>commandA</i> from THEN to END if <i>condition</i> = 1 (true) (F)	↑  CTL (THEN)	2-3
IF <i>condition</i> THEN <i>commandA</i> ELSE <i>commandB</i> END	Executes <i>commandA</i> from THEN to ELSE if <i>condition</i> = 1 (true), from ELSE to END if <i>condition</i> = 0 (false) (F)	↑  CTL (ELSE)	10-7
INPUT	Displays the current graph with the free-moving cursor (F)	↑  MO (INPUT)	10-12
INPUT <i>variable</i>	Prompts for input to store to <i>variable</i> (F)	↑  MO (INPUT)	10-12
INPUT "or n", <i>variable</i>	Prompts using text and stores input to <i>variable</i> (F)	↑  MO (INPUT)	10-12
INT <i>value</i>	Returns the largest integer ≤ <i>value</i> (F)	 MATH (INT)	2-10
INT <i>list</i>	Returns the largest integer less element (F)	 MATH (INT)	2-10
<i>integerA</i> INT <i>integerB</i>	Divides <i>integerA</i> by <i>integerB</i> and returns a quotient (Q) and remainder (R) on the Home screen, if there are no pending operations (F)	 MATH (INT)	2-7
<i>listA</i> INT <i>listB</i>	Returns a list of quotients from <i>listA</i> and <i>listB</i> (F)	 MATH (INT)	2-7
<i>listA</i> INT <i>integer</i> or <i>integer</i> INT <i>list</i>	Returns list of quotients from <i>integer</i> and <i>list</i> (F)	 MATH (INT)	2-7
Inverse <i>value</i> ⁻¹	Returns 1 divided by <i>value</i> (F)		2-4
Inverse <i>list</i> ⁻¹	Returns 1 divided by each list element (F)		2-4

Table of TI-80 Functions and Instructions (Continued)

IPART <i>value</i>	Returns the integer part of <i>value</i> (F)	 NUM (IPART)	2-10
IPART <i>list</i>	Returns a list of the integer part for each list element (F)	 NUM (IPART)	2-10
LBL <i>label</i>	Assigns <i>label</i> to the command. (I)	 CTL (LBL)	10-10
Less Than <i>valueA-valueB</i>	Returns 1 if <i>valueA</i> < <i>valueB</i> . Returns 0 if <i>valueA</i> ≥ <i>valueB</i> (F)	 TEST (<)	2-16
Less Than <i>listA-listB</i>	Applies the < test to each element of <i>listA</i> and <i>listB</i> and returns a list (F)	 TEST (<)	2-16
Less Than, Absolute <i>value-value</i>	Applies the < test to each element of <i>list</i> and <i>value</i> and returns a list (F)	 TEST (<)	2-16
Less Than or Equal <i>valueA-valueB</i>	Returns 1 if <i>valueA</i> ≤ <i>valueB</i> . Returns 0 if <i>valueA</i> > <i>valueB</i> (F)	 TEST (≤)	2-16
Less Than or Equal <i>listA-listB</i>	Applies the ≤ test to each element of <i>listA</i> and <i>listB</i> and returns a list (F)	 TEST (≤)	2-16
Less Than or Equal <i>list-value</i> or <i>value-list</i>	Applies the ≤ test to each element of <i>list</i> and <i>value</i> and returns a list (F)	 TEST (≤)	2-16
LINE (<i>X1,Y1,X2,Y2</i>)	Draws a line from (<i>X1,Y1</i>) to (<i>X2,Y2</i>) (D)	 DRAW (LINE)	7-4
LNREG (<i>a+bX</i>) <i>Xlistname</i> , <i>Ylistname</i>	Fits <i>Xlistname</i> and <i>Ylistname</i> to the linear model (I)	 CALC (LNREG(a+bX))	9-16
LNREG (<i>aX+b</i>) <i>Xlistname</i> , <i>Ylistname</i>	Fits <i>Xlistname</i> and <i>Ylistname</i> to the linear model with frequency (I)	 CALC (LNREG(aX+b))	9-15
LNREG (<i>a+bX</i>) <i>Xlistname</i> , <i>Ylistname</i> , <i>Freqlistname</i>	Fits <i>Xlistname</i> and <i>Ylistname</i> to the linear model with frequency (I)	 CALC (LNREG(a+bX))	9-15
LN <i>value</i>	Returns the natural logarithm of <i>value</i> (F)	 (LN)	7-5
LN <i>list</i>	Returns a list of the natural logarithm for each list element (F)	 (LN)	7-5

LNREG <i>Xlistname, Ylistname</i>	Fits <i>Xlistname</i> and <i>Ylistname</i> to the logarithmic model (F)	  (LNREG)	9-16
LNREG <i>Xlistname, Ylistname, frequency</i>	Fits <i>Xlistname</i> and <i>Ylistname</i> to the logarithmic model with frequency <i>frequency</i> (F)	  (LNREG)	9-16
LOG <i>value</i>	Returns the logarithm of <i>value</i> (F)		2-5
LOG <i>list</i>	Returns a list of the logarithm for each list element (F)		2-4
MANSMP	Selects manual simplification mode for fractions (F)	 (MANSMP)	1-11
MAX (<i>valueA, valueB</i>)	Returns the larger of <i>valueA</i> and <i>valueB</i> (F)	  MATH (MAX)	3-9
MAX (<i>list</i>)	Returns the largest element in <i>list</i> (F)	  MATH (MAX)	3-9
MAX (<i>listA listB</i>)	Returns a list of the larger of each pair of elements in <i>listA</i> and <i>listB</i> (F)	  MATH (MAX)	3-9
MAX (<i>list, value</i>) or MAX (<i>value, list</i>)	Returns a list of the larger of each list element compared to <i>value</i> (F)	  MATH (MAX)	3-9
MEAN (<i>list</i>)	Returns the mean of <i>list</i> (F)	  MATH (MEAN)	3-9
MEAN (<i>list frequency</i>)	Returns the mean of <i>list</i> with frequency <i>frequency</i> (F)	  MATH (MEAN)	3-9
MEDIAN (<i>list</i>)	Returns the median of <i>list</i> (F)	  MATH (MEDIAN)	3-9
MEDIAN (<i>list frequency</i>)	Returns the median of <i>list</i> with frequency <i>frequency</i> (F)	  MATH (MEDIAN)	3-9
MIN (<i>valueA valueB</i>)	Returns the smaller of <i>valueA</i> and <i>valueB</i> (F)	  MATH (MIN)	3-9
MIN (<i>list</i>)	Returns the smallest element in <i>list</i> (F)	  MATH (MIN)	3-9

Table of TI-80 Functions and Instructions (Continued)

MIN(A, listA, listB)	Returns a list of the smaller of each pair of elements in listA and listB (F)	  MATH (MIN)	8-9
MIN(listA, value) or MIN(value, listA)	Returns a list of the smaller of each list element compared to value (F)	  MATH (MIN)	8-9
Multiplication valueA × valueB	Returns valueA times valueB (F)		2-4
Multiplication valueA list or list × value	Returns a list containing each value times each list element (F)		2-4
Multiplication listA × listB	Returns a list of list elements times list elements (F)		2-4
valueA nCr valueB	Returns the combinations of valueA (integer ≥ 0) taken valueB (integer ≥ 0) at a time (F)	 PROB (nCr)	2-11
value nCr list	Returns a list of the combinations of value (integer ≥ 0) taken each element in list (integer ≥ 0) at a time (F)	 PROB (nCr)	2-11
list nCr value	Returns a list of the combinations of each element (integer ≥ 0) in list taken value (integer ≥ 0) at a time (F)	 PROB (nCr)	2-11
listA nCr listB	Returns a list of the combinations of each element (integer ≥ 0) in listA taken each element in listB (integer ≥ 0) at a time (F)	 PROB (nCr)	2-11
NDERIV(expression, variable value)	Returns the approximate numerical derivative of expression with respect to variable at value. x is $1E-10$ (F)	 MATH (NDEPRN)	2-4
NDERIV(expression, variable value, Δx)	Returns the approximate numerical derivative of expression with respect to variable at value, with a specified Δx (F)	 MATH (NDEPRN)	2-4









Negation <i>-value</i>	Returns the negative of <i>value</i> (F)		2-6
Negation <i>-list</i>	Returns a list with each list element negated (F)		2-6
NORMAL	Set normal display mode (B)	   (NORMAL)	1-10
Not Equal <i>valueA=valueB</i>	Returns 1 if <i>valueA</i> \neq <i>valueB</i> Returns 0 if <i>valueA</i> = <i>valueB</i> (F)	   (1)101 (<i>x</i>)	2-10
Not Equal <i>listA=listB</i>	Applies the \neq test to each element of <i>listA</i> and <i>listB</i> and returns a list (F)	   (<i>x</i>)	2-10
Not Equal <i>Arithmetic or value<list</i>	Applies the \neq test to each element of <i>list</i> and <i>value</i> and returns a list (F)	   (<i>x</i>)	2-10
<i>valueA</i> nPr <i>valueB</i>	Returns a list of the permutations of <i>valueA</i> (integer ≥ 0) taken <i>valueB</i> (integer ≥ 0) at a time (F)	   PRB (<i>xPr</i>)	2-13
<i>value</i> nPr <i>list</i>	Returns a list of the permutations of <i>value</i> (integer ≥ 0) taken each element in <i>list</i> (integer ≥ 0) at a time (F)	   PRB (<i>xPr</i>)	2-13
<i>listA</i> nPr <i>value</i>	Returns a list of the permutations of each element (integer ≥ 0) in <i>listA</i> taken <i>value</i> (integer ≥ 0) at a time (F)	   PRB (<i>xPr</i>)	2-13
<i>listA</i> nPr <i>listB</i>	Returns a list of the permutations of each element (integer ≥ 0) in <i>listA</i> taken each element in <i>listB</i> (integer ≥ 0) at a time (F)	   PRB (<i>xPr</i>)	2-13
1-VAR STATS <i>Arithmetic</i>	Performs one variable analysis using <i>Arithmetic</i> and a frequency of 1 (B)	  CALC (1 VAR STATS)	9-14
1-VAR STATS <i>Arithmetic, frequency</i>	Performs one variable analysis using <i>Arithmetic</i> and frequency <i>frequency</i> (B)	  CALC (1 VAR STATS)	9-14
PARAM	Set parameter graphing mode	   (PARAM)	1-11

Table of TI-80 Functions and Instructions (Continued)

PAUSE	Suspends execution of the program until ENTER is pressed. (I)	\uparrow PAUSE CTL (PAUSE)	10-9
PI	Returns the value of π rounded to 11 digits. (F)	$\overline{\text{2ND}}$ [π]	2-6
PLOTn (type,Xlist,Ylist)	Plots stat plot n (1-3) of type (L_ or L_2) for Xlist and Ylist coordinate pairs.	\uparrow $\overline{\text{2ND}}$ [STAT PLOT] (PLOTn)	9-20
PLOTn (type,Xlist,Ylist,mark)	Plots stat plot n (1-3) of type (L_ or L_2) for Xlist and Ylist coordinate pairs with the specified type of mark. (I)	\uparrow $\overline{\text{2ND}}$ [STAT PLOT] (PLOTn)	9-20
PLOTn (type, Xlist) or PLOTn (type,Xlist,Flist)	Plots stat plot n (1-3) of type (L_ or L_2) for Xlist with frequency Flist. If Flist is omitted, frequency = 1. (I)	\uparrow $\overline{\text{2ND}}$ [STAT PLOT] (PLOTn)	9-20
PLOTSOFF	Deactivates all stat plots. (I)	$\overline{\text{2ND}}$ [STAT PLOT] (PLOTSOFF)	9-21
PLOTSOFF <i>plot1</i> <i>plot2</i>	Deactivates stat plot1, plot2, or plot3. (I)	$\overline{\text{2ND}}$ [STAT PLOT] (PLOTSOFF)	9-21
PLOTSON	Selects all stat plots. (I)	$\overline{\text{2ND}}$ [STAT PLOT] (PLOTSON)	9-21
PLOTSON <i>plot1</i> <i>plot2</i>	Selects stat plot1, plot2, or plot3. (I)	$\overline{\text{2ND}}$ [STAT PLOT] (PLOTSON)	9-21
Power <i>value</i> ^{<i>power</i>}	Returns <i>value</i> raised to <i>power</i> . (F)	\square	2-5
Power <i>list</i> ^{<i>power</i>}	Returns a list of each element raised to the value of <i>power</i> . (F)	\square	2-5
Power <i>value</i> ^{<i>list</i>}	Returns a list of <i>value</i> raised to the power of each list element. (F)	\square	2-5
Power <i>list</i> ^{<i>list2</i>}	Returns a list of each list element raised to the power of each list2 element. (F)	\square	2-5
Power of ten 10^{power}	Returns 10 raised to the value of <i>power</i> . (F)	$\overline{\text{2ND}}$ [10^x]	2-5
Power of ten 10^{list}	Returns a list of 10 raised to the power of each list element. (F)	$\overline{\text{2ND}}$ [10^x]	2-5

FROM_programname	Executes the program <i>programname</i> (0)	1 [F5] CTRL (FROM)	10-10
PROD list	Returns the product of elements in <i>list</i> (F)	[2nd] [x\times] MATH (PROD)	8-10
Po-Ra(R,θ)	Returns the rectangular coordinate <i>x</i> , given the polar coordinates <i>R</i> and <i>θ</i> (F)	[2nd] [ANG\angle] (PoRa)	2-15
Po-Ra(Rlist,θ)	Returns a list of <i>x</i> coordinates, given the <i>R</i> coordinates in <i>Rlist</i> and a single <i>θ</i> (F)	[2nd] [ANG\angle] (PoRa)	2-15
Po-Ra(R,θlist)	Returns a list of <i>x</i> coordinates, given the single <i>R</i> coordinate and the <i>θ</i> coordinates in <i>θlist</i> (F)	[2nd] [ANG\angle] (PoRa)	2-15
Po-Ra(Rlist,θlist)	Returns a list of <i>x</i> coordinates, given the <i>R</i> and <i>θ</i> coordinates in <i>Rlist</i> and <i>θlist</i> (F)	[2nd] [ANG\angle] (PoRa)	2-15
Po-Ry(R,θ)	Returns rectangular coordinate <i>y</i> , given polar coordinates <i>R</i> and <i>θ</i> (F)	[2nd] [ANG\angle] (PoRy)	2-15
Po-Ry(Rlist,θ)	Returns a list of <i>y</i> coordinates, given the <i>R</i> coordinates in <i>Rlist</i> and a single <i>θ</i> coordinate (F)	[2nd] [ANG\angle] (PoRy)	2-15
Po-Ry(R,θlist)	Returns a list of <i>y</i> coordinates, given a single <i>R</i> coordinate and the <i>θ</i> coordinates in <i>θlist</i> (F)	[2nd] [ANG\angle] (PoRy)	2-15
Po-Ry(Rlist,θlist)	Returns a list of <i>y</i> coordinates, given the <i>R</i> coordinates in <i>Rlist</i> and the <i>θ</i> coordinates in <i>θlist</i> (F)	[2nd] [ANG\angle] (PoRy)	2-15
PT-CHANGE(X,Y)	Toggles the point at (X,Y) (0)	[2nd] [DRAW] POINTS (PT-CHANGE)	7-10
PT-OFF(X,Y)	Erases the point at (X,Y) (0)	[2nd] [DRAW] POINTS (PT-OFF)	7-10
PT-ON(X,Y)	Draws the point at (X,Y) (0)	[2nd] [DRAW] POINTS (PT-ON)	7-10

Table of TI-80 Functions and Instructions (Continued)

PWRREG <i>Xlistname</i> , <i>Ylistname</i>	Fits <i>Xlistname</i> and <i>Ylistname</i> to the power model (F)	 CALC (PWRREG)	9-16
PWRREG <i>Xlistname</i> , <i>Ylistname</i> , <i>Freqlistname</i>	Fits <i>Xlistname</i> and <i>Ylistname</i> to the power model with frequency <i>freqlistname</i> (F)	 CALC (PWRREG)	9-16
QUADREG <i>Xlistname</i> , <i>Ylistname</i>	Fits <i>Xlistname</i> and <i>Ylistname</i> to the quadratic model (F)	 CALC (QUADREG)	9-16
QUADREG <i>Xlistname</i> , <i>Ylistname</i> , <i>Freqlistname</i>	Fits <i>Xlistname</i> and <i>Ylistname</i> to the quadratic model with frequency <i>freqlistname</i> (F)	 CALC (QUADREG)	9-16
RADIAN	Sets radian mode (F)	 MODE (RADIAN)	1-11
Radian Notation: <i>value</i> [°]	Interprets <i>value</i> as an angle in radians	 ANGLE (°)	2-14
RAND	Returns a random number between 0 and 1 (F)	 PRB (RAND)	3-13
RANDINT (<i>lower</i> , <i>upper</i>)	Returns a random integer between <i>lower</i> and <i>upper</i> (F)	 PRB (RANDINT)	3-13
RANDINT (<i>lower</i> , <i>list</i> , <i>upper</i>)	Returns a list of random integers between each element of <i>lower</i> and <i>upper</i> (F)	 PRB (RANDINT)	3-13
RANDINT (<i>lower</i> , <i>upper</i> , <i>list</i>)	Returns a list of random integers between <i>lower</i> and each element of <i>upper</i> (F)	 PRB (RANDINT)	3-13
RANDINT (<i>lower</i> , <i>list</i> , <i>upper</i> , <i>list</i>)	Returns a list of random integers between each element of <i>lower</i> and <i>upper</i> (F)	 PRB (RANDINT)	3-13
REMAINDER (<i>valueA</i> , <i>valueB</i>)	Returns the remainder from the division of <i>valueA</i> by <i>valueB</i>	 NUM (REMAINDER)	2-11
REMAINDER (<i>list</i> , <i>value</i> <i>list</i>)	Returns a list of remainders from the division of <i>value</i> by each element in <i>list</i>	 NUM (REMAINDER)	2-11

REMAINDER (<i>list</i> , <i>value</i>)	Returns a list of remainders from the division of each element in <i>list</i> by <i>value</i> .	 MATH NUM (REMAINDER)	2-11
REMAINDER (<i>value</i> , <i>list</i>)	Returns a list of remainders from the division of each element in <i>list</i> by the each element in <i>value</i> .	 MATH NUM (REMAINDER)	2-11
RETURN	Returns to the calling program. (F)	 PROGRAM CTL (RETURN)	10-10
<i>e</i>^{base} (<i>value</i>)	Returns <i>e</i> ^{base} of <i>value</i> . (F)	 MATH (%)	2-6
<i>e</i>^{base} (<i>list</i>)	Returns a list of <i>e</i> ^{base} for each list element. (F)	 MATH (%)	2-6
<i>i</i>^{base} (<i>value</i>)	Returns the roots of <i>value</i> . (F)	 MATH (%)	2-6
<i>i</i>^{base} (<i>list</i>)	Returns a list of list roots of <i>list</i> . (F)	 MATH (%)	2-6
ROUND (<i>value</i>)	Returns <i>value</i> rounded to 10 digits. (F)	 MATH NUM (ROUND)	2-10
ROUND (<i>value</i> , <i>digits</i> , <i>mode</i>)	Returns <i>value</i> rounded to <i>digits</i> mode(<i>mode</i> = 9). (F)	 MATH NUM (ROUND)	2-10
ROUND (<i>list</i>)	Returns list elements rounded to 10 digits. (F)	 MATH NUM (ROUND)	2-10
ROUND (<i>list</i> , <i>digits</i> , <i>mode</i>)	Returns list elements rounded to <i>digits</i> mode(<i>mode</i> = 9). (F)	 MATH NUM (ROUND)	2-10
Rt-Pt (<i>X</i> , <i>Z</i>)	Returns the polar coordinate <i>r</i> , given the rectangular coordinates <i>X</i> and <i>Z</i> . (F)	 MATH (Rt-Pt)	2-15
Rt-Pt (<i>X</i> , <i>Z</i> , <i>r</i>)	Returns a list of <i>r</i> coordinates, given the <i>X</i> coordinates in <i>X</i> and a single <i>Z</i> coordinate. (F)	 MATH (Rt-Pt)	2-15
Rt-Pt (<i>X</i> , <i>r</i> , <i>list</i>)	Returns a list of <i>r</i> coordinates, given a single <i>X</i> coordinate and the <i>Z</i> coordinates in <i>list</i> . (F)	 MATH (Rt-Pt)	2-15

Table of TI-80 Functions and Instructions (Continued)

R→Pn(Xlist,Ylist)	Returns a list of r coordinates, given the X coordinates in <i>Xlist</i> and the Y coordinates in <i>Ylist</i> (P)	 (ANGLE) (R→Pn)	2-13
R→Pn(X,Y)	Returns the polar coordinate θ , given the rectangular coordinates X and Y (P)	 (ANGLE) (R→Pn)	2-13
R→Pn(Xlist,r)	Returns a list of θ coordinates, given the X coordinates in <i>Xlist</i> and a single r coordinate (P)	 (ANGLE) (R→Pn)	2-13
R→Pn(X,rlist)	Returns a list of θ coordinates, given a single X coordinate and the r coordinates in <i>rlist</i> (P)	 (ANGLE) (R→Pn)	2-13
R→Pn(Xlist,rlist)	Returns a list of θ coordinates, given the X coordinates in <i>Xlist</i> and the r coordinates in <i>rlist</i> (P)	 (ANGLE) (R→Pn)	2-13
SCI	Set scientific display mode (D)	 (SCI)	1-10
SEQ , <i>upper case, variable, begin/end, on screen</i>	Returns a list created by evaluating expression for variable, from <i>begin</i> to <i>end</i> by <i>on screen</i> (P)	 /LIST/OPS (SEQ)	8-8
SEQUENTIAL	Set sequential graphing mode (P)	 (SEQUENTIAL)	1-11
SHADE <i>(lowercase, upper/lower)</i>	Shades the area above <i>lower/lower</i> and below <i>upper/lower</i> (D)	 (DRAW) (SHADE)	7-9
SHADE <i>(lower/lower, upper/lower, resolution)</i>	Shades the area above <i>lower/lower</i> , below <i>upper/lower</i> , and with <i>resolution</i> (1 to 9) (D)	 (DRAW) (SHADE)	7-9
SHADE <i>(lower/lower, upper/lower, resolution, Xleft)</i>	Shades the area above <i>lower/lower</i> , below <i>upper/lower</i> , to right of <i>X=Xleft</i> , and with <i>resolution</i> (1 to 9) (D)	 (DRAW) (SHADE)	7-9




































SHADE (<i>lowerflw</i> , <i>upperflw</i> , <i>resolution</i> , <i>left</i> , <i>right</i>)	Shades the area above <i>lowerflw</i> , below <i>upperflw</i> , to right of <i>left</i> , to left of <i>right</i> , and with <i>resolution</i> (1 to 9) (F)	 (DRAW) DRAW (SHADE)	7-3
SHADE <i>Y</i> <i>area 1</i> , <i>area 2</i>	Shades the area above <i>area 1</i> with vertical pattern and above <i>area 2</i> with diagonal pattern (lower left to upper right), etc. (F)	 (DRAW) DRAW (SHADE <i>Y</i>)	9-1
SHADE <i>Y</i> <i>area 1</i> , <i>area 2</i>	Shades the area below <i>area 1</i> with horizontal pattern and below <i>area 2</i> with diagonal pattern (upper left to lower right), etc. (F)	 (DRAW) DRAW (SHADE <i>Y</i>)	7-3
fraction \rightarrow SIMP	Simplifies <i>fraction</i> by its lowest common factor (F)	 (SIMP)	5-3
(fraction <i>factor</i> \rightarrow SIMP	Simplifies <i>fraction</i> by the specified factor, which must be an integer (F)	 (SIMP)	5-3
SIMUL	Sets simultaneous graphing mode (F)	 (SIMUL)	1-11
SIN <i>value</i>	Returns the sine of <i>value</i> (F)	 (SIN)	2-4
SIN <i>list</i>	Returns a list of the sine for each <i>list</i> element (F)	 (SIN)	2-4
SIN⁻¹ <i>value</i>	Returns the arcsine of <i>value</i> (F)	 (SIN ⁻¹)	2-4
SIN⁻¹ <i>list</i>	Returns a list of the arcsine for each <i>list</i> element (F)	 (SIN ⁻¹)	2-4
SORTA (<i>ascending</i>)	Sorts <i>ascending</i> elements in ascending order (F)	 (LIST) OPS (SORTA)	9-5
SORTA (<i>ascending</i> , <i>dependent1</i> , <i>dependent2</i> , ...)	Sorts the elements of <i>ascending</i> in ascending order with <i>dependent1</i> , <i>dependent2</i> , or <i>dependent list</i> (F)	 (LIST) OPS (SORTA)	9-5

Table of TI-80 Functions and Instructions (Continued)

SORTD (<i>listname</i>)	Sorts the elements of <i>listname</i> in descending order (F)	  OPS (SORTD)	8-9
SORTD (<i>listname</i> , <i>dependent1</i> , <i>dependent2</i> , ...)	Sorts the elements of <i>listname</i> in descending order with <i>dependent1</i> , <i>dependent2</i> , ... as dependent lists (F)	  OPS (SORTD)	8-9
Square <i>value</i> ²	Returns <i>value</i> multiplied by itself (F)		2-3
Square <i>list</i> ²	Returns a list of each list element squared (F)		2-3
Square Root $\sqrt{\text{value}}$	Returns the square root of <i>value</i> (F)	 	2-3
Square Root $\sqrt{\text{list}}$	Returns a list of the square roots of each list element (F)	 	2-3
STOP	Stops program execution and returns to the Home screen (F)	   CHL (STOP)	10-10
Store <i>value</i> → <i>variable</i>	Stores <i>value</i> to <i>variable</i> (F)		1-13
Store <i>list</i> → <i>listname</i>	Stores <i>list</i> to <i>listname</i> (F)		1-13
Store "expression"→To or "expression"→List or "expression"→Int	Stores <i>expression</i> to To, List or Int function (F)		1-13
Subtraction <i>valueA</i> - <i>valueB</i>	Subtracts <i>valueB</i> from <i>valueA</i> (F)		2-4
Subtraction <i>value</i> - <i>list</i>	Subtracts list elements from <i>value</i> and returns a list (F)		2-4
Subtraction <i>list</i> - <i>value</i>	Subtracts <i>value</i> from list elements and returns a list (F)		2-4
Subtraction <i>listA</i> - <i>listB</i>	Subtracts each listB element from each listA element and returns a list (F)		2-4
SUM <i>list</i>	Returns the sum of elements in <i>list</i> (F)	  MATH (SUM)	8-10
TAN <i>value</i>	Returns the tangent of <i>value</i> (F)		2-4

TAN list	Returns a list of the tangent for each list element (F)	[TAN]	2-4
TAN⁻¹ value	Returns the arctangent of value (F)	[2nd] [TAN⁻¹]	2-4
TAN⁻¹ list	Returns a list of the arctangent for each list element (F)	[2nd] [TAN⁻¹]	2-4
THEN			
See IF:THEN			
TRACE	Displays a graph and enters Trace mode (F)	[F5] [TRACE]	4-13
2-VAR STATS <i>Xlistname, Ylistname</i>	Performs two-variable analysis using Xlistname and Ylistname (F)	[STAT] CALC (2-VAR STATS)	9-15
2-VAR STATS <i>Xlistname, Ylistname, freqlistname</i>	Performs two-variable analysis using Xlistname and Ylistname with frequency freqlistname (F)	[STAT] CALC (2-VAR STATS)	9-15
VERTICAL X	Draws a vertical line at value X (F)	[2nd] [DRAW] DRAW (VERTICAL)	7-5
ZBOX	Displays a graph to allow the user to define new viewing window (F)	[F2] [ZOOM] (ZBOX)	4-15
ZDECIMAL	Displays a graph in new viewing window (F)	[F2] [ZOOM] (ZDECIMAL)	4-17
ZOOM IN	Displays a graph in new viewing window (F)	[F2] [ZOOM] (ZOOM IN)	4-16
ZOOM OUT	Displays a graph in new viewing window (F)	[F2] [ZOOM] (ZOOM OUT)	4-16
ZSQUARE	Displays a graph in new viewing window (F)	[F2] [ZOOM] (ZSQUARE)	4-17
ZSTANDARD	Displays a graph in new viewing window (F)	[F2] [ZOOM] (ZSTANDARD)	4-17
ZTRIG	Displays a graph in new viewing window (F)	[F2] [ZOOM] (ZTRIG)	4-17

TI-80 Menu Map

Menus begin in the upper left of the keyboard. Default values are shown.

Y=

(FUNC mode)

Y1=

Y2=

Y3=

Y4=

(PARAM mode)

X1=

Y1=

X2=

Y2=

X3=

Y3=

WINDOW

(FUNC mode)

WINDOW

XMIN=-10

XMAX=10

XSCL=1

YMIN=-10

YMAX=10

YSCL=1

(PARAM mode)

WINDOW

XMIN=0

XMAX=2π

XSTEP=π/24

YMIN=-10

YMAX=10

YSCL=1

YMIN=-10

YMAX=10

YSCL=1

TABLE (TblSet)

TABLE SETUP

TBLN=0

ΔTBL=1

MODE

MODE

1:2D0X

2:2D0X IN

3:2D0X OUT

4:2DECIMAL

5:2SQUARE

6:2STANDARD

7:2TRNG

MODE

NORMAL SCI

FIXED 0123456789

RADIAN DEGREE

a-b/c b/c

AUTOSIMP MANSIMP

FUNC PARAM

CONNECTED DOT

SEQUENTIAL SIMUL

MODE (in program editor)

MODE

1: NORMAL

2: SCI

3: FLOAT

4: FIX

5: RADIAN

6: DEGREE

7: a-b/c

8: b/c

9: AUTOSIMP

0: MANSIMP

A: FUNC

B: PARAM

C: CONNECTED

D: DOT

E: SEQUENTIAL

F: SIMUL

[F5] [Stat Plot]

STAT PLOTS

1: PLOT1

OFF L1 L1 L2 =

2: PLOT2

OFF L1 L1 L2 =

3: PLOT3

OFF L1 L1 L2 =

4: PLOTSOFF

5: PLOTSON

[F5] [Stat Plot] (via program editor)

PLOTS

TYPE

MARK

1: PLOT1

1: L1

1: *

2: PLOT2

2: L2

2: +

3: PLOT3

3: M

3: +

4: PLOTSOFF

4: A

5: PLOTSON

Screen for 1- or 2-plot

(1-variable plots)

PLOTs

ON OFF

TYPE: L1 L2 M A

XL: L1 L2 L3 L4 L5 L6

F: L1 L2 L3 L4 L5 L6

Screen for L1 or L2 plot

(2-variable plots)

PLOTs

ON OFF

TYPE: L1 L2 M A

XL: L1 L2 L3 L4 L5 L6

YL: L1 L2 L3 L4 L5 L6

MARK: * +

[F2] [STAT]

EDIT

1: EDIT

2: SORTA

3: SORTQ

4: C/RLIST

CALC

1: 1 VAR STATS

2: 2 VAR STATS

3: LINREG(ax+b)

4: QUADREG

5: LINREG(a+bX)

6: LNREG

7: EXPREG

8: PWRREG

TI-80 Menu Map (Continued)

2ND [1/x]

OPS	MATH
1: SORTA(1: MIN(
2: SORTC(2: MAX(
3: DIM	3: MEAN(
4: SDC(4: MEDIAN(
	5: SUM
	6: PROD

2ND [2/x]

MATH	SUM	PRB
1: INT(1: ROUND(1: RAND
2: DEC	2: IPART	2: nPr
3: $\frac{1}{x}$	3: FPART	3: nCr
4: \sqrt{x}	4: INT	4: !
5: $\sqrt[n]{x}$	5: MIN(5: RANDINT(
6: NOERF(6: MAX(
	7: REMAINDER(

2ND [3/x]

FRACTION
1: FIMP
2: FDEC
3: FFLBFC
4: FFRAC
5: FDEC

2ND [4/x]

TEST
1: =
2: \neq
3: $>$
4: \geq
5: $<$
6: \leq

2ND [5/x]

ANGLE
1: $^{\circ}$
2: $^{\circ}$
3: DegPr(
4: DegPr(
5: DegRn(
6: DegRn(

PROG

EXEC	EDIT	NEW
1: name	1: name	1: CREATE NEW
2: name	2: name	
3: name	3: name	

PROG (in program editor)

CTL	I/O	EXEC
1: IF	1: INPUT	1: name
2: THEN	2: DISP	2: name
3: ELSE	3: DISPGRAPH	3: name
4: FORC	4: CLRHOME	-
5: END		
6: PAUSE		
7: LBL		
8: GOTO		
9: PROG		
0: RETURN		
A: STOP		

PRG [DRAW]

DRAW	POINTS
1: CLRDRAW	1: PT ON
2: LINE	2: PT OFF
3: HORIZONTAL	3: PT CHANGE
4: VERTICAL	
5: DRAW	
6: SHADE Y>	
7: SHADE Y<	
8: SHADE	
9: GRIDON	
0: GRIDOFF	

TI-80 Menu Map (Continued)

Vars

- Vars
- 1: WINDOW
- 2: STATISTICS
- 3: TABLE
- 4: SIMPFACTOR

WINDOW

- X/Y
- 1: XMIN
- 2: XMAX
- 3: XSC1
- 4: YMIN
- 5: YMAX
- 6: YSC1
- 7: XE
- 8: YE
- 9: XFACT
- 0: YFACT

TABLE

- TABLE
- 1: TDMIN
- 2: TDBL

SIMPFACTOR

- SIMPFACTOR
- 1: FACTOR

STATISTICS

- X/Y
- 1: E
- 2: E
- 3: Sx
- 4: sx
- 5: y
- 6: Sy
- 7: xy
- 8: H1N2
- 9: HAX3
- 0: H1N2
- A: HAXT
- 1: EX
- 2: EX²
- 3: EY
- 4: EY²
- 5: EXY
- 6: E
- 7: a
- 8: b
- 9: c
- 0: P
- 1: Q1
- 2: MED
- 3: Q3
- 4: RESED

Y-vars

- Y
- 1: Y1
- 2: Y2
- 3: Y3
- 4: Y4
- 5: Y5
- 6: Y6
- 7: Y7
- 8: Y8
- 9: Y9
- 0: Y10
- 1: F1N1
- 2: F1N2
- 3: F1N3
- 4: F1N4
- 5: F1N5
- 6: F1N6
- 7: F1N7
- 8: F1N8
- 9: F1N9
- 0: F1N10
- 1: F1N11
- 2: F1N12
- 3: F1N13
- 4: F1N14
- 5: F1N15
- 6: F1N16
- 7: F1N17
- 8: F1N18
- 9: F1N19
- 0: F1N20
- 1: F1N21
- 2: F1N22
- 3: F1N23
- 4: F1N24
- 5: F1N25
- 6: F1N26
- 7: F1N27
- 8: F1N28
- 9: F1N29
- 0: F1N30
- 1: F1N31
- 2: F1N32
- 3: F1N33
- 4: F1N34
- 5: F1N35
- 6: F1N36
- 7: F1N37
- 8: F1N38
- 9: F1N39
- 0: F1N40
- 1: F1N41
- 2: F1N42
- 3: F1N43
- 4: F1N44
- 5: F1N45
- 6: F1N46
- 7: F1N47
- 8: F1N48
- 9: F1N49
- 0: F1N50
- 1: F1N51
- 2: F1N52
- 3: F1N53
- 4: F1N54
- 5: F1N55
- 6: F1N56
- 7: F1N57
- 8: F1N58
- 9: F1N59
- 0: F1N60
- 1: F1N61
- 2: F1N62
- 3: F1N63
- 4: F1N64
- 5: F1N65
- 6: F1N66
- 7: F1N67
- 8: F1N68
- 9: F1N69
- 0: F1N70
- 1: F1N71
- 2: F1N72
- 3: F1N73
- 4: F1N74
- 5: F1N75
- 6: F1N76
- 7: F1N77
- 8: F1N78
- 9: F1N79
- 0: F1N80
- 1: F1N81
- 2: F1N82
- 3: F1N83
- 4: F1N84
- 5: F1N85
- 6: F1N86
- 7: F1N87
- 8: F1N88
- 9: F1N89
- 0: F1N90
- 1: F1N91
- 2: F1N92
- 3: F1N93
- 4: F1N94
- 5: F1N95
- 6: F1N96
- 7: F1N97
- 8: F1N98
- 9: F1N99
- 0: F1N100

MEM

MEMORY

- 1. CHECK RAM...
- 2. DELETE...
- 3. RESET...

MEM (CHECK RAM...)

MEM FREE 7814
REAL 14
LIST 0
Y VARS 80
PRGM 14

MEM (DELETE...)

DELETE:
program memory
name memory
name memory

MEM (RESET...)

1: NO
2: RESET

RESETTING MEMORY
ERASES ALL DATA
AND PROGRAMS.

names include defined
programs, lists, Y=
equations, and user
variables, in that order.)


Ti-80 Variables

The variables listed below are used by the Ti-80 in various ways. Some have restrictions on their use.

User Variables

The variables **A**, **Z**, and **θ** can hold only numbers—either decimals or fractions. You may store to these variables. The Ti-80 can update **X**, **Y**, and **T** during graphing; therefore, you may wish to reserve these variables for graphing activities.

The variables **L1** to **L6** are defined as lists. You cannot store another type of data to them.

You can store any string of characters, functions, instructions, or variable names to the functions **Y₀** (in **FUNC** mode) and **X₀** and **Y₀** (in **PARAM** mode) by using either  or the **Y₀** editor. The validity of the string is determined when the function is evaluated.

System Variables

The values of the Window variables—**XMIN**, **XMAX**, **XSCL**, **ΔX**, **TSTEP**, etc.—must be real numbers. You may store to them. Since the Ti-80 can update some of them, as the result of a **Zoom** instruction, for example, you may wish to reserve these variables for graphing activities.

The statistical result variables—**n**, **Σ**, **MIN**, **LX**, **σ**, **r**, **REGEQ**, **X1**, **Y1**, **Q1**, **MED**, **Q3**, etc.—are reserved for use by the Ti-80. You cannot store to them.

Appendix B: Service and Warranty Information

This appendix provides supplementary information that may be helpful as you use the TI-80. It includes procedures that may help you correct problems with the calculator, and it describes the service and warranty provided by Texas Instruments.

Appendix	Battery Information . . .	B-2
Contents	Accuracy Information . . .	B-8
	In Case of Difficulty . . .	B-10
	Error Conditions	B-11
	Two-Year Limited Warranty . .	B-14

Battery Information

The TI-80 uses two CR2032 lithium 3-volt batteries.

When to Replace the Batteries

As you use the TI-80, the battery voltage will gradually drop, and the display will dim. You can adjust the contrast to darken the display when this happens. If the display is dim and adjusting the contrast to level 9 does not make it dark enough, you should replace the batteries. Refer to pages B-3 to B-7 for instructions on how to change the batteries.

Battery Precautions

Follow these safety guidelines concerning batteries.

- Do not mix new and used batteries.
- Do not run different types of battery.
- Follow polarity diagrams carefully.
- Do not replace batteries with rechargeable batteries.
- Do not place non-rechargeable batteries in a battery charger.
- Properly dispose of used batteries immediately. Do not leave them within the reach of small children.
- Do not incinerate used batteries.

Retaining Stored Data

Caution: The TI-80 retains stored data when you are changing batteries only if you

- Do not remove both batteries at the same time. (At least one battery must be installed at all times in order to retain memory.)
- Turn the unit off and do not turn it back on until you have changed the batteries.
- Do not allow the batteries to run down completely before changing them.

Follow the steps on pages B-3 to B-7 when changing batteries.

**Changing the
Batteries
(Continued)**

To change the batteries, first:

- a. Turn the calculator off.
- b. Replace the plastic slide cover over the keys.
- c. Turn the calculator so that the back is facing you.



Placing your thumb on the ridged area of the plastic battery compartment cover, push down slightly and slide the cover about 1/4-inch to the right. You can then lift the cover off.



Push the end switch up to free the metal battery cover over the lower battery.

Changing the Batteries (Continued)

3.



Slide the metal battery cover away from the battery. The battery pops up.

4.



Remove the old battery. Insert a new battery, positive side (+) up.

5.



Hold the new battery in place and slide the metal battery cover back into position over the battery.

Changing the Batteries (Continued)

6.



Push the red switch all the way down to free the metal battery cover over the upper battery.

7.



Slide the metal battery cover to the right.

8.



Remove the old battery. Insert a new battery, positive side (+) up.

Battery Information (Continued)

Changing the Batteries (Continued)

9.



Hold the new battery in place and slide the metal battery cover back into position over the battery.

10.



Push the red switch to its center position to lock the metal covers and batteries into place.




Note: The calculator will not turn on unless the red switch is in the center position.

Changing the Batteries (Continued)

11.



Replace the plastic battery compartment cover. Turn the calculator on and adjust the display contrast.

To adjust the display contrast, press and release the  key. To increase the contrast (darken the screen), press and hold . To decrease the contrast (lighten the screen), press and hold .

Accuracy Information

To maximise accuracy, the TI-89 carries more digits internally than it displays.

Computational Accuracy

Values in memory are stored using up to 13 digits with a two-digit exponent.

- You can store values in the Window variables using up to 10 digits (13 digits for **XSCL**, **YSCL**, and **TSTEP**).
- When a value is displayed, the displayed value is rounded as specified by the **MODE** setting (Chapter 7), with a maximum of 10 digits and a two-digit exponent.
- **REGIO** displays up to 13 digits.

Graphing Accuracy

XMIN is the centre of the left-hand panel. **XMAX** is the centre of the next to the right-hand panel. (The right-hand panel is reserved for the busy indicator.) **ΔX** is the distance between the centres of two adjacent panels.

- ΔX is calculated as $(XMAX - XMIN) \div 40$.
- If ΔX is entered from the Home screen or a program, then **XMAX** is calculated as $XMIN + \Delta X \cdot 40$.

YMIN is the centre of the next to the bottom panel. **YMAX** is the centre of the top panel. **ΔY** is the distance between the centres of two adjacent panels.

- ΔY is calculated as $(YMAX - YMIN) \div 40$.
- If ΔY is entered from the Home screen or a program, then **YMAX** is calculated as $YMIN + \Delta Y \cdot 40$.

Cursor coordinates are displayed as six characters, which may include a negative sign, decimal point, and exponent.

Function Limits

Below is a table of functions and the range of input values for each.

Function	Input Values
$\sin x$, $\cos x$, $\tan x$	$0 < x < 10^{100}$ (degree)
$\sin^{-1} x$, $\cos^{-1} x$	$-1 \leq x \leq 1$
$\ln x$, $\log x$	$10^{-100} < x < 10^{100}$
x^y	$-10^{100} < x \leq 2.3025850929943$
10^x	$-10^{100} < x < 100$
x^x	$0 \leq x < 10^{100}$
x^y	$0 \leq x \leq 69$, where y is an integer

Function Results

Below is a table of functions and the range of the result for each.

Function	Range of Result
$\sin^{-1} x$, $\tan^{-1} x$	-90° to 90° or $-\pi/2$ to $\pi/2$ (radians)
$\cos^{-1} x$	0° to 180° or 0 to π (radians)

In Case of Difficulty

If you have difficulty operating the calculator, the following suggestions may help you to correct the problem.

Handling a Difficulty

Follow these procedures if you have difficulties.

- 1 If you cannot see anything on the display, perhaps the display contrast needs adjusting.

Press and release the **[2nd]** key. To increase the contrast (darken the screen), press and hold **[+]**. To decrease the contrast (lighten the screen), press and hold **[-]**.

You will find additional information on display contrast on page B-3.

2 If after adjusting the display contrast, the calculator does not appear to be working at all, ensure the batteries are installed properly and that they are fresh. Refer to "Batteries Information" beginning on page B-2 for more details.

Note: Make sure the red switch in the battery compartment is in the center position.

- 3 If an error occurs, follow the procedure on page B-22. Refer to the more detailed explanations about specific errors beginning on page B-11, if necessary.
- 4 If the cursor is a checked pattern, memory is full. Press **[2nd]** **[FNC]** **DELETE**... and delete some items from memory. See Chapter 12 for additional information about memory management.
- 5 If the dotted-line busy indicator is displayed, a graph or program is paused, and the TI-89 is waiting for input. Press **[2nd]** **[F12]** to continue or **[2nd]** **[F6]** to break.

Error Conditions

When the TI-80 detects an error, it displays **ERR** message and the error menu. The general procedure for correcting errors is described on page 1-22. The error messages, their possible causes, and suggestions for correction are shown below.

ARGUMENT	A function or instruction does not have the correct number of arguments. See Appendix A and the appropriate chapter.
BREAK	You have pressed the 2ND key to break execution of a program, halt a Draw instruction, or stop evaluation of an expression.
DATA TYPE	<p>You have entered a value or variable of the wrong data type.</p> <ul style="list-style-type: none">• A function (including implied multiplication) or an instruction has an argument of an invalid data type, for example, a list where a real number is required. See Appendix A and the appropriate chapter.• You are attempting to store to an incorrect data type, for example, a list to a real variable.• In function graphing or parametric graphing, you have generated a list result rather than a single value, for example, attempting to graph $Y1=(1,2,3)-X$.
DIM MISMATCH	You are attempting to perform an operation that uses more than one list, but the dimensions do not match.
DOMAIN	<p>Typically, this occurs when the value of an argument does not fall within a specified range.</p> <ul style="list-style-type: none">• You are attempting to divide by zero.• You are attempting a logarithmic or power regression with a $-X$ or an exponential or power regression with a $-Y$.• A zero value for c for NDORM will result in this error. <p>This error does not occur during graphing because the TI-80 allows for undefined values on a graph.</p>

Error Conditions (Continued)

INCREMENT	<ul style="list-style-type: none">• The increment in SEQ is 0 or has the wrong sign. This error does not occur during graphing. The TI-80 allows for undefined values on a graph.• The increment in FOR is 0 or has the wrong sign.
INVALID	You are attempting to reference a variable or use a function in a place where it is not valid. For example, TBLMIN references Y , XMIN , ΔX , or TBLMIN .
INVALID DIM	<ul style="list-style-type: none">• The dimension of the argument is not appropriate for the operation.• List element dimensions must be integers between 1 and 99, for example, LN(100) will cause an error.
LABEL	The label in the GOTO instruction is not defined with a LBL instruction in the program.
MEMORY	<ul style="list-style-type: none">• There is insufficient memory in which to perform the desired command. You must delete item(s) from memory (Chapter 12) before executing this command.• Using an IF/THEN or FOR with a GOTO that branches out of the loop can also cause this error because the END statement that terminates the loop is never reached.
MODE	You are attempting a ▶SMP in AUTOSMP mode.
NEST LEVEL	This error occurs when any nested combination of function evaluation, NDERIV , or SEQ exceeds 5 levels.
OVERFLOW	You are attempting to enter, or you have calculated, a number that is beyond the range of the calculator. This error does not occur during graphing. The TI-80 allows for undefined values on a graph.

STAT	<ul style="list-style-type: none"> You are attempting a linear regression with a vertical line. Statistical analyses must have at least two data points. QUADREG must have at least three data points. The list of F (frequency) elements must be ≥ 0, and at least one F value must be ≥ 0. The frequency list, when used for "sorting" statistics (median, Q1, Q3, or boxplot), must be an integer ≥ 0 and ≤ 99. (XMAX-XMIN):TSTEP, must be $\leq .31$ for a histogram.
STAT PLOT	You are trying to display a graph when there is a statistical plot turned on that uses an undelined list.
SYNTAX	The command contains a syntax error. Look for misplaced functions, arguments, parentheses, or commas. See Appendix A and the appropriate chapter.
UNDEFINED	You are attempting to reference a variable that is not currently defined. For example, a statistical variable, which has no current value because a list has been edited, has been referenced.
WINDOW RANGE	<p>There is a problem with the Window variables.</p> <ul style="list-style-type: none"> You may have defined XMAX:XMIN, YMAX:YMIN, TSTEP=0, or TMAX:TMIN and TSTEP=0 for one or more. The Window variables are too small or too large to graph correctly. This can occur if you attempt to zoom in or out so far that you are not within the numerical range of the calculator.
ZOOM	A point or a line, rather than a box, is defined in ZBOX , or a math error has resulted from a Zoom operation.

Two-Year Contractual Warranty

1. The terms and conditions set out hereunder shall not apply where you have purchased this calculator directly from Texas Instruments Ltd. in which the conditions of sale of Texas Instruments Ltd. shall apply.
2. This electronic calculator (including charger if applicable) from Texas Instruments is warranted to the original purchaser for a period of two (2) years from the original purchase date - normal use and service - against defective materials or workmanship. For those calculators designed to incorporate batteries, this warranty does not cover damage resulting from any battery leakage. Batteries delivered with calculators are for demonstration purposes only. This warranty is void if the calculator has been damaged by accident or other causes not arising out of defects in material or workmanship.

During the above two-year period, the calculator or its defective parts will be repaired, adjusted and/or replaced with a reconditioned model of equivalent quality, (RECONDITIONED) at manufacturer's option without charge to the purchaser when the calculator is returned, by way of the dealer to Texas Instruments with proof of purchase date. **UNITS RETURNED WITHOUT PROOF OF PURCHASE DATE WILL BE RETURNED AT THE CARRIAGE RATES IN EFFECT AT THE TIME OF RETURN.**

In the event of replacement with a reconditioned model, the replacement unit will continue to be covered by the warranty of the original calculator product or for a period of 90 days, whichever is longer.

THIS CONDITION 2 SHALL NOT AFFECT THE STATUTORY RIGHTS OF A CONSUMER AS DEFINED IN THE CONSUMER TRANSACTIONS (RESTRICTIONS ON STATEMENTS) ORDER 1974 (AS AMENDED).

3. Save as expressly provided in Condition 2, Texas Instruments shall be under no liability of whatsoever kind, howsoever caused whether or not due to the negligence or a willful default of Texas Instruments, or its servants or agents arising out of or in connection with this calculator provided that nothing contained in this condition 3 shall exclude or restrict:
 - (a) Any liability of Texas Instruments for death or personal injury resulting from the negligence of Texas Instruments or its servants or agents, or
 - (b) Any liability of Texas Instruments for loss or damage arising from this calculator (within the meaning of Sec. 5(42)) (As United Contract Terms Act 1977) and resulting from the negligence of Texas Instruments or its servants or agents.

A

- a** variable, 9-15 to 9-17, A-26
- adjc MODE**, 1-9, 1-11, 3-4, A-2
- Ans.beg**, 1-8, 3-9, A-2
- ABS**, 2-6, A-2
- Absolute value**, 2-6, A-2
- Accuracy**, 4-12, B-6, B-9
- Address**, 4-2-4, A-2
- ALPHA, ALPHA-LOCK**, 1-8
- Angle entry indicators ($^{\circ}$, $^{\circ}$), 2-14, A-2, A-14**
- ANGLE menu**, 2-14, 2-15
- Angle MODE**, 1-11
- ANS**, G5-6, 1-16, B-2, 10-4
- API**, 1-2
- Applications**
 - Box with lid, G5-7 to G5-13
 - Building height and city size, 9-2 to 9-7
 - Compound interest, G5-5, G5-6
 - Generating a sequence, 9-2
 - Graphing a circle, 4-2
 - Graphing inequalities, 11-14
 - Graphing the inverse of a function, 11-10 to 11-11
 - Graphing a piece-by-piece function, 11-12 to 11-13
 - Graphing a polar equation, 11-15
 - Guess the coefficients, 11-16
 - Luxury chances, 2-2
 - Newton's numerical solve routine, 11-4 to 11-5
 - Numerical integration, 11-6 to 11-7
 - Probability experiments: coins, dice, and spinners, 11-2
 - Path of a ball, 5-2
 - Rolling a die, 10-2 to 10-3
 - Roots of a function, 4-2
 - Shading a graph, 7-2
 - Unit circle and trig curves, 11-3
 - Windows variables store and recall, 11-8 to 11-9
 - Working with fractions, 2-2 to 2-3

Arctan, arcsine, arctangent. See **SIN⁻¹**, **COS⁻¹**, **TAN⁻¹**

Argument, x

A (Cont.)

- ARGUMENT error**, B-11
- Arrow keys**, 1-8
- Automatic Power Down**, 1-2
- AUTOSIMP MODE**, 1-9, 1-11, 3-4, A-2
- Axes (graphing)**, 4-9

B

- b** variable, 9-15 to 9-17, A-26
- Batteries**, 1-2, 1-3, B-2 to B-7
- b/c MODE**, 1-9, 1-11, 3-4, A-2
- b/c**, 1-9, A-2
- BOX (YANS) menu**, 1-18, 9-17
- BOX plus**, 9-19 to 9-21
- Break**, 1-7, 10-4, B-11
- BREAK error**, B-11
- Busy indicator**, 1-5, B-10

C

- c** variable, 9-17, A-26
- Calling other programs**, 10-10, 10-14
- Cancelling a menu**, G5-4, 1-18
- CHECK RAM screen**, 12-2
- Circles**, 4-2
- Clearing**, 1-8
 - display, G5-4, 1-8
 - drawing, 7-12
 - expression, 1-8
 - Home screen, 1-8
 - list, 9-2, 9-11, 9-13, A-2
 - menu, G5-4, 1-18
- Curve coordinates**, 4-12
- CLDRAW**, 4-11, 7-3, 7-12, A-2
- CLRHOME**, 10-2, 10-13, A-2
- CLRLIST**, 9-2, 9-11, 9-13, A-2
- Coefficients (regression equations)**, 9-15 to 9-17
- Combinations (probability)**, 2-13, A-10
- Commands, x**, 10-4 to 10-6
- Compare**, 2-16
- Concatenating commands**, 1-6, 1-15
- CONNECTED MODE**, 1-9, 1-11, 4-4, A-3
- Contrast setting**, G5-3, 1-3

C (Cont.)

Conversions

- decimals, 2-7, 2-8, 3-8, 9-10, 82, A-3
- fractions, 3-8, 3-10, A-6
- polar to rectangular, 2-14, 2-15, A-11
- rectangular to polar, 2-14, 2-15, A-15, A-16

Coordinates, 4-12

Correlation coefficient r , 9-15 to 9-17

COS, COS⁻¹, 2-4, A-3, B-9

Cosine, 2-4, A-3, B-9

CTL (PRGM) menu, 10-7 to 10-10

Cube, 2, 2, 2, 2-8, A-3

Cube root, $\sqrt[3]{}$, 2-7, 2-8, A-3

Cursor coordinates, 4-12, B-8

Cursor keys, 1-8

Curves, 1-5, 1-6

Curve fitting, 9-18 to 9-21

D

DATA TYPE error, B-11

DEG, 2-7, 2-8, 3-8, 9-10, B-2, A-3

Decimal display, 1-10, 2-8, A-3

Decimal window, 4-15, 4-17, A-19

DEGREE MODE, 1-9, 1-11, 2-14, 4-4, A-3

Degree notation, 2-14, A-3

Deleting

- characters, 1-8
- from memory, 12-4

STOL variable, 6-2, 6-3, 6-5, 6-6

ΔX , ΔY , 4-10, 4-17, A-26, B-5

Dependent variable, 6-4 to 6-6

Derivative. See Numerical derivative

Difficulty, in case of, B-10

DI1, 8-6, B-7, A-3

Dimension (list), 8-6, B-7, A-3

DI1 MISMATCH error, B-11

DISP, 10-3, 10-11, 10-13, A-3

DISGRAPH, 9-24, 10-11, 10-13, A-3

Display, 1-4, 1-5

- comma, C15-3, 1-3, B-2, B-10
- curves, 1-5, 1-6
- decimal, 2-8, A-3
- fraction, 3-8, 3-10, A-6

D (Cont.)

Display (Cont.)

- graph, 4-11, 4-12
- Home screen, 1-4
- table, 6-5, 6-6
- text, 10-12, 10-13, A-3, A-7

Division, 2-4, A-4

DOMAIN error, B-11

DOT MODE, 1-9, 1-11, 4-4, A-4

DRAW menu, 7, 3 to 7-11

DRAWF, 7-3, 7-6, A-4

Drawing

- function, 7-6
- lines, 7-4 to 7-5
- on a graph, 7-1 to 7-11
- points, 7-10
- stat data, 9-18 to 9-21

E

e , 2-9

e^x , 2-9, A-4, B-9

e (natural log), 2-9, A-8, B-9

Exit keys, 1-8

Editors, 1-8

- function, 4-5, 4-6, 5-3
- list, 9-9 to 9-12
- program, 10-5 to 10-7, 10-14
- variables, 9-9 to 9-12
- table, 6-3 to 6-6
- Y=, 4-5, 4-6, 5-3

Elements

- list, 9-3 to 9-5

ELSE, 10-7, 10-8, A-4

END, 10-3, 10-7 to 10-9, A-4

Entering

- expressions, 1-6
- fractions, 3-6
- functions, 1-7, 4-5 to 4-7, 5-3, 6-4, A-26
- lists, 9-3 to 9-5, 9-10 to 9-12
- negative numbers, 1-71, 2-6, A-11
- programs, 10-5 to 10-6
- variables, 9-2 to 9-24

EQS, 1-30, 1-21

EQ OVAR menu, 1-19, 9-17

Equal =, 2-16, A-4

E (Cont.)

- Equation Operating System, 1-25, 1-21
- Equations, parametric, 5-2 to 5-6
- Erasing a program, 10-4, 12-3
- Errors, 1-22, 6-5, 10-4, B-11 to B-13
- Evaluating expressions, 1-6, 3-4
- Evaluating functions, 4-7
- Executing programs, 10-3
- Exponent, n , 1-7, A-4
- Exponential regression, 9-14, 9-16, A-5
- EXPREG**, 9-14, 9-16, A-5
- Expressions, x , 1-6

F

- F (frequency), 9-19, 9-20
- Factorial!, 2-12, 2-13, A-3, B-9
- Features, QS-14
- FIX MODE**, 1-9, 1-10, A-5
- FLOAT MODE**, 1-9, 1-10, A-5
- FN OFF, FN ON**, 4-8, A-5
- FOR**, 10-9, A-5
- FPART**, 2-10, A-6
- FRACTION** menu, 1-8, 3-10
- Fractional part, 2-10, A-6
- Fractions
 - converting, 3-8 to 3-10
 - entering, 3-6
 - in expressions, 3-5
 - mixed, 3-6
 - modes, 3-4, 3-8, 3-5
 - simple, 3-6
 - simplifying, 3-8
- ←FRAC**, 3-10, A-6
- Free-moving cursor, 4-12, 5-6
- Frequencies, 9-19, 9-20
- FUNC MODE**, 1-9, 1-11, 4-4, 7-3, A-6
- Functions, x , 1-6, 1-7, 2-3, B-9
 - clearing, 4-6
 - editing, 4-6
 - entering, 4-7
 - defining, 4-3, 4-6, 5-3
 - evaluating, 4-7
 - graphing, 4-2 to 4-18
 - parametric, 5-2 to 5-6
 - selecting, 4-8, 5-4

G

- Getting Started, *See* Applications
- Glossary, x
- GOTO**, 10-7, 10-10, A-6, B-12
- Graph
 - accuracy, 4-12, B-8
 - defining, 4-3, 5-3
 - displaying, QS-12, 4-11, 5-5
 - mode, 1-9, 4-4
 - parametric, 5-1 to 5-6
- Greater than, $>$, 2-16, A-6
- Greater than or equal, \geq , 2-16, A-6
- Greatest integer, 2-10, A-7
- GRID OFF GRID ON**, 4-11, 7-6, A-6
- Gridwork, using, 4-8 to 4-9

H

- HISTOGRAM**, 9-19
- Home screen, x , 1-4
- HORIZONTAL**, 7-3, 7-5, A-7
- Horizontal line, 7-3, A-7

I

- IF**, 10-7, 10-8, A-7
- Implied multiplication, 1-21
- INCREMENT** error, B-12
- Independent variable, 4-5, 6-1, 6-3, 6-6
- INPUT**, 10-2, 10-11, A-7
- Input to programs, 10-11 to 10-13
- IO** menu, 10-11 to 10-13
- Inserting, 1-8
- Instructions, x , 1-6, 1-7
- INT**, 2-10, A-7
- INT** \leftarrow , 2-7, A-7
- Integer part, 2-10, A-8
- Interrupt, 1-7, 10-4, B-11
- INVALID** error, B-12
- INVALID DIM** error, B-12
- Inverse, $^{-1}$, 2-4, A-7
 - log, 2-5
 - trig, 2-4
- IPART**, 2-10, A-8

K

keyboard, C3-2

L

La (list), B-2 to B-5, A-26

LABEL error, B-12

Labels (programs), 10-10

Last Answer, 1-16, 10-4

Last Entry, 1-14, 1-15, 10-4

LBL, 10-7, 10-10, A-8, B-12

Less than, <, 2-16, A-8

Less than or equal, ≤, 2-16, A-8

LINE1, 7-3, 7-4, A-8

List data, 9-18, 9-20 to 9-21

Linear regression, 9-15, 9-16, A-8

LNREQ, 9-14 to 9-16, A-8

LIST MATH menu, 8-8, 8-10

LIST OPS menu, 8-6 to 8-8

Lists, A, 8-2 to 8-10

arguments, 2-3, 8-5

copying, 8-1

deleting, 9-11, 9-13

dimension, 8-6, 8-7, A-4

displaying, 8-4

editing, 9-10, 9-11

elements, 9-10 to 9-12

entering, 8-3 to 8-5, 9-10 to 9-12

in expressions, 8-3

graphing, 8-4

resulting values, 8-4

saving, 8-3

sorting values, 8-4

variables, 8-2 to 8-5, A-26

viewing, 8-4

LN, 2-5, A-8, B-9

LNREQ, 9-14, 9-16, A-8

LOG, 2-5, A-8, B-9

Logarithm, 2-5, A-8

Logarithmic regression, 9-16, A-8

M

MAKESMP MODE, 1-9, 1-11, 3-5, A-9

MARK (STAT), 9-20 to 9-21

MATH menu, 2-7 to 2-13

MAX1, 2-10, 2-11, 8-9, A-9

Maximum, 2-10, 2-11, 8-9, 9-17,

9-19, 9-21

M (Cont.)

MAX1, **MAX2**, 9-17, 9-19, 9-21

MEAN1, 8-9, A-9

MEO, 9-17, 9-19, 9-21, A-26

MEDIAN1, 8-9, A-9

Median point, 9-17

MEMORY error, B-12

MEMORY menu, 12-2 to 12-4

MEMORY screens, 12-2, 12-3, 12-4

Memory management, 12-2 to 12-4

Menu map, A-20 to A-25

Menus, > C3-8, 1-17 to 1-19

ANGLE, 2-14, 2-15

BOX (VARS), 1-19, 9-17

CRW, 1-11 to 1-9

EO (VARS), 1-19, 9-17

EO (FROM), 10-12 to 10-13

LIST MATH, 8-8, 8-10

LIST OPS, 8-6 to 8-8

MATH MATH, 2-7 to 2-9

MEMORY, 12-2 to 12-4

NUM (MATH), 2-10, 2-11

POINTS (DRAW), 7-10, 7-11

PRM (MATH), 2-12, 2-13

FROM EXEC, 10-9, 10-10, 10-14

FROM EDIT, 10-6

FROM NEW, 10-5

I (VARS), 1-19, 9-17

STAT CALC, 9-14 to 9-17

STAT EDIT, 9-9, 9-13

STAT MARK, 9-18, 9-20, 9-21

STAT PLOTS, 9-18 to 9-20

STAT TYPE, 9-18 to 9-21

TEST, 2-16

VARS, 1-19, 4-10

XY (VARS), 1-19, 9-17

Y-VARS, 1-19

Zoom, 4-15 to 4-17

MIN1, 2-10, 2-11, 8-9, A-9, A-10

Minimum, 2-10, 2-11, 8-9, 9-17,

9-17, 9-19, 9-21

MIN1, **MIN2**, 9-17, 9-19, 9-21

Modes, 1-9 to 1-11, 3-5, 4-4, 5-3

MODE error, B-12

Models, 9-15, 9-16

Multi argument functions, 1-20

Multiple entries, 1-6, 1-15

Multiplication, ×, 1-21, 2-4, A-10

N

n (statistics), 9-17, A-26
Natural log, 2-5, A-8
nCr, 2-12, 2-13, A-10
NOERR?, 2-7, 2-9, A-10
Negative, 1-21, 2-6, A-11
NEST LEVEL error, 8-12
NORMAL MODE, 1-9, 1-10, A-11
Not equal, 2-16, A-11
nPr, 2-12, A-11
NUM (MATH) menu, 2-10, 2-11
Numerical derivative, 2-7, 2-9, A-10

O

OFF/ON, 4-5, 5, 8-2
1-VAR STATS, 9-14, 9-15, A-11
One variable statistics, 9-14,
9-15, A-11
OVERFLOW error, 8-12

P

Parenthesis, 4-13, 4-6
PARAM MODE, 1-9, 1-11, 4-4, 5-3,
A-11
Parameters, 1-19, 5-2 to 5-6
Parentheses, 1-21
PAUSE, 10-7, 10-9, 10-13, A-12
Pausing a program, 10-7, 10-9,
10-13, A-12
Permutations, 2-12, 2-13, A-11
Pi, π , 2-6, A-12
Pixel, 4-12, 8-8
PLOT?, 9-18 to 9-24, A-12
PLOT/?, PLOT/ON, 9-23, A-12
Plotting graphs, 4-11, 4-14
Plotting stat data, 9-18 to 9-21,
9-23 to 9-24
POINTS (DRAW) menu, 7-82, 7-11,
A-13
Polar to rectangular, 2-14, 2-15,
A-13
Power of ten, 10^n , 2-5, A-12, 8-9
Power regression, 9-14, 9-16, A-14
Powers, 2-5, A-12
PRG (MATH) menu, 2-12, 2-15
PRGM, 10-7, 10-10, 10-14, A-13
PRGM CTL menu, 10-7 to 10-10

P (Cont.)

PRGM EXEC menu, 10-5, 10-14
PRGM EDIT menu, 10-6
PRGM PO menu, 10-13 to 10-13
PRGM NEW menu, 10-2, 10-5
Probability, 2-2, 2-12, 2-13, A-10,
A-11
PRQ, 3-9, 8-10, A-13
Product of a sequence, 8-10
Program editor, 10-6, 10-7, 10-11
Programs, 10-2 to 10-14
 constants, 10-5
 creating, 10-4
 executing programs, 10-5
 saving, 10-4
PrRn, PrRy, 2-14, 2-15, A-13
PT-CHANGE? PT-OFF, PT-ON, 7-10,
7-11, A-13
PWRREG, 9-14, 9-16, A-14

Q

Q1, Q3, 9-17, 9-19, 9-21, A-26
Quadrat, 8-10, 9-16, 9-18
QUADREQ, 9-14, 9-16, A-14
Quartile, 9-17, 9-19
QuickZoom, 4-13, 5-6

R

$^{\circ}$ (radian notation), 2-14, A-14
r (statistics), 9-15 to 9-17, A-26
r variable, A-26
RADIAN, 1-9, 1-11, 2-14, 4-4, A-14
RAND, 2-12, A-14
RANDINT?, 2-12, 2-13, A-14
Random numbers, 2-12, 2-13, A-14
Real numbers, x
Rectangular coordinates, 4-12, 4-13,
5-6, A-13, A-16
Rectangular to polar, 2-14, 2-15,
A-16, A-17
REGEQ (regression equation),
9-4 to 9-5, 9-15, A-26
Regression, 9-4, 9-5, 9-14 to 9-16
Relational operators, 2-16
REMAINDER?, 2-82, 2-11, A-14, A-15
Reserved variables, A-26
Resolving, GS-3, 12-4

R (Cont.)

Recalls, 9-6, 9-7
RETURN, 10-7, 10-10, A-13
rnd, 2-7, 2-8, A-13, B-9
ROUND, 2-10, A-17
 Running programs, 10-5
R-Prg, **R-Prg**, 2-14, 2-15, A-15, A-16

S

SCATTER plot, 9-18, 9-20
SCI MODE, 1-7, 1-9, 1-10, A-16
 Scientific notation, 1-7, 1-9, 1-10, A-16
Secd, 1-8
 Selecting from a menu, C5-4, 1-17
 Selecting functions, 1-19, 4-8, 5-4
SECl, 8-2, 8-6, 8-8, 8-10, A-16
 Sequence
 generating, 8-2, 8-6, 8-8, 8-10, A-16
 product, 8-10
 sum, 8-10
SEQUENTIAL mode, 1-9, 1-11, 4-4, A-16
SHAde, 7-1, 7-8, A-16, A-17
SHADE, 7-1, 7-2, 7-3, 7-7, A-17
SHADE, **Y=**, 7-2, 7-3, 7-8, A-17
sX, **sY**, 9-17, A-26
S(VARS) menu, 1-19, 9-17
sX, **sY**, **sX²**, **sY²**, **sXY**, 9-16, 9-17, A-26
SIMP, 3-1, 3-8, A-17
SIMPL, 1-9, 1-11, 4-4, A-17
SIN, **SIN⁻¹**, 2-4, A-17, B-9
 Size, 2-4, A-17, B-9
 Smart Graph, 4-11, 4-14, 5-5
SORTA, **SORTC**, 8-6, 9-9, 9-13, A-17
 Sorting lists, 8-6, 9-3, 9-13
 Square $\sqrt{}$, 2-5, A-18, B-9
 Square Window, 4-2, 4-15, 4-17, A-19
 Standard deviation, 9-17
 Standard Window, 4-2, 4-9, 4-15, 4-17, A-19
STAT error, B-13
STAT CALC menu, 9-14 to 9-17

S (Cont.)

STAT EDIT menu, 9-9 to 9-13
STAT list editor, 9-2 to 9-7, 9-9 to 9-13
STAT MARK menu, 9-20, 9-23
STAT PLOT error, B-11
STAT PLOTS, 9-18 to 9-20
STAT TYPE menu, 9-18 to 9-21
 Statistics, 1-19, 9-1 to 9-24
 analysis, 9-2 to 9-7, 9-8, 9-14 to 9-17
 calculators, 9-2 to 9-7, 9-14 to 9-16
 data, 9-9 to 9-11
 in programs, 9-22
 plotting, 9-18 to 9-21, 9-23, 9-24
 results, 1-19, 9-17
 variables, 1-19, 9-17
STOP, 10-7, 10-10, A-18
 Stopping, 1-7, 10-6, 10-7, 10-10
 Store \rightarrow , 1-13, 8-1, 8-4, A-18
 Storing, 1-13, 1-16, 8-1, 8-4
 Subroutines, 10-10, 10-14
 Subtraction $-$, 2-4, A-18
SUM, 8-9, 8-10, A-18
 Summation, 8-10, A-18
 Sum of a sequence, 8-10
SX, **SY**, 9-17, A-26
SYNTAX error, B-13
 System variables, A-26

T

T variable, 5-1, 5-4, 6-3, A-26
 Tables, C5-6 to C8-10, 6-1 to 6-6
TABLE SETUP screen, 6-2, 6-1
 Table variables, 1-19, 6-3, 6-5
TAN, **TAN⁻¹**, 2-4, A-18, A-19, B-9
TBLMn, 1-19, 6-2, 6-3, 6-5
TEST menu, 2-16
THEN, 10-7, 10-8, A-19
 T variable, 1-13, A-26
TIME TMR, 5-4, 5-5, B-13
TRACE, 4-11, 4-14, A-19
 Trace, C5-12, 4-13, 4-14, 5-6, 9-21
 Trig functions, 2-3
TSTEP, 5-4, 5-5, 5-6, B-8, B-13

..... T (Cont.)

Turning functions on and off,
1-19, 4-8, 5-4

Turning the TI-80 on and off,
OS-3, 1-2

2-VAR STATS, 9-14, 9-15, A-19

Two-variable statistics, 9-14,
9-15, A-19

..... U

UNDEFINED error, B-13

..... V

Variables, x, 1-12, 1-13, A-26

VARS menu, 1-19

VERTICAL, 7-3, 7-5, A-19

Vertical line, 7-5

Viewing rectangle, viewing window,
See Windows

..... W

Warranty information, B-16

Windows, OS-13, 1-19, 4-9 to 4-10,
4-15 to 4-18, 5-3 to 5-6,
9-21, A-26, B-8

WINDOW RANGE error, B-13

..... X

X,T key, 1-8, 4-5, 7-3

X, 9-17, A-26

X, 4-5, 4-11 to 4-13, 6-3, A-26, B-11

X² functions, 1-19, 5-3, A-26

XFACT variable, 4-16

XL (Y-list), 9-15, 9-18, 9-20

XMAX, XMIN, XSC1, 4-9, 4-13, 4-6,
4-10, 4-12, 4-17, 5-2, 5-4,
9-19, A-26, B-8, B-12, B-13

XY (VARS) menu, 1-19, 9-17

XYLINE, 9-18, 9-20, 9-21

..... Y

Y, 9-17, A-26

Y, 4-11 to 4-13, A-26, B-11

Y-VARS menu, 1-19

..... Y (Cont.)

Y₀, 1-19, 4-5 to 4-7, 10-12, A-26

Y1, Y2, Y3, 9-14, 9-15, A-26

Y_T functions, 1-19, 5-3, A-26

Y₀ editor, 1-19, 4-5 to 4-7, 5-3, 6-4,
A-26

Y_n functions, See Y₀, X_T, functions

YFACT variable, 4-16, 4-18

YL (Y-list), 9-15, 9-18, 9-20

YMAX, YMIN, YSC1, 4-9, 4-10, 4-12,
4-13, 4-17, 5-2, 5-4, 9-19,
A-26, B-8, B-12, B-13

..... Z

ZBOX, 4-15, A-19

ZDECIMAL, 4-15, 4-17, A-19

ZOOM, OS-13, 1-18, 4-15 to 4-18,
5-6

ZOOM error, B-13

ZOOM FACTORS, 4-18

ZOOM IN, 4-15, 4-16

ZOOM menu, 4-15 to 4-17

ZOOM OUT, 4-15, 4-16

ZSQUARE, 4-2, 4-15, 4-17, A-19

ZSTANDARD, 4-15, 4-17, 5-6, A-19

ZTRG, 4-15, 4-17, A-19

ATEL, 6-2, 6-3, 6-5, 4-18, 4-19, 6-6

AR, AR, 4-10, 4-17, A-26, B-8

E, 2-9

eX, eY, 9-17, A-26

Z (VARS) menu, 1-19, 9-17

ZX, ZY, ZX², ZY², ZXY, 9-17, A-26

B, 1-12, A-26

